

# Well Construction Log

Sheet: 1 of 12

Date Started:	01/11/2020	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15
Date Completed:	01/16/2020	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2103151.55	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst:	A. & H. Amezguita	Borehole Diameter:	15.5-18 inches	
Logger:	Ellen Redner	Static Water Level:	See Log for Depths	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	6/29/2020	
Total Depth:	232.6 ft bgs	Well Completion:	<input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
1			NR		(0.0 - 30.0') 10" SHUR-GRIP SDR17 PVC Casing		
2					(0.0 - 4.0') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(0.0 - 4.0') 9.8 bags	(0.0 - 4.0') 10 bags (102%) Note: Temporary backfill sand to fill annular space prior to vault installation.
3		Topock - Fill	SP				
4							
5							
6							
7							
8							
9							
10					(4.0 - 17.1') Portland Cement 3% Bentonite Type I, II and V and Hydrogel	(4.0 - 17.1') 119.7 gallons	(4.0 - 17.1') 105 gallons (88%) Note: Grout seal
11		Topock - Fill	SP				
12							
13							
14							
15							
16					(15.5 - 16.5') Centralizer		
17							
18		Topock - Alluvium Deposits	SM		(17.1 - 22.0') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(17.1 - 22.0') 12 bags	(17.1 - 22.0') 12 bags (100%) Note: Transition sand between filter pack and grout seal.
19							
20							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezcuita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
21		Topock - Alluvium Deposits	SM		(17.1 - 22.0') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(17.1 - 22.0') 12 bags	(17.1 - 22.0') 12 bags (100%) Note: Transition sand between filter pack and grout seal.
22							
23		Topock - Alluvium Deposits	GW-GM		(0.0 - 30.0') 10" SHUR-GRIP SDR17 PVC Casing		
24							
25			NR				
26							
27							
28		Topock - Alluvium Deposits	ML				
29							
30					(30.0 - 55.3') 10" 25-Slot 316L SS Wire Wrap Screen		
31					(22.0 - 58.6') Cemex #2/16 Mesh (16x30) Lapis Lustre Sand	(22.0 - 58.6') 89.4 bags	(22.0 - 58.6') 122 bags (136%) Note: Filter pack. Used >20% of the calculated volume due to potential voids forming during drilling. Swabbed for approximately 60 minutes prior to adding additional well materials.
32							
33							
34	IRZ-15-VAS-32-37 (13 ppb) 11/1/2018 13:00	Topock - Alluvium Deposits	GM				
35							
36							
37							
38							
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezcuita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
41		Topock - Alluvium Deposits	GM		(30.0 - 55.3') 10" 25-Slot 316L SS Wire Wrap Screen		
42							
43							
44							
45							
46		Topock - Alluvium Deposits	GM				
47							
48							
49					(22.0 - 58.6') Cemex #2/16 Mesh (16x30) Lapis Lustre Sand	(22.0 - 58.6') 89.4 bags	(22.0 - 58.6') 122 bags (136%) Note: Filter pack. Used >20% of the calculated volume due to potential voids forming during drilling. Swabbed for approximately 60 minutes prior to adding additional well materials.
50							
51							
52							
53							
54							
55							
56					(55.3 - 150.3') 10" SHUR-GRIP SDR17 PVC Casing		
57		Topock - Alluvium Deposits	GM				
58							
59					(58.6 - 59.8') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(58.6 - 59.8') 2.9 bags	(58.6 - 59.8') 4 bags (138%) Note: Transition sand between filter pack and intermediate seal. Used >20% of the calculated volume due to potential voids
60							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezcuita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
61					(55.3 - 150.3') 10" SHUR-GRIP SDR17 PVC Casing		forming during drilling.
62							
63							
64	IRZ-15-VAS-62-67 (0.459 J ppb) 11/2/2018 12:30	Topock - Alluvium Deposits	GM				
65							
66							
67							
68							
69							
70		Topock - Alluvium Deposits	GW-GM		(59.8 - 140.9') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(59.8 - 140.9') 133.2 buckets	(59.8 - 140.9') 184 buckets (138%) Note: Intermediate seal. Used >20% of the calculated volume due to potential voids forming during drilling.
71							
72							
73							
74							
75		Topock - Alluvium Deposits	SW-SM		(74.5 - 75.5') Centralizer		
76							
77							
78							
79							
80					(78.8 - 98.4') 18.0" Borehole		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

# Well Construction Log

Sheet: 5 of 12

Date Started:	01/11/2020	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15
Date Completed:	01/16/2020	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2103151.55	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst:	A. & H. Amezcuita	Borehole Diameter:	15.5-18 inches	
Logger:	Ellen Redner	Static Water Level:	See Log for Depths	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	6/29/2020	
Total Depth:	232.6 ft bgs	Well Completion:	<input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
81		Topock - Alluvium Deposits	SW-SM		(55.3 - 150.3') 10" SHUR-GRIP SDR17 PVC Casing		
82							
83							
84							
85							
86		Topock - Alluvium Deposits	GM				
87							
88							
89							
90					(59.8 - 140.9') Bentonite seal pellets Pel-Plug (TR30) 3/8"		
91							
92							
93							
94							
95							
96		Topock - Alluvium Deposits	SM				
97							
98							
99							
100					(98.4 - 116.7') 16.0" Borehole		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

# Well Construction Log

Sheet: 6 of 12

Date Started:	01/11/2020	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15
Date Completed:	01/16/2020	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2103151.55	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst:	A. & H. Amezguita	Borehole Diameter:	15.5-18 inches	
Logger:	Ellen Redner	Static Water Level:	See Log for Depths	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	6/29/2020	
Total Depth:	232.6 ft bgs	Well Completion:	<input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
101	IRZ-15-VAS-102-107 ( $< 0.17$ U ppb) 11/3/2018 16:15	Topock - Alluvium Deposits	SM		(55.3 - 150.3') 10" SHUR-GRIP SDR17 PVC Casing		
102							
103		Topock - Alluvium Deposits	SM				
104							
105		Topock - Alluvium Deposits	ML		(98.4 - 116.7') 16.0" Borehole		
106							
107							
108							
109		Topock - Alluvium Deposits	GM		(59.8 - 140.9') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(59.8 - 140.9') 133.2 buckets	(59.8 - 140.9') 184 buckets (138%) Note: Intermediate seal. Used >20% of the calculated volume due to potential voids forming during drilling.
110							
111							
112							
113		Topock - Alluvium Deposits	ML		(116.7 - 137.3') 16.0" Borehole		
114							
115							
116							
117		Topock - Alluvium Deposits	ML				
118							
119							
120							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively



Date Started:	01/11/2020	Surface Elevation:	480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed:	01/16/2020	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2103151.55	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst:	A. & H. Amezcuita	Borehole Diameter:	15.5-18 inches	
Logger:	Ellen Redner	Static Water Level:	See Log for Depths	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	6/29/2020	
Total Depth:	232.6 ft bgs	Well Completion:	<input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
121		Topock - Alluvium Deposits	GM		(55.3 - 150.3') 10" SHUR-GRIP SDR17 PVC Casing		
122							
123		Topock - Alluvium Deposits	ML				
124							
125							
126							
127							
128							
129							
130					(59.8 - 140.9') Bentonite seal pellets Pel-Plug (TR30) 3/8"		
131							
132		Topock - Alluvium Deposits	GM				
133							
134	IRZ-15-VAS-132-137 ( $< 0.17$ U ppb) 11/4/2018 12:40						
135					(134.5 - 135.5') Centralizer	(59.8 - 140.9') 133.2 buckets	(59.8 - 140.9') 184 buckets (138%) Note: Intermediate seal. Used >20% of the calculated volume due to potential voids forming during drilling.
136							
137							
138		Topock - Alluvium Deposits	ML				
139					(137.3 - 158.1') 16.0" Borehole		
140			SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezguita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
141		Topock - Alluvium Deposits	SM		(55.3 - 150.3') 10" SHUR-GRIP SDR17 PVC Casing	(59.8 - 140.9') 133.2 buckets	
142					(140.9 - 142.1') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(140.9 - 142.1') 2.1 bags	(140.9 - 142.1') 3 bags (143%) Note: Transition sand between filter pack and intermediate seal. Used >20% of the calculated volume due to potential voids forming during drilling.
143							
144							
145		Topock - Alluvium Deposits	SM				
146							
147							
148							
149						(137.3 - 158.1') 16.0" Borehole	
150					(150.3 - 200.2') 10" 30-Slot 316L SS Wire Wrap Screen		
151					(142.1 - 207.5') Cemex #2/12 Mesh (12x20) Lapis Lustre Sand	(142.1 - 207.5') 112.8 bags	(142.1 - 207.5') 153 bags (136%) Note: Filter pack. Used >20% of the calculated volume due to potential voids forming during drilling. Swabbed for approximately 105 minutes prior to adding additional well materials, during swabbing well casing dropped approximately 0.5 ft. bgs.
152							
153							
154							
155							
156							
157							
158							
159					(158.1 - 177.8') 16.0" Borehole		
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively









Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezcuita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
161	IRZ-15-VAS-162-167 (3200 ppb) 11/5/2018 13:00	Topock - Alluvium Deposits	SM		(150.3 - 200.2') 10" 30-Slot 316L SS Wire Wrap Screen		
162		Topock - Alluvium Deposits	ML				
163		Topock - Alluvium Deposits	SM				
164		Topock - Alluvium Deposits	SM				
165		Topock - Alluvium Deposits	SM				
166		Topock - Alluvium Deposits	SM				
167		Topock - Alluvium Deposits	SM				
168		Topock - Alluvium Deposits	SM				
169		Topock - Alluvium Deposits	SM				
170		Topock - Alluvium Deposits	SM		(142.1 - 207.5') Cemex #2/12 Mesh (12x20) Lapis Lustre Sand	(142.1 - 207.5') 112.8 bags	(142.1 - 207.5') 153 bags (136%) Note: Filter pack. Used >20% of the calculated volume due to potential voids forming during drilling. Swabbed for approximately 105 minutes prior to adding additional well materials, during swabbing well casing dropped approximately 0.5 ft. bgs.
171		Topock - Alluvium Deposits	SM				
172		Topock - Alluvium Deposits	SM				
173		Topock - Alluvium Deposits	GM				
174		Topock - Alluvium Deposits	GM				
175		Topock - Alluvium Deposits	GM				
176		Topock - Alluvium Deposits	GM				
177		Topock - Alluvium Deposits	GM				
178		Topock - Alluvium Deposits	GM				
179		Topock - Alluvium Deposits	GM		(177.8 - 197.3') 16.0" Borehole		
180		Topock - Alluvium Deposits	GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezcuita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
181	IRZ-15-VAS-182-187 (140 ppb) 11/6/2018 11:10	Topock - Alluvium Deposits	GM		(150.3 - 200.2') 10" 30-Slot 316L SS Wire Wrap Screen		
182							
183							
184							
185							
186							
187		Topock - Alluvium Deposits	ML				
188							
189		Topock - Alluvium Deposits	ML		(177.8 - 197.3') 16.0" Borehole		
190							
191		Topock - Alluvium Deposits	ML		(142.1 - 207.5') Cemex #2/12 Mesh (12x20) Lapis Lustre Sand	(142.1 - 207.5') 112.8 bags	(142.1 - 207.5') 153 bags (136%) Note: Filter pack. Used >20% of the calculated volume due to potential voids forming during drilling. Swabbed for approximately 105 minutes prior to adding additional well materials, during swabbing well casing dropped approximately 0.5 ft. bgs.
192							
193							
194							
195		Topock - Alluvium Deposits	SM				
196							
197							
198							
199		Topock - Alluvium Deposits	SM		(197.3 - 218.0') 16.0" Borehole		
200							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively



Date Started: 01/11/2020	Surface Elevation: 480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed: 01/16/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2103151.55	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst: A. & H. Amezguita	Borehole Diameter: 15.5-18 inches	
Logger: Ellen Redner	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/29/2020	
Total Depth: 232.6 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
201		Topock - Alluvium Deposits	SM		(202.0 - 203.0') Centralizer		(142.1 - 207.5') 153 bags (136%) Note: Filter pack. Used >20% of the calculated volume due to potential voids forming during drilling. Swabbed for approximately 105 minutes prior to adding additional well materials, during swabbing well casing dropped approximately 0.5 ft. bgs.
202							
203					(142.1 - 207.5') Cemex #2/12 Mesh (12x20) Lapis Lustre Sand	(142.1 - 207.5') 112.8 bags	
204							
205					(200.2 - 205.9') Sump and PVC End Cap		
206		Topock - Alluvium Deposits	ML				(197.3 - 218.0') 16.0" Borehole
207							
208							
209							
210							
211		Topock - Weathered Bedrock - conglomerate	ML				(207.5 - 232.6') 66 buckets (117%) Note: Decommissioned Rathole
212							
213							
214					(207.5 - 232.6') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(207.5 - 232.6') 56.2 buckets	
215							
216							
217							
218							
219							
220					(218.0 - 232.6') 16.0" Borehole		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

# Well Construction Log

Date Started:	01/11/2020	Surface Elevation:	480.53 ft amsl	<b>Well ID: IRZ-15</b>
Date Completed:	01/16/2020	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2103151.55	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615773.15	Location: PG&E Topock, Needles, California
Drilling Asst:	A. & H. Amezguita	Borehole Diameter:	15.5-18 inches	
Logger:	Ellen Redner	Static Water Level:	See Log for Depths	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	6/29/2020	
Total Depth:	232.6 ft bgs	Well Completion:	<input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
221	IRZ-15-VAS-222-227 ( $< 0.17$ U ppb) 11/7/2018 14:00	Topock - Weathered Bedrock - conglomerate	ML			(207.5 - 232.6') 56.2 buckets	(207.5 - 232.6') 66 buckets (117%) Note: Decommissioned rathole
222							
223							
224							
225							
226					(207.5 - 232.6') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(218.0 - 232.6') 16.0" Borehole	
227							
228							
229							
230							
231							
232							
233	End of Boring at 232.6 ft bgs.						
234							
235							
236							
237							
238							
239							
240							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
1		NR			(0.0 - 2.0') (NR)	(0.0') Confirmed drill casing was centered on the pilot borehole prior to drilling. (0.5 - 25.0') Soft drilling	(0.0 - 59.7') 1079 gallons of water used; 1000 gallons of water recovered; 79 gallons of water lost
2					(2.0 - 7.0') Topock - Fill; Poorly graded sand (SP); yellowish brown / moderate yellowish brown (10YR 5/4)		
3							
4							
5		SP					
6							
7					(7.0 - 17.0') Topock - Fill; Poorly graded sand (SP); brown (10YR 4/3)		
8							
9							
10	(0.0 - 19.7) 1.65 mins/ft			(0.0 - 19.7') 18.0" Steel Casing		(10.0') Observed trace amounts of Cemex #60 and Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
11							
12		SP					
13							
14							
15							
16							
17					(17.0 - 22.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark yellowish brown (10YR 4/4)		
18							
19		SM					
20							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
21		SM				(20.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
22							
23		GW-GM			(22.5 - 23.5') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); (10Y 3/2)		
24					(23.5 - 27.0') (NR)		
25		NR					
26							
27					(27.0 - 29.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); brown (10YR 4/3)		
28		ML					
29							
30	(19.7 - 40.5) 2.69 mins/ft			(19.7 - 40.5') 18.0" Steel Casing	(29.5 - 47.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (10YR 5/3)	(30.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
31							
32							
33							
34							
35		GM					
36							
37							
38							
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval



# Drilling Log

Sheet: 3 of 12

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
41	(19.7 - 40.5) 2.69 mins/ft			(19.7 - 40.5') 18.0" Steel Casing		(40.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
42						(42.0 - 55.0') Soft drilling	
43							
44			GM				
45							
46							
47							
48					(47.0 - 57.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); grayish brown (10YR 5/2)		
49							
50	(40.5 - 59.7) 2.63 mins/ft			(40.5 - 59.7') 18.0" Steel Casing		(50.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
51							
52			GM				
53							
54							
55							
56							
57							
58					(57.0 - 69.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 5/3) and reddish brown (5YR 5/3)		
59			GM				
60							(59.7 - 79.8') 1683

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
61						(60.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	gallons of water used; 1920 gallons of water recovered; 237 gallons of water gained
62							
63							
64							
65							
66							
67							
68							
69							
70	(59.7 - 78.8) 3.03 mins/ft	GM		(59.7 - 78.8') 18.0" Steel Casing	(69.5 - 74.5') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); brown (7.5YR 4/3)	(70.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
71							
72							
73							
74							
75							
76							
77							
78							
79							
80	(78.8 - 98.4) 3.98 mins/ft	GW-GM		(78.8 - 98.4') 18.0" Steel Casing	(74.5 - 87.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 4/3)	(79.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

# Drilling Log






Sheet: 5 of 12

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
81						(80.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	(79.8 - 98.4') 534 gallons of water used; 5000 gallons of water recovered; 4466 gallons of water gained
82							
83							
84		SW-SM					
85							
86							
87							
88					(87.0 - 97.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 4/3)		
89	(78.8 - 98.4) 3.98 mins/ft			(78.8 - 98.4') 18.0" Steel Casing		(90.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
90							
91						(91.0 - 95.0') Smooth drilling	
92		GM					
93							
94							
95							
96							
97							
98					(97.0 - 104.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4)		
99	(98.4 - 116.7) 2.82 mins/ft	SM		(98.4 - 116.7') 16.0" Steel Casing		(98.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	(98.4 - 177.8') 9300 gallons of water used; 9000 gallons of water recovered; 300 gallons of water lost
100							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description  (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
101	(98.4 - 116.7) 2.82 mins/ft	SM		(98.4 - 116.7') 16.0" Steel Casing		(100.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
102						(101.0 - 108.0') Rough drilling	
103							
104							
105		SM			(104.5 - 106.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown (5YR 4/4)		
106							
107		ML			(106.5 - 116.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown (5YR 4/4)		
108							
109							
110							
111	(110.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.						
112	(111.0 - 113.0') Rough drilling						
113							
114							
115							
116					(115.0 - 116.0') Rough drilling		
117	(116.7 - 137.3) 2.18 mins/ft	GM		(116.7 - 137.3') 16.0" Steel Casing	(116.0 - 117.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4)		
118		ML			(117.0 - 120.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown (5YR 4/4)		
119							
120							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezcuita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
121		GM			(120.0 - 121.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4)	(120.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
122					(121.0 - 127.0') Topock - Alluvium Deposits; Gravelly silt with sand (ML); reddish brown / moderate brown (5YR 4/4)		
123							
124		ML					
125							
126							
127							
128					(127.0 - 137.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4)		
129	(116.7 - 137.3) 2.18 mins/ft			(116.7 - 137.3') 16.0" Steel Casing			
130						(130.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
131							
132		GM					
133							
134							
135							
136							
137							
138					(137.0 - 139.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); reddish brown / moderate brown (5YR 4/4)		
139	(137.3 - 158.1) 1.63 mins/ft	ML		(137.3 - 158.1') 16.0" Steel Casing			
140		SM			(139.5 - 144.5') Topock -		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

# Drilling Log

Sheet: 8 of 12

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
141					Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4)	(140.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
142							
143							
144							
145					(144.5 - 161.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4)		
146							
147							
148						(147.0 - 151.0') Rough drilling	
149	(137.3 - 158.1) 1.63 mins/ft			(137.3 - 158.1') 16.0" Steel Casing			
150							
151						(150.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
152							
153							
154							
155							
156							
157							
158							
159	(158.1 - 177.8) 1.29 mins/ft			(158.1 - 177.8') 16.0" Steel Casing			
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

IRZ DRILLING LOG PG&amp;E TOPOCK C:\USERS\SMC\GRAND\DOCUMENTS\PG&amp;E TOPOCK\DRIFT BORING LOGS\GINT FILES\07\_28\_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 07/28/20 16:13



Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
161		SM				(160.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
162					(161.0 - 164.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); dark reddish brown (2.5YR 3/3)		
163		ML					
164							
165					(164.5 - 167.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4)	(165.0 - 172.0') Drill rods chattering	
166		SM					
167					(167.0 - 172.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4)		
168							
169	(158.1 - 177.8) 1.29 mins/ft	SM		(158.1 - 177.8') 16.0" Steel Casing		(170.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
170							
171							
172					(172.0 - 174.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4)		
173		GM					
174							
175					(174.5 - 187.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4)		
176							
177		GM				(177.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
178							
179	(177.8 - 197.3) 1.53 mins/ft			(177.8 - 197.3') 16.0" Steel Casing			(177.8 - 232.6') 4900 gallons of water used; 8674 gallons of water recovered; 3774 gallons of water gained
180							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock,
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		California
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
181						(180.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
182							
183							
184							
185							
186							
187							
188							
189	(177.8 - 197.3) 1.53 mins/ft						
190							
191							
192							
193							
194							
195							
196							
197							
198							
199	(197.3 - 218.0) 1.28 mins/ft						
200							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	Project Number: RC000753.0051	
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone		
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
201					(200.0 - 206.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4)	(200.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
202							
203							
204		SM					
205							
206							
207					(206.5 - 212.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown (2.5YR 4/4)		
208							
209	(197.3 - 218.0) 1.28 mins/ft	ML		(197.3 - 218.0') 16.0" Steel Casing			
210						(210.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
211							
212					(212.0 - 232.6') Topock - Weathered Bedrock - conglomerate; Sandy silt with gravel (ML); red (2.5YR 4/6)		
213							
214							
215							
216		ML					
217							
218							
219	(218.0 - 232.6) 1.09 mins/ft			(218.0 - 232.6') 16.0" Steel Casing			
220							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

# Drilling Log

Date Started:	12/19/2019	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15</b>	
Date Completed:	01/16/2020	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	232.6 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Topock, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	Project Number:	RC000753.0051
Drilling Asst:	A. & H. Amezguita	Drill Bit:	15 5/8" & 17 5/8" Tricone		
Tool-Pusher:	Arnold Lamon	Depth to First Water:	26.0 ft bgs		
Rig Geologist:	Ellen Redner	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description  (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
221	(218.0 - 232.6) 1.09 mins/ft	ML		(218.0 - 232.6') 16.0" Steel Casing		(220.0') Observed trace amounts of Cemex #3 MESH (8x10) Lapis Luster Sand in drill cuttings.	
222							
223							
224							
225							
226							
227							
228							
229							
230							
231							
232							
233	End of Boring at 232.6 ft bgs.						
234							
235							
236							
237							
238							
239							
240							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	10/31/2018	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15 Pilot</b>	
Date Completed:	11/13/2018	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Topock, California
Driller Name:	Nick Petrone	Depth to First Water:	26.0 ft bgs		
Drilling Asst:	T. Aylmer/J. Candelaria	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	A. Garcia / C.Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
1	0				NR		(0.0 - 2.0') No recovery (NR); not logged during hand clearing	(0.0 - 5.0') Attempted to hand clear for utility clearance.	(0.0 - 257.0') No water used
2									
3									
4									
5	60			Topock - Fill	SP		(2.0 - 7.0') Topock - Fill; Poorly graded sand (SP); yellowish brown / moderate yellowish brown (10YR 5/4); very fine grained to medium grained, angular to round; little coarse to very coarse grained sand, angular to round; trace granule to small pebbles, subround; trace silt; trace clay; dry		
6									
7									
8									
9									
10									
11									
12				Topock - Fill	SP		(7.0 - 17.0') Topock - Fill; Poorly graded sand (SP); brown (10YR 4/3); very fine grained to medium grained, angular to round; little coarse to very coarse grained sand, angular to round; trace granule to small pebbles, subround; trace silt; trace clay; dry		
13	120								
14									
15									
16									
17									
18	78			Topock - Alluvium Deposits	SM		(17.0 - 22.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark yellowish brown (10YR 4/4); very fine grained to very coarse grained, angular to subangular; some granule to large pebble, angular to subangular; some very fine to very coarse grained sand, angular to subround; some silt; trace clay; dry	(17.0 - 27.0') Core barrel and sediments were hot	
19									
20									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
21	78			Topock - Alluvium Deposits	SM				
22									
23				Topock - Alluvium Deposits	GW-GM		(22.5 - 23.5') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); very dark grayish brown (10YR 3/2); granules to large pebbles, angular to subangular; little very fine to very coarse grained sand, angular; little silt; trace granule to small pebbles, subangular; moist		
24							(23.5 - 27.0') (NR); No recovery core barrel was hot and melted the sample bag part of the core fell through the rig deck into the hopper.		
25	120				NR				
26									
27		IRZ-15-SS-25-30 11/14/2018 11:55		Topock - Alluvium Deposits	ML		(27.0 - 29.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); brown (10YR 4/3); medium plasticity; little granules to very large pebbles, angular to subangular; little very fine to very coarse grained sand, angular to subangular; trace clay; wet	(27.0') Approximate depth of water table	
28									
29	300								
30									
31		IRZ-15-SS-30-35 11/14/2018 12:03					(29.5 - 47.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (10YR 5/3); granules to medium pebbles, angular to subangular; and silt; little very fine to very coarse grained sand, subangular to round; trace large pebbles, angular to subangular; wet		
32									
33			IRZ-15-VAS-32-37 (13 ppb) 11/1/2018 13:00	Topock - Alluvium Deposits	GM				
34									
35									
36									
37		IRZ-15-SS-35-40 11/14/2018 12:15							
38									
39									
40									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag



Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
41									
42		IRZ-15-SS-40-45							
43		11/14/2018 12:24		Topock - Alluvium Deposits	GM				
44									
45									
46									
47		IRZ-15-SS-45-50							
48		11/14/2018 12:43					(47.0 - 57.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); grayish brown (10YR 5/2); granules to medium pebbles, angular to subangular; some very fine to very coarse grained sand, subangular to rounded; little large to very large pebbles, angular to subangular; little silt; trace subangular; wet		
49									
50	300								
51									
52		IRZ-15-SS-50-55		Topock - Alluvium Deposits	GM				
53		11/14/2018 13:23							
54									
55									
56									
57		IRZ-15-SS-55-60							
58		11/14/2018 13:32		Topock - Alluvium Deposits	GM		(57.0 - 69.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 5/3) and reddish brown (5YR 5/3); granules to medium pebbles, angular to subangular; some very fine to very coarse grained sand, subangular to round; little large to very large pebbles, angular to subangular; little silt; trace subangular; wet		
59									
60									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

# Boring Log

Sheet: 4 of 13

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
61									
62		IRZ-15-SS-60-65 11/14/2018 15:58							
63	300								
64			IRZ-15-VAS-62-67 (0.459 J ppb) 11/2/2018 12:30	Topock - Alluvium Deposits	GM				
65									
66									
67		IRZ-15-SS-65-70 11/15/2018 09:30							
68									
69									
70							(69.5 - 74.5') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); brown (7.5YR 4/3); granules to large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; little silt; trace very large pebbles, angular; trace subangular; wet		
71									
72	96	IRZ-15-SS-70-75 11/15/2018 09:40		Topock - Alluvium Deposits	GW-GM				
73									
74									
75							(74.5 - 87.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 4/3); very fine grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subangular; little silt; wet		
76									
77		IRZ-15-SS-75-80 11/15/2018 09:45		Topock - Alluvium Deposits	SW-SM				
78	108								
79									
80									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
81									
82		IRZ-15-SS-80-85							
83		11/15/2018 09:50							
84	108			Topock - Alluvium Deposits	SW-SM				
85									
86									
87		IRZ-15-SS-85-90							
88		11/15/2018 09:58							
89									
90									
91									
92	96	IRZ-15-SS-90-95		Topock - Alluvium Deposits	GM				
93		11/15/2018 10:05							
94									
95									
96									
97		IRZ-15-SS-95-100							
98		11/15/2018 10:15							
99	96			Topock - Alluvium Deposits	SM				
100									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
101	96	IRZ-15-SS-100-105 12/6/2018 10:25	IRZ-15-VAS-102-107 ( $< 0.17$ U ppb) 11/3/2018 16:15	Topock - Alluvium Deposits	SM				
102									
103									
104									
105	300	IRZ-15-SS-105-110 11/15/2018 11:00		Topock - Alluvium Deposits	SM		(104.5 - 106.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown (5YR 4/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebble, angular; some silt; trace angular; wet		
106									
107							(106.5 - 116.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown (5YR 4/4); medium plasticity; some granules to very large pebble, angular to subangular; some very fine to very coarse grained sand, angular to subangular; wet; weak cementation		
108									
109									
110									
111									
112									
113	300	IRZ-15-SS-110-115 11/15/2018 11:20		Topock - Alluvium Deposits	ML				
114									
115									
116									
117				Topock - Alluvium Deposits	GM		(116.0 - 117.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4); granules to very large pebbles, angular to subangular; and silt; little very fine to very coarse grained sand, angular to subangular; wet; weak cementation		
118									
119				Topock - Alluvium Deposits	ML		(117.0 - 120.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown (5YR 4/4); medium plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; wet; weak cementation		
120									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
121				Topock - Alluvium Deposits	GM		(120.0 - 121.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4); granules to very large pebbles, angular to subangular; some silt; little very fine to very coarse grained sand, angular to subangular; wet		
122									
123									
124				Topock - Alluvium Deposits	ML		(121.0 - 127.0') Topock - Alluvium Deposits; Gravelly silt with sand (ML); reddish brown / moderate brown (5YR 4/4); medium plasticity; some granules to very large pebble, angular to subangular; little very fine to very coarse grained sand, angular to subangular; wet; weak cementation		
125									
126									
127									
128									
129	300								
130									
131									
132				Topock - Alluvium Deposits	GM		(127.0 - 137.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; some silt; wet; weak cementation; pebbles composed of metadiorite		
133									
134			IRZ-15-VAS-132-137 (< 0.17 U ppb) 11/4/2018 12:40						
135									
136									
137									
138	96			Topock - Alluvium Deposits	ML		(137.0 - 139.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); reddish brown / moderate brown (5YR 4/4); low plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; wet; weak cementation		
139									
140					SM		(139.5 - 144.5') Topock - Alluvium Deposits; Silty sand with gravel		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; Notes: apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>	
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>		
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client:	<u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project:	<u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location:	<u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>		
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number:	<u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>		
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
141							(SM); reddish brown (2.5YR 4/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular; little silt; trace angular; wet		
142		IRZ-15-SS-140-145		Topock - Alluvium Deposits	SM				
143	96	11/15/2018 11:25							
144									
145							(144.5 - 161.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular; some silt; trace angular; wet		
146									
147		IRZ-15-SS-145-150					(147'); increase in granules and very large pebbles, decrease in silt		
148		11/15/2018 11:30							
149									
150									
151									
152	96	IRZ-15-SS-150-150		Topock - Alluvium Deposits	SM				
153		11/15/2018 12:40							
154									
155							(154.5'); decrease in silt, trace clay		
156									
157									
158		IRZ-15-SS-155-160							
159	96	11/15/2018 12:45							
160									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag



Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
161	96	IRZ-15-SS-160-165 11/15/2018 12:50	IRZ-15-VAS-162-167 (3200 ppb) 11/5/2018 13:00	Topock - Alluvium Deposits	SM		(161.0 - 164.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); dark reddish brown (2.5YR 3/3); no plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; wet; weak cementation		
162				Topock - Alluvium Deposits	ML				
163				Topock - Alluvium Deposits	SM				
164	114	IRZ-15-SS-165-170 11/15/2018 13:05		Topock - Alluvium Deposits	SM		(164.5 - 167.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular; some silt; trace angular; wet		
165				Topock - Alluvium Deposits	SM				
166				Topock - Alluvium Deposits	SM				
167	108	IRZ-15-SS-170-175 11/15/2018 13:15		Topock - Alluvium Deposits	SM		(167.0 - 172.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular; some silt; trace angular; trace clay; wet		
168				Topock - Alluvium Deposits	SM				
169				Topock - Alluvium Deposits	SM				
170				Topock - Alluvium Deposits	GM		(172.0 - 174.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; some silt; wet; weak cementation		
171				Topock - Alluvium Deposits	GM				
172				Topock - Alluvium Deposits	GM				
173				Topock - Alluvium Deposits	GM		(174.5 - 187.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; some silt; wet; weak cementation		
174				Topock - Alluvium Deposits	GM				
175				Topock - Alluvium Deposits	GM				
176				Topock - Alluvium Deposits	GM				
177				Topock - Alluvium Deposits	GM				
178				Topock - Alluvium Deposits	GM				
179				Topock - Alluvium Deposits	GM				
180				Topock - Alluvium Deposits	GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
181									
182		IRZ-15-SS-180-185 11/15/2018 13:27		Topock - Alluvium Deposits	GM				
183	108								
184			IRZ-15-VAS-182-187 (140 ppb) 11/6/2018 11:10						
185									
186									
187		IRZ-15-SS-185-190 11/15/2018 13:25		Topock - Alluvium Deposits	ML		(187.0 - 189.5') Topock - Alluvium Deposits; Gravelly silt with sand (ML); reddish brown (2.5YR 4/4); no plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; wet; weak cementation		
188									
189									
190				Topock - Alluvium Deposits	ML		(189.5 - 192.0') Topock - Alluvium Deposits; Gravelly silt with sand (ML); reddish brown (2.5YR 4/4); no plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; wet; weak cementation		
191									
192	108	IRZ-15-SS-190-195 11/15/2018 13:30		Topock - Alluvium Deposits	ML		(192.0 - 197.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown (2.5YR 4/4); no plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; wet; weak cementation		
193									
194									
195									
196									
197		IRZ-15-SS-195-200 11/15/2018 13:35		Topock - Alluvium Deposits	SM		(197.0 - 200.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark reddish brown (2.5YR 3/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular; some silt; trace angular; trace clay; wet	(197.0 - 202.0') Interval is coarse grained and very saturated	
198	108								
199									
200									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
201	108	IRZ-15-SS-200-205 11/15/2018 13:45		Topock - Alluvium Deposits	SM		(200.0 - 206.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (2.5YR 4/4); very fine grained to very coarse grained, angular to subangular; some granules to very large pebble, angular; some silt; trace angular; trace clay; wet		
202									
203									
204									
205	108	IRZ-15-SS-205-210 11/15/2018 13:50		Topock - Alluvium Deposits	ML		(206.5 - 212.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown (2.5YR 4/4); low plasticity; some very fine to very coarse grained sand, angular to subround; little granules to very large pebbles, angular to subangular; trace clay; wet; weak cementation		
206									
207									
208									
209	108	IRZ-15-SS-210-215 11/15/2018 14:00		Topock - Weathered Bedrock - conglomerate	ML		(212.0 - 232.0') Topock - Weathered Bedrock - conglomerate; Sandy silt with gravel (ML); red (2.5YR 4/6); medium plasticity; little granules to very large pebbles, angular to subangular; little very fine to very coarse grained sand, angular to subround; trace clay; wet; weak cementation		
210									
211									
212									
213	96	IRZ-15-SS-215-220 11/15/2018 14:05		Topock - Weathered Bedrock - conglomerate	ML				
214									
215									
216									
217	96								
218									
219									
220									




Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/31/2018	Surface Elevation:	480.53 ft amsl	<b>Boring No.: IRZ-15 Pilot</b>	
Date Completed:	11/13/2018	Northing (NAD83):	2103151.55		
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Topock, California
Driller Name:	Nick Petrone	Depth to First Water:	26.0 ft bgs		
Drilling Asst:	T. Aylmer/J. Candelaria	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	A. Garcia / C. Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
221	96		IRZ-15-VAS-222-227 ( $< 0.17$ U ppb) 11/7/2018 14:00	Topock - Weathered Bedrock - conglomerate	ML				
222									
223									
224									
225									
226	60						(227.0 - 232.0'); some very fine to very coarse grained sand, angular to subround; little clay; wet; decrease in silt		
227									
228									
229									
230									
231	60								
232									
233									
234									
235									
236	108								
237									
238									
239									
240									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/31/2018</u>	Surface Elevation:	<u>480.53 ft amsl</u>	<b>Boring No.: <u>IRZ-15 Pilot</u></b>
Date Completed:	<u>11/13/2018</u>	Northing (NAD83):	<u>2103151.55</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615773.15</u>	Client: <u>PG&amp;E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>257 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Boart Longyear Track</u>	Borehole Diameter:	<u>6-12 inches</u>	Location: <u>PG&amp;E Topock, Topock, California</u>
Driller Name:	<u>Nick Petrone</u>	Depth to First Water:	<u>26.0 ft bgs</u>	
Drilling Asst:	<u>T. Aylmer/J. Candelaria</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>A. Garcia / C.Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
241	108			Topock - Weathered Bedrock - conglomerate	SM				
242									
243									
244									
245									
246									
247	108			Topock - Weathered Bedrock - conglomerate	SM		(247.0 - 255.0') Topock - Weathered Bedrock - conglomerate; Silty sand with gravel (SM); red (2.5YR 4/6); very fine grained to medium grained, angular to subround; some granules to very large pebbles, angular; some silt; trace coarse to very coarse grained sand, subangular to round; trace clay; moist		
248									
249									
250									
251									
252									
253									
254									
255									
256									
257				Topock - Competent Bedrock - conglomerate			(255.0 - 257.0') Topock - Competent Bedrock - conglomerate; red (2.5YR 4/6); friable		
End of Boring at 257.0 ft bgs.									
258									
259									
260									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion; U = not detected above the laboratory reporting limit, J - estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the collection of samples from the temporary well; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
1			NR		(0.0 - 0.5') Steel Plate		Note: Steel plate BMPs in place
2					(0.5 - 4.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(0.5 - 4.0') 6.3 bags	(0.5 - 4.0') 4 bags (63%) Note: Surface seal sand. Used <20% of the calculated volume due to loose dredge sands collapsing during removal of 12 inch conductor casing.
3							
4		Topock - Fill	SP				
5							
6							
7							
8							
9							
10							
11							
12		Topock - Fill	SP		(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(4.0 - 227.0') 99.3 bags	(4.0 - 227.0') 89 bags (90%) Note: Backfill sand
13							
14							
15							
16							
17							
18		Topock - Alluvium Deposits	SM		(9.0 - 257.0') 6" Borehole		
19							
20							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole









Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	<b>Well ID: IRZ-15 Pilot</b>
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
21		Topock - Alluvium Deposits	SM				
22							
23		Topock - Alluvium Deposits	GW-GM				
24							
25			NR				
26							
27							
28		Topock - Alluvium Deposits	ML				
29							
30					(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(9.0 - 257.0') 6" Borehole	(4.0 - 227.0') 89 bags (90%) Note: Backfill sand
31							
32							
33							
34	IRZ-15-VAS-32-37 (13 ppb) 11/1/2018 13:00	Topock - Alluvium Deposits	GM				
35							
36							
37							
38							
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole



Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction			Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
41		Topock - Alluvium Deposits	GM						
42									
43									
44									
45									
46									
47									
48									
49									
50									
51		Topock - Alluvium Deposits	GM				(4.0 - 227.0') 99.3 bags	(4.0 - 227.0') 89 bags (90%) Note: Backfill sand	
52									
53									
54									
55									
56									
57									
58									
59									
60									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
61							
62							
63							
64	IRZ-15-VAS-62-67 (0.459 J ppb) 11/2/2018 12:30	Topock - Alluvium Deposits	GM				
65							
66							
67							
68							
69							
70		Topock - Alluvium Deposits	GW-GM		(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(9.0 - 257.0') 6" Borehole	(4.0 - 227.0') 99.3 bags
71							(4.0 - 227.0') 89 bags (90%) Note: Backfill sand
72							
73							
74							
75		Topock - Alluvium Deposits	SW-SM				
76							
77							
78							
79							
80							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction			Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
81		Topock - Alluvium Deposits	SW-SM						
82									
83									
84									
85									
86		Topock - Alluvium Deposits	GM		<p>(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis</p>	<p>(9.0 - 257.0') 6" Borehole</p>	<p>(4.0 - 227.0') 99.3 bags</p>	<p>(4.0 - 227.0') 89 bags (90%) Note: Backfill sand</p>	
87									
88									
89									
90									
91									
92									
93									
94									
95									
96		Topock - Alluvium Deposits	SM						
97									
98									
99									
100									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	<b>Well ID: IRZ-15 Pilot</b>
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C. Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
101	IRZ-15-VAS-102-107 ( $< 0.17$ U ppb) 11/3/2018 16:15	Topock - Alluvium Deposits	SM				
102		Topock - Alluvium Deposits	SM				
103		Topock - Alluvium Deposits	SM				
104		Topock - Alluvium Deposits	SM				
105		Topock - Alluvium Deposits	SM		(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(9.0 - 257.0') 6" Borehole	(4.0 - 227.0') 99.3 bags
106		Topock - Alluvium Deposits	SM				
107		Topock - Alluvium Deposits	SM				
108		Topock - Alluvium Deposits	SM				
109		Topock - Alluvium Deposits	SM				
110		Topock - Alluvium Deposits	SM				
111		Topock - Alluvium Deposits	SM				
112		Topock - Alluvium Deposits	SM				
113		Topock - Alluvium Deposits	SM				
114		Topock - Alluvium Deposits	SM				
115		Topock - Alluvium Deposits	SM				
116		Topock - Alluvium Deposits	SM				
117		Topock - Alluvium Deposits	SM				
118		Topock - Alluvium Deposits	SM				
119		Topock - Alluvium Deposits	SM				
120		Topock - Alluvium Deposits	SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	<b>Well ID: IRZ-15 Pilot</b>
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
121		Topock - Alluvium Deposits	GM				
122							
123							
124		Topock - Alluvium Deposits	ML				
125							
126							
127							
128							
129							
130					(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis		
131					(9.0 - 257.0') 6" Borehole		
132		Topock - Alluvium Deposits	GM			(4.0 - 227.0') 99.3 bags	(4.0 - 227.0') 89 bags (90%) Note: Backfill sand
133							
134	IRZ-15-VAS-132-137 ( $< 0.17$ U ppb) 11/4/2018 12:40						
135							
136							
137							
138		Topock - Alluvium Deposits	ML				
139							
140			SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
141		Topock - Alluvium Deposits	SM				
142							
143							
144							
145		Topock - Alluvium Deposits	SM		(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(9.0 - 257.0') 6" Borehole	(4.0 - 227.0') 99.3 bags
146							
147							
148							
149							
150							
151							
152							
153							
154							
155							
156							
157							
158							
159							
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
161	IRZ-15-VAS-162-167 (3200 ppb) 11/5/2018 13:00	Topock - Alluvium Deposits	SM				
162		Topock - Alluvium Deposits	ML				
163		Topock - Alluvium Deposits	SM				
164		Topock - Alluvium Deposits	SM		(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(9.0 - 257.0') 6" Borehole	(4.0 - 227.0') 99.3 bags
165		Topock - Alluvium Deposits	SM				
166		Topock - Alluvium Deposits	SM				
167		Topock - Alluvium Deposits	SM				(4.0 - 227.0') 89 bags (90%) Note: Backfill sand
168		Topock - Alluvium Deposits	SM				
169		Topock - Alluvium Deposits	SM				
170		Topock - Alluvium Deposits	GM				
171		Topock - Alluvium Deposits	GM				
172		Topock - Alluvium Deposits	GM				
173		Topock - Alluvium Deposits	GM				
174		Topock - Alluvium Deposits	GM				
175		Topock - Alluvium Deposits	GM				
176		Topock - Alluvium Deposits	GM				
177		Topock - Alluvium Deposits	GM				
178		Topock - Alluvium Deposits	GM				
179		Topock - Alluvium Deposits	GM				
180		Topock - Alluvium Deposits	GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole





















Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction		Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume			
181	IRZ-15-VAS-182-187 (140 ppb) 11/6/2018 11:10	Topock - Alluvium Deposits	GM								
182											
183											
184											
185											
186											
187		Topock - Alluvium Deposits	ML								
188											
189		Topock - Alluvium Deposits	ML								
190											
191											
192		Topock - Alluvium Deposits	ML								
193											
194											
195		Topock - Alluvium Deposits	ML								
196											
197											
198		Topock - Alluvium Deposits	SM								
199											
200											

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction			Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
201		Topock - Alluvium Deposits	SM						
202									
203									
204									
205									
206									
207		Topock - Alluvium Deposits	ML						
208									
209									
210									
211									
212		Topock - Weathered Bedrock - conglomerate	ML						
213									
214									
215									
216									
217									
218									
219									
220									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	Well ID: IRZ-15 Pilot
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
221	IRZ-15-VAS-222-227 ( $< 0.17$ U ppb) 11/7/2018 14:00	Topock - Weathered Bedrock - conglomerate	ML		(4.0 - 227.0') Cemex #3 MESH (8x10) Lapis Lustre Sand Lapis	(4.0 - 227.0') 99.3 bags	(4.0 - 227.0') 89 bags (90%) Note: Backfill sand
222							
223							
224							
225							
226							
227		Topock - Weathered Bedrock - conglomerate	SM		(227.0 - 232.0') Wildcat Washed Plastering Sand	(227.0 - 232.0') 1.4 bags	(227.0 - 232.0') 3 bags (214%) Note: Indicator sand. Used >20% of the calculated volume due to potential voids forming during drilling.
228							
229							
230							
231							
232							
233							
234							
235							
236							
237							
238							
239		Topock - Weathered Bedrock - conglomerate	SM		(232.0 - 247.0') Bentonite seal chips Puregold medium chips	(232.0 - 247.0') 4.4 bags	(232.0 - 247.0') 6 bags (136%) Note: Decommissioned rathole. After placement of 6 bags of bentonite chips and tagged at 238 ft, the bentonite expanded to 202 ft. bgs in the casing, the over chipped portion was cleaned out of the casing to 232 ft bgs
240							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	11/13/2018	Surface Elevation:	480.53 ft amsl	<b>Well ID: IRZ-15 Pilot</b>
Date Completed:	11/15/2018	Northing (NAD83):	2103151.55	
Drilling Co.:	Cascade	Easting (NAD83):	7615773.15	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	257 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Nick Petrone	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Aylmer/J. Candelaria	Depth to First Water:	26.0 ft bgs	
Logger:	A. Garcia / C.Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
241							
242							
243		Topock - Weathered Bedrock - conglomerate	SM		(232.0 - 247.0') Bentonite seal chips Puregold medium chips	(232.0 - 247.0') 4.4 bags	(232.0 - 247.0') 6 bags (136%) Note: Decommissioned rathole. After placement of 6 bags of bentonite chips and tagged at 238 ft, the bentonite expanded to 202 ft. bgs in the casing, the over chipped portion was cleaned out of the casing to 232 ft bgs
244							
245							
246							
247							
248		Topock - Weathered Bedrock - conglomerate	SM		(9.0 - 257.0') 6" Borehole		
249							
250							
251							
252		Topock - Weathered Bedrock - conglomerate	SM		(247.0 - 257.0') 100% Portland Cement Type I. II and V	(247.0 - 257.0') 15.7 gallons	(247.0 - 257.0') 35 gallons (223%) Note: Decommissioned rathole. Used >20% of the calculated volume due to potential voids forming during drilling and grout migration into the formation.
253							
254							
255							
256		Topock - Competent Bedrock - conglomerate					
257							
258							
259							
260							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit, J = estimated value, NR = no recovery; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole