








Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylor	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume		
1		Topock - Fluvial Deposits	GW-GM		(0.0 - 49.0') 10" SHUR-GRIP SDR17 PVC Casing		(0.0 - 5.0') 30 bags (120%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling.		
2								(0.0 - 5.0') Cemex #0/30 sand	(0.0 - 5.0') 25 bags
3									
4		Topock - Fluvial Deposits	SP-SM						
5									
6		Topock - Fluvial Deposits	SM						
7									
8		Topock - Fluvial Deposits	SM						
9									
10							(0.0 - 23.3') 24.0" Borehole		
11									
12					(5.0 - 34.5') Portland Cement 3% Bentonite Type I, II and V with Hydrogel				
13						(5.0 - 34.5') 439.1 gallons	(5.0 - 34.5') 485.3 gallons (111%) Note: Grout seal		
14		Topock - Fluvial Deposits	SM						
15									
16		Topock - Fluvial Deposits	SM						
17									
18		Topock - Fluvial Deposits	GM						
19									
20									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylor	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
21		Topock - Fluvial Deposits	GM		(0.0 - 49.0') 10" SHUR-GRIP SDR17 PVC Casing		
22					(0.0 - 23.3') 24.0" Borehole		
23							
24							
25		Topock - Fluvial Deposits	SM		(5.0 - 34.5') Portland Cement 3% Bentonite Type I, II and V with Hydrogel	(5.0 - 34.5') 439.1 gallons	(5.0 - 34.5') 485.3 gallons (111%) Note: Grout seal
26							
27							
28							
29		Topock - Fluvial Deposits	SM		(23.3 - 40.0') 18.0" Borehole		
30							
31							
32							
33		Topock - Fluvial Deposits	SM		(34.5 - 35.5') Centralizer		
34					(34.5 - 37.2') Bentonite seal chips	(34.5 - 37.2') 4.3 bags	(34.5 - 37.2') 7 bags (163%) Note: Seal between sand and grout, used >20% of the calculated volume due to potential voids forming during drilling.
35					Puregold medium chips		
36							
37		Topock - Fluvial Deposits	SM		(37.2 - 40.3') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(37.2 - 40.3') 6.9 bags	(37.2 - 40.3') 7 bags (101%) Note: Transition sand
38							
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylor	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
41					(0.0 - 49.0') 10" SHUR-GRIP SDR17 PVC Casing		
42							
43		Topock - Alluvium Deposits	SM				
44							
45							
46							
47							
48					(40.3 - 73.3') Cemex # 1 C (16x40) Lapis Lustre Sand		
49							
50					(49.0 - 71.0') 10" 316L Stainless Steel Wire Wrap (20-slot) Screen		
51							
52		Topock - Alluvium Deposits	GM				
53	IRZ-20-VAS-51-56 (150 ppb) 10/20/2018 11:40						
54							
55							
56							
57		Topock - Alluvium Deposits	SM				
58							
59		Topock - Alluvium Deposits	SM				
60							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylor	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume			
61		Topock - Alluvium Deposits	SM		(49.0 - 71.0') 10" 316L Stainless Steel Wire Wrap (20-slot) Screen					
62										
63										
64										
65		Topock - Alluvium Deposits	ML							
66										
67								(40.3 - 73.3') 74.6 bags		
68										
69		Topock - Alluvium Deposits	ML							
70								(59.8 - 78.9') 18" Borehole		
71										
72								(71.0 - 136.0') 10" SHUR-GRIP SDR17 PVC Casing		
73		Topock - Alluvium Deposits	ML							
74										
75								(73.3 - 75.4') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(73.3 - 75.4') 4.7 bags	(73.3 - 75.4') 6 bags (128%) Note: Transition sand, used >20% of the calculated volume due to potential voids forming during drilling.
76										
77		Topock - Alluvium Deposits	ML							
78								(75.4 - 125.6') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(75.4 - 125.6') 90.9 buckets	(75.4 - 125.6') 148 buckets (163%) Note: Intermediate seal, used >20% of the calculated volume due to potential voids forming during drilling.
79										
80								(78.9 - 99.9') 18" Borehole		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylors	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
81	IRZ-20-VAS-82-87 (<0.033 U ppb) 10/21/2018 14:45	Topock - Alluvium Deposits	ML		(79.5 - 80.5') Centralizer		
82							
83							
84							
85							
86							
87							
88		Topock - Alluvium Deposits	SM				
89							
90					(75.4 - 125.6') Bentonite seal pellets Pel-Plug (TR30) 3/8"		
91							
92							
93							
94							
95							
96							
97							
98							
99							
100							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylors	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
101					(71.0 - 136.0') 10" SHUR-GRIP SDR17 PVC Casing		
102							
103		Topock - Alluvium Deposits	SM				
104							
105							
106							
107							
108		Topock - Alluvium Deposits	SM				
109							
110					(75.4 - 125.6') Bentonite seal pellets Pel-Plug (TR30) 3/8"		
111							
112							
113		Topock - Alluvium Deposits	ML				
114	IRZ-20-VAS-112-117 (<0.17 U ppb) 10/22/2018 14:02						
115							
116							
117							
118		Topock - Alluvium Deposits	ML				
119							
120							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started:	04/12/2019	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20
Date Completed:	04/23/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102761.41	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylor	Borehole Diameter:	18-24 inches	
Logger:	David Cornell	Static Water Level:	See Log for Depths	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	5/30/2019	
Total Depth:	188.1 ft bgs	Well Completion:	<input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
121		Topock - Alluvium Deposits	ML		(119.5 - 120.5') Centralizer		
122							
123		Topock - Alluvium Deposits	GM		(75.4 - 125.6') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(75.4 - 125.6') 90.9 buckets	(75.4 - 125.6') 148 buckets (163%) Note: Intermediate seal, used >20% of the calculated volume due to potential voids forming during drilling.
124							
125		Topock - Alluvium Deposits	ML				
126					(125.6 - 127.2') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(125.6 - 127.2') 3.5 bags	(125.6 - 127.2') 4 bags (114%) Note: Transition sand
127							
128		Topock - Alluvium Deposits	ML				
129							
130					(119.9 - 139.9') 18" Borehole		
131							
132							
133	IRZ-20-SS-131-136 (<0.17 U ppb) 10/23/2018 13:25	Topock - Alluvium Deposits	SM		(127.2 - 163.3') Cemex #1 C (16x40) Lapis Lustre Sand	(127.2 - 163.3') 86 bags	(127.2 - 163.3') 123 bags (143%) Note: Filter pack, used >20% of the calculated volume due to potential voids forming during drilling. Swabbed filter pack for approximately 75 minutes prior to installation of additional annular materials.
134							
135							
136							
137					(136.0 - 155.0') 10" 316L Stainless Steel Wire Wrap (20-slot) Screen		
138		Topock - Weathered Bedrock - conglomerate	SM				
139							
140							



Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylors	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
141					(136.0 - 155.0') 10" 316L Stainless Steel Wire Wrap (20-slot) Screen		
142							
143							
144							
145							
146							
147							
148		Topock - Weathered Bedrock - conglomerate	SM				
149							
150					(127.2 - 163.3') Cemex # 1 C (16x40) Lapis Lustre Sand	(127.2 - 163.3') 86 bags	(127.2 - 163.3') 123 bags (143%) Note: Filter pack, used >20% of the calculated volume due to potential voids from during drilling. Swabbed filter pack for approximately 75 minutes prior to installation of additional annular materials.
151							
152							
153							
154							
155							
156							
157							
158		Topock - Weathered Bedrock - conglomerate	ML		(157.0 - 158.0') Centralizer		
159							
160							
					(155.0 - 160.0')		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylors	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
161		Topock - Weathered Bedrock - conglomerate	CL		(127.2 - 163.3') Cemex # 1 C (16x40) Lapis Lustre Sand	(127.2 - 163.3') 86 bags	(127.2 - 163.3') 123 bags (143%) Note: Filter pack, used >20% of the calculated volume due to potential voids froming during drilling. Swabbed filter pack for approximately 75 minutes prior to installation of additional annular materials.
162							
163							
164							
165							
166		Topock - Weathered Bedrock - conglomerate	ML				
167							
168							
169							
170							
171							
172							
173							
174							
175	IRZ-20-VAS-173-178 (<0.83 U ppb) 10/24/2018 14:12						
176							
177							
178							
179							
180							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Date Started: 04/12/2019	Surface Elevation: 497.71 ft amsl	Well ID: IRZ-20
Date Completed: 04/23/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102761.41	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615814.23	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylors	Borehole Diameter: 18-24 inches	
Logger: David Cornell	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 5/30/2019	
Total Depth: 188.1 ft bgs	Well Completion: <input type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input checked="" type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
181		Topock - Competent Bedrock - conglomerate			(179.9 - 180.0') 18" Borehole		
182							
183							
184		Topock - Competent Bedrock - conglomerate			(163.3 - 188.1') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(180.0 - 188.1') 17.5" Borehole	(163.3 - 188.1') 68.6 buckets
185							(163.3 - 188.1') 71 buckets (103%) Note: Decommissioned rathole
186							
187							
188			NR		End of Boring at 188.1 ft bgs.		
189							
190							
191							
192							
193							
194							
195							
196							
197							
198							
199							
200							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured pre-specific capacity for the shallow and deep screens respectively

Drilling Log

Sheet: 1 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylors	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		



Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
1					(0.0 - 4.0') Topock - Fluvial Deposits; Well graded gravel with silt and sand (GW-GM); very pale brown (10YR 8/3)	(0.0 - 8.0') Losing air to the formation, not getting any cuttings back.	(0.0 - 23.3') 400 gallons of water used; 200 gallons of water recovered; 200 gallons of water lost
2		GW-GM					
3							
4							
5		SP-SM			(4.0 - 5.5') Topock - Fluvial Deposits; Poorly graded sand with silt (SP-SM); very pale brown (10YR 8/3)		
6							
7		SM			(5.5 - 7.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3)		
8							
9							
10	(0.0 - 23.3) 10.37 mins/ft	SM		(0.0 - 23.3') 24.0" Steel Casing Note: Removed after during well installation	(7.0 - 13.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3)	(8.0 - 8.5') Started getting fines and water back at 8 ft bgs.	
11							
12							
13							
14		SM			(13.0 - 15.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3)	(13.0 - 13.5') Rough drilling	
15							
16		SM			(15.0 - 17.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3)		
17							
18		GM			(17.0 - 33.0') Topock - Fluvial Deposits; Silty gravel with sand (GM); grayish brown (10YR 5/2)	(17.0 - 17.5') Rough drilling	
19							
20							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Drilling Log

Sheet: 2 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
21	(0.0 - 23.3) 10.37 mins/ft	GM		(0.0 - 23.3') 24.0" Steel Casing Note: Removed after during well installation			(23.3 - 40.0') 200 gallons of water used; 100 gallons of water recovered; 100 gallons of water lost
22						(22.0 - 23.3') Conductor casing down to 23.3 ft bgs.	
23							
24	(23.3 - 40.0) 8.91 mins/ft	SM		(23.3 - 40.0') 18.0" Steel Casing Note: Removed after during well installation			
25						(25.0 - 33.0') Rough drilling	
26							
27							
28							
29							
30							
31							
32							
33							
34						(33.0 - 36.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); brown (10YR 5/3)	
35							
36							
37						(36.0 - 39.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); brown (10YR 4/3)	
38							
39							
40						(39.0 - 47.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (10YR 5/2)	

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Drilling Log

Sheet: 3 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylors	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
41							(40.0 - 59.8') 260 gallons of water used; 100 gallons of water recovered; 160 gallons of water lost
42						(41.0 - 56.0') smooth drilling	
43							
44		SM					
45							
46							
47							
48					(47.0 - 56.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (10YR 4/3)		
49							
50	(40.0 - 59.8) 2.68 mins/ft			(40.0 - 59.8') 18" Steel Casing Note: Removed after during well installation			
51							
52		GM					
53							
54							
55							
56							
57		SM			(56.0 - 57.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark grayish brown / dark yellowish brown (10YR 4/2)		
58					(57.0 - 65.0') Topock - Alluvium Deposits; Silty sand (SM); yellowish brown / moderate yellowish brown (10YR 5/4)		
59		SM					
60							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylors	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
61							(59.8 - 79.9') 500 gallons of water used; 350 gallons of water recovered; 150 gallons of water lost
62							
63		SM					
64							
65					(65.0 - 69.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (10YR 5/3)		
66							
67		ML					
68							
69	(59.8 - 78.9) 4.99 mins/ft			(59.8 - 78.9') 18" Steel Casing Note: Removed after during well installation	(69.0 - 71.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (7.5YR 4/4)		
70		ML					
71					(71.0 - 77.0') Topock - Alluvium Deposits; Silt with sand (ML); brown (7.5YR 4/4)		
72							
73							
74		ML				(74.0 - 75.0') Rough drilling	
75							
76							
77							
78					(77.0 - 83.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (7.5YR 4/4)		
79		ML					
80	(78.9 - 99.9) 3.81 mins/ft						

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Drilling Log

Sheet: 5 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: <u>IRZ-20</u>	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
81		ML					(79.9 - 99.9') 220 gallons of water used; 2600 gallons of water recovered; 2380 gallons of water gained
82							
83					(83.0 - 107.0') Topock - Alluvium Deposits; Silty sand (SM); brown (10YR 4/3)		
84							
85							
86							
87							
88							
89							
90	(78.9 - 99.9) 3.81 mins/ft			(78.9 - 99.9') 18" Steel Casing Note: Removed after during well installation			
91		SM					
92							
93							
94							
95							
96							
97							
98							
99							
100							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Drilling Log

Sheet: 6 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
101							
102							
103							
104		SM					
105							
106							
107							
108		SM			(107.0 - 109.0') Topock - Alluvium Deposits; Sandy silt with gravel (SM); brown (7.5YR 4/3)		
109							
110	(99.9 - 119.9) 5.70 mins/ft			(99.9 - 119.9') 18" Steel Casing Note: Removed after during well installation	(109.0 - 117.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (10YR 4/3)		(99.9 - 119.9') 200 gallons of water used; 5000 gallons of water recovered; 4800 gallons of water gained
111							
112							
113		ML					
114							
115							
116							
117							
118							
119		ML			(117.0 - 123.0') Topock - Alluvium Deposits; Sandy silt (ML); strong brown (7.5YR 4/6)		
120							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

IRZ DRILLING LOG_PG&E TOPOCK C:\USERS\SMCGRANED\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.30.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 12/06/20 21:41

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
121		ML					(119.9 - 139.9') 200 gallons of water used; 4700 gallons of water recovered; 4500 gallons of water gained
122							
123							
124		GM			(123.0 - 124.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); yellowish brown / moderate yellowish brown (10YR 5/4)		
125							
126		ML			(124.5 - 127.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (7.5YR 4/3)		
127							
128							
129		ML			(127.0 - 131.0') Topock - Alluvium Deposits; Sandy silt (ML); reddish brown / moderate brown (5YR 4/4)		
130	(119.9 - 139.9) 4.75 mins/ft			(119.9 - 139.9') 18" Steel Casing Note: Removed after during well installation			
131							
132					(131.0 - 136.5') Topock - Alluvium Deposits; Silty sand (SM); brown (7.5YR 5/3)		
133		SM					
134							
135							
136							
137							
138		SM			(136.5 - 157.0') Topock - Weathered Bedrock - conglomerate; Silty sand (SM); reddish brown (5YR 5/4)		
139							
140							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Drilling Log

Sheet: 8 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: <u>IRZ-20</u>	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylors	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
141							(139.9 - 159.9') 220 gallons of water used; 4900 gallons of water recovered; 4680 gallons of water gained
142							
143							
144							
145							
146							
147							
148							
149		SM					
150	(139.9 - 159.9) 4.95 mins/ft				(139.9 - 159.9') 18" Steel Casing Note: Removed after during well installation		
151							
152							
153							
154							
155							
156							
157							
158		ML			(157.0 - 160.0') Topock - Weathered Bedrock - conglomerate; Sandy silt (ML); brown (7.5YR 5/4)		
159							
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

IRZ DRILLING LOG_PG&E TOPOCK C:\USERS\SMCGRANED\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.30.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 12/06/20 21:41

Drilling Log

Sheet: 9 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles,
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches		California
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	17.5 inch tricone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
161					(160.0 - 166.0') Topock - Weathered Bedrock - conglomerate; Lean clay with sand (CL); brown (10YR 4/3)		(159.9 - 179.9') 200 gallons of water used; 2150 gallons of water recovered; 1950 gallons of water gained
162							
163		CL					
164							
165							
166					(166.0 - 179.5') Topock - Weathered Bedrock - conglomerate; Sandy silt with gravel (ML); dark yellowish brown (10YR 3/6)		
167							
168							
169							
170	(159.9 - 179.9) 3.70 mins/ft			(159.9 - 179.9') 18" Steel Casing Note: Removed after during well installation			
171							
172							
173		ML					
174							
175							
176							
177							
178							
179							
180					(179.5 - 182.0') Topock -		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

IRZ DRILLING LOG_PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.30.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 12/06/20 21:41

Drilling Log

Sheet: 10 of 10

Date Started:	03/31/2019	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20	
Date Completed:	04/12/2019	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	188.1 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	24 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	18 inches	Project Number:	RC000753.0051
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	17.5 inch tricone		
Tool-Pusher:	Arnold Lamon	Depth to First Water:	44.6 ft bgs		
Rig Geologist:	David Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		








Depth (ft)	Drilling Run (ft) and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling notes and observations confirming presence of temporary backfill material in drill cuttings	Drilling Fluid
181	(179.9 - 180.0) mins/ft			(179.9 - 180.0') 18" Steel Casing Note: Removed after during well installation	Competent Bedrock - conglomerate; dark yellowish brown (10YR 4/4)	(179.9 - 188.1') Rough drilling	220 gallons used; 900 gallons recovered; 680 gallons gained
182					(182.0 - 187.0') Topock - Competent Bedrock - conglomerate; yellowish red (5YR 4/6)		
183							
184	(180.0 - 188.1) 6.30 mins/ft			(180.0 - 188.1') 17.5" Open Hole			
185							
186							
187							
188		NR			(187.0 - 188.1') (NR)		

End of Boring at 188.1 ft bgs.

189
190
191
192
193
194
195
196
197
198
199
200




Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: blue water table symbol collected during the first VAS interval of the pilot borehole

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles,
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs		California
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
1	60			Topock - Fluvial Deposits	GW-GM		(0.0 - 4.0') Topock - Fluvial Deposits; Well graded gravel with silt and sand (GW-GM); very pale brown (10YR 8/3); granules to very large pebbles, angular to subround; and very fine to very coarse grained sand, angular to round; little silt; trace angular to subangular; dry		(0.0 - 187.0') No water used
2									
3									
4		Topock - Fluvial Deposits	SP-SM		(4.0 - 5.5') Topock - Fluvial Deposits; Poorly graded sand with silt (SP-SM); very pale brown (10YR 8/3); very fine grained to fine grained, angular to subround; little silt; dry; homogeneous				
5									
6					Topock - Fluvial Deposits	SM			
7									
8	66			Topock - Fluvial Deposits	SM		(7.0 - 13.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3); fine grained to fine grained, angular to round; little silt; dry		
9									
10									
11									
12									
13		Topock - Fluvial Deposits	SM		(13.0 - 15.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3); very fine grained to very coarse grained, angular to subround; little silt; trace granules to very large pebbles, angular to subround; trace angular to subround; dry				
14									
15									
16	Topock - Fluvial Deposits	SM		(15.0 - 17.0') Topock - Fluvial Deposits; Silty sand (SM); very pale brown (10YR 8/3); very fine grained to fine grained, angular to subround; little silt; dry					
17									
18				120			Topock - Fluvial Deposits	GM	
19									
20									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel		
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
21	120			Topock - Fluvial Deposits	GM			(22.0 - 36.0') Open borehole collapsed overnight between 10/18/18 to 10/19/18.	
22									
23									
24									
25									
26									
27									
28									
29									
30									
31	96			Topock - Fluvial Deposits	SM		(33.0 - 36.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); brown (10YR 5/3); very fine grained to coarse grained, angular to round; some silt; little clay; trace granules to very large, angular to subround; dry		
32									
33									
34									
35									
36									
37									
38									
39									
40									
				Topock - Alluvium Deposits	SM		(39.0 - 47.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (10YR 5/2); very fine grained to very coarse grained, angular to subangular; and granule to very large pebbles,		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles,
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs		California
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
41	96			Topock - Alluvium Deposits	SM		angular to subround; little silt; trace clay; dry		
42									
43									
44									
45	114	IRZ-20-SS-45-50 10/30/2018 12:00		Topock - Alluvium Deposits	GM		(47.0 - 56.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (10YR 4/3); granules to large pebbles, angular to subangular; some very fine to coarse grained sand, angular to subround; little silt; moist	(48.0') Soil starts getting moist.	
46									
47									
48									
49									
50									
51									
52									
53									
54									
55	96	IRZ-20-SS-55-60 10/30/2018 12:04		Topock - Alluvium Deposits	SM		(56.0 - 57.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark grayish brown / dark yellowish brown (10YR 4/2); very fine grained to coarse grained, angular to subround; some granule to large pebbles, angular to subangular; some silt; wet		
56									
57									
58									
59									
60									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel		
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
61	96	IRZ-20-SS-60-65 10/30/2018 12:06		Topock - Alluvium Deposits	SM				
62									
63									
64									
65		IRZ-20-SS-65-70 10/30/2018 12:08		Topock - Alluvium Deposits	ML		(65.0 - 69.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (10YR 5/3); no plasticity; some very fine to coarse grained sand, angular to subround; little small pebbles, angular to subangular; moist		
66									
67									
68									
69				Topock - Alluvium Deposits	ML		(69.0 - 71.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (7.5YR 4/4); no plasticity; some fine to coarse grained sand, angular to subround; little granule to small pebbles, angular to subangular; moist		
70									
71									
72									
73		IRZ-20-SS-70-75 10/30/2018 12:10		Topock - Alluvium Deposits	ML		(71.0 - 77.0') Topock - Alluvium Deposits; Silt with sand (ML); brown (7.5YR 4/4); no plasticity; little very fine to coarse grained sand, angular to subround; trace granule to medium pebbles, angular to subangular; trace clay; moist		
74									
75									
76									
77	114	IRZ-20-SS-75-80 10/30/2018 12:12		Topock - Alluvium Deposits	ML		(77.0 - 83.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (7.5YR 4/4); no plasticity; some very fine to medium grained sand, angular to subround; trace granule, angular to subangular; wet		
78									
79									
80									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Boring Log

Sheet: 5 of 10

Date Started:	<u>10/18/2018</u>	Surface Elevation:	<u>497.71 ft amsl</u>	Boring No.: <u>IRZ-20 Pilot</u>
Date Completed:	<u>10/25/2018</u>	Northing (NAD83):	<u>2102761.41</u>	
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615814.23</u>	Client: <u>PG&E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>187 ft bgs</u>	Project: <u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Prosonic Truck Mount</u>	Borehole Diameter:	<u>4-12 inches</u>	Location: <u>PG&E Topock, Needles,</u>
Driller Name:	<u>Eddie Ramoos</u>	Depth to First Water:	<u>44.6 ft bgs</u>	<u>California</u>
Drilling Asst:	<u>T. Alymer/C. Alvarez</u>	Sampling Method:	<u>4 inch x 10 ft. Core Barrel</u>	Project Number: <u>RC000753.0051</u>
Logger:	<u>Connor Mills</u>	Sampling Interval:	<u>Continuous</u>	
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
81									
82		IRZ-20-SS-80-85 10/30/2018 12:14		Topock - Alluvium Deposits	ML				
83									
84	114		IRZ-20-VAS-82-87 (<0.033 U ppb) 10/21/2018 10:37				(83.0 - 107.0') Topock - Alluvium Deposits; Silty sand (SM); brown (10YR 4/3); very fine grained to coarse grained, angular to subround; and silt; little granule to small pebbles, angular to subangular; wet		
85									
86									
87		IRZ-20-SS-85-90 10/30/2018 12:16							
88									
89									
90									
91									
92	132	IRZ-20-SS-90-95 10/30/2018 12:18		Topock - Alluvium Deposits	SM				
93									
94									
95									
96									
97		IRZ-20-SS-95-100 11/30/2018 12:20							
98									
99	120								
100									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	<u>10/18/2018</u>	Surface Elevation:	<u>497.71 ft amsl</u>	Boring No.: <u>IRZ-20 Pilot</u>	
Date Completed:	<u>10/25/2018</u>	Northing (NAD83):	<u>2102761.41</u>		
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615814.23</u>	Client:	<u>PG&E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>187 ft bgs</u>	Project:	<u>Final GW Remedy Phase 1</u>
Drill Rig Type:	<u>Prosonic Truck Mount</u>	Borehole Diameter:	<u>4-12 inches</u>	Location:	<u>PG&E Topock, Needles,</u>
Driller Name:	<u>Eddie Ramoes</u>	Depth to First Water:	<u>44.6 ft bgs</u>		<u>California</u>
Drilling Asst:	<u>T. Alymer/C. Alvarez</u>	Sampling Method:	<u>4 inch x 10 ft. Core Barrel</u>	Project Number:	<u>RC000753.0051</u>
Logger:	<u>Connor Mills</u>	Sampling Interval:	<u>Continuous</u>		
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
101	120	IRZ-20-SS-100-105 10/30/2018 12:22		Topock - Alluvium Deposits	SM				
102									
103									
104									
105	103.2	IRZ-20-SS-105-110 10/30/2018 12:24		Topock - Alluvium Deposits	SM		(107.0 - 109.0') Topock - Alluvium Deposits; Sandy silt with gravel (SM); brown (7.5YR 4/3); fine grained to coarse grained, angular to subround; and silt; little granule to small pebbles, angular to subangular; wet		
106									
107									
108									
109	132	IRZ-20-SS-110-115 10/30/2018 12:26	IRZ-20-VAS-112-117 (<0.17 U ppb) 10/22/2018 14:02	Topock - Alluvium Deposits	ML		(109.0 - 117.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (10YR 4/3); no plasticity; some fine to coarse grained sand, angular to subround; trace granule, angular to subround; trace clay; wet		
110									
111									
112									
113	132	IRZ-20-SS-115-120 10/30/2018 12:28		Topock - Alluvium Deposits	ML		(117.0 - 123.0') Topock - Alluvium Deposits; Sandy silt (ML); strong brown (7.5YR 4/6); no plasticity; little granule to medium pebbles, angular to subangular; little fine to coarse grained sand, angular to subround; wet		
114									
115									
116									
117	132								
118									
119									
120									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles,
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs		California
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
121	132	IRZ-20-SS-120-125 10/30/2018 12:30		Topock - Alluvium Deposits	ML				
122				Topock - Alluvium Deposits	GM		(123.0 - 124.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); yellowish brown / moderate yellowish brown (10YR 5/4); granules to very large pebbles, angular to subangular; some silt; little very fine to coarse grained sand, angular to subangular; moist		
123				Topock - Alluvium Deposits	ML		(124.5 - 127.0') Topock - Alluvium Deposits; Sandy silt (ML); brown (7.5YR 4/3); no plasticity; little granule to medium pebbles, angular to subangular; little fine to coarse grained sand, angular to subround; moist		
124	132	IRZ-20-SS-125-130 10/30/2018 12:32		Topock - Alluvium Deposits	ML		(127.0 - 131.0') Topock - Alluvium Deposits; Sandy silt (ML); reddish brown / moderate brown (5YR 4/4); no plasticity; some fine grained sand, angular to subround; trace granule to small pebbles, angular to subangular; wet		
125				Topock - Alluvium Deposits	ML				
126				Topock - Alluvium Deposits	ML				
127	132	IRZ-20-SS-130-135 10/30/2018 12:34	IRZ-20-VAS-131-136 (<0.17 U ppb) 10/23/2018 12:00	Topock - Alluvium Deposits	SM		(131.0 - 136.5') Topock - Alluvium Deposits; Silty sand (SM); brown (7.5YR 5/3); fine grained to coarse grained, angular to subround; some silt; little granule to medium pebbles, subangular to round; wet		
128				Topock - Alluvium Deposits	SM				
129				Topock - Alluvium Deposits	SM				
130	132	IRZ-20-SS-135-140 10/30/2018 12:36		Topock - Alluvium Deposits	SM		(136.5 - 157.0') Topock - Alluvium Deposits; Silty sand (SM); reddish brown (5YR 5/4); very fine grained to coarse grained, angular to subangular; and silt; little granule to very large pebbles, angular to subangular; wet; granules and pebbles are composed of metadiorite		
131				Topock - Alluvium Deposits	SM				
132				Topock - Alluvium Deposits	SM				
133									
134									
135									
136									
137									
138									
139									
140									



Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles,
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs		California
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
141									
142									
143		IRZ-20-SS-140-145 10/30/2018 12:38							
144	132								
145									
146									
147		IRZ-20-SS-145-150 10/30/2018 12:40							
148				Topock - Alluvium Deposits	SM				
149									
150									
151									
152	132	IRZ-20-SS-150-155 10/30/2018 12:42							
153									
154									
155									
156									
157									
158		IRZ-20-SS-155-160 10/30/2018 12:44							
159	132			Topock - Weathered Bedrock - conglomerate	ML		(157.0 - 160.0') Topock - Weathered Bedrock - conglomerate; Sandy silt (ML); brown (7.5YR 5/4); no plasticity; and fine to coarse grained sand, angular to subround; trace granule, angular to subangular; trace clay; moist	(157.0 - 167.0') Soil core hot and dry, lost approximately 2 ft. of core down hole, tripped back in to retrieve lost core.	
160									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: <u>IRZ-20 Pilot</u>	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles,
Driller Name:	Eddie Ramoos	Depth to First Water:	44.6 ft bgs		California
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
161	132	IRZ-20-SS-160-165 10/30/2018 12:46		Topock - Weathered Bedrock - conglomerate	CL		(160.0 - 166.0') Topock - Weathered Bedrock - conglomerate; Lean clay with sand (CL); brown (10YR 4/3); low plasticity; some small to medium pebbles, angular to subangular; some fine to coarse grained sand, angular to subround; little silt; trace angular to subangular; dry		
162									
163									
164									
165	87.6	IRZ-20-SS-165-170 10/30/2018 12:48		Topock - Weathered Bedrock - conglomerate	ML		(166.0 - 179.5') Topock - Weathered Bedrock - conglomerate; Sandy silt with gravel (ML); dark yellowish brown (10YR 3/6); medium plasticity; some fine to coarse grained sand, angular to subround; little granule to small pebbles, angular to subangular; wet		
166									
167									
168									
169									
170									
171									
172									
173	79.2	IRZ-20-SS-170-175 10/30/2018 12:50		Topock - Weathered Bedrock - conglomerate					
174									
175									
176									
177		IRZ-20-VAS-173-178 (<0.83 U ppb) 10/24/2018 18:52							
178									
179									
180									
							(179.5 - 182.0') Topock - Competent Bedrock - conglomerate;	(177.0 - 182.0') Very rough drilling, had refusal at 182', tripped out and make another run for 182-187'.	

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/18/2018	Surface Elevation:	497.71 ft amsl	Boring No.: IRZ-20 Pilot	
Date Completed:	10/25/2018	Northing (NAD83):	2102761.41		
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Eddie Ramoes	Depth to First Water:	44.6 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	T. Alymer/C. Alvarez	Sampling Method:	4 inch x 10 ft. Core Barrel		
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
181	79.2			Topock - Competent Bedrock - conglomerate			dark yellowish brown (10YR 4/4); dry; moderate cementation; friable		
182									
183		IRZ-20-SS-180-187					(182.0 - 187.0') Topock - Competent Bedrock - conglomerate; yellowish red (5YR 4/6); moist; weak cementation; friable	(182.0 - 187.0')	
184		10/30/2018		Topock - Competent Bedrock - conglomerate				Had to vibrate the core barrel and lost the core downhole, retrieved with flapper bit, sediment were very wet due to lost of core in the borehole.	
185	58.8	12:54							
186									
187									
End of Boring at 187.0 ft bgs.									
188									
189									
190									
191									
192									
193									
194									
195									
196									
197									
198									
199									
200									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction		Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume					
1		Topock - Fluvial Deposits	GW-GM		(0.0 - 0.5') Steel Plate			Note: Steel plates with BMPs in place					
2													
3													
4		Topock - Fluvial Deposits	SP-SM		(0.5 - 10.0') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(0.0 - 9.0') 12" Borehole	(0.5 - 10.0') 7.9 bags	(0.5 - 10.0') 8 bags (101%) Note: Surface sand seal					
5													
6		Topock - Fluvial Deposits	SM										
7													
8													
9		Topock - Fluvial Deposits	SM										
10													
11													
12		Topock - Fluvial Deposits	SM										
13													
14													
15		Topock - Fluvial Deposits	SM		(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.					
16													
17		Topock - Fluvial Deposits	SM										
18													
19													
20		Topock - Fluvial Deposits	GM										

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction			Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume	
21		Topock - Fluvial Deposits	GM				(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
22										
23										
24										
25										
26										
27										
28										
29										
30										
31		Topock - Fluvial Deposits	SM				(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
32										
33										
34										
35		Topock - Fluvial Deposits	SM				(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
36										
37										
38										
39		Topock - Alluvium Deposits	SM				(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
40										

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
41							
42							
43		Topock - Alluvium Deposits	SM				
44							
45							
46							
47							
48							
49							
50					(10.0 - 177.0') Wildcat Washed Plastering Sand		
51							
52		Topock - Alluvium Deposits	GM				
53	IRZ-20-VAS-51-56 (150 ppb) 10/20/2018 11:40						
54							
55							
56							
57		Topock - Alluvium Deposits	SM				
58							
59		Topock - Alluvium Deposits	SM				
60							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoes	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
61		Topock - Alluvium Deposits	SM				
62							
63							
64							
65		Topock - Alluvium Deposits	ML				
66							
67							
68							
69		Topock - Alluvium Deposits	ML		(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags
70							
71							
72							
73		Topock - Alluvium Deposits	ML				
74							
75							
76							
77		Topock - Alluvium Deposits	ML				
78							
79							
80							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
81		Topock - Alluvium Deposits	ML				
82							
83							
84	IRZ-20-VAS-82-87 (<0.033 U ppb) 10/21/2018 10:37						
85							
86							
87							
88							
89							
90					(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used $>20\%$ of the calculated volume due to potential voids forming during drilling.
91		Topock - Alluvium Deposits	SM				
92							
93							
94							
95							
96							
97							
98							
99							
100							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
101		Topock - Alluvium Deposits	SM				
102							
103							
104							
105		Topock - Alluvium Deposits	SM				
106							
107							
108							
109		Topock - Alluvium Deposits	ML		(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags
110							
111							
112							
113	IRZ-20-VAS-112-117 (<0.17 U ppb) 10/22/2018 14:02	Topock - Alluvium Deposits	ML				(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
114							
115							
116							
117		Topock - Alluvium Deposits	ML				
118							
119							
120							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
121		Topock - Alluvium Deposits	ML				
122							
123		Topock - Alluvium Deposits	GM				
124							
125		Topock - Alluvium Deposits	ML				
126							
127							
128		Topock - Alluvium Deposits	ML				
129							
130					(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
131							
132							
133	IRZ-20-VAS-131-136 (<0.17 U ppb) 10/23/2018 12:00	Topock - Alluvium Deposits	SM				
134							
135							
136							
137							
138		Topock - Alluvium Deposits	SM				
139							
140							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
141							
142							
143							
144							
145							
146							
147							
148							
149		Topock - Alluvium Deposits	SM				
150					(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 68 bags (146%) Note: Backfill sand, used >20% of the calculated volume due to potential voids forming during drilling.
151							
152							
153							
154							
155							
156							
157							
158		Topock - Weathered Bedrock - conglomerate	ML				
159							
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
161							
162							
163		Topock - Weathered Bedrock - conglomerate	CL				
164							
165							
166							
167							
168							
169					(10.0 - 177.0') Wildcat Washed Plastering Sand	(9.0 - 177.0') 6" Borehole	(10.0 - 177.0') 46.7 bags
170							
171							
172							
173		Topock - Weathered Bedrock - conglomerate	ML				
174							
175	IRZ-20-VAS-173-178 (<0.83 U ppb) 10/24/2018 18:52						
176							
177							
178					(177.0 - 187.0') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(177.0 - 187.0') 4" Borehole	(177.0 - 187.0') 2.8 bags
179							
180							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Date Started:	10/30/2018	Surface Elevation:	497.71 ft amsl	Well ID: IRZ-20 Pilot
Date Completed:	10/31/2018	Northing (NAD83):	2102761.41	
Drilling Co.:	Cascade	Easting (NAD83):	7615814.23	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	187 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Eddie Ramoos	Borehole Diameter:	4-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	T. Alymer/C. Alvarez	Depth to First Water:	44.6 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
181		Topock - Competent Bedrock - conglomerate					
182							
183					(177.0 - 187.0') Cemex #0/30 Mesh (30x50) Lapis Lustre Sand	(177.0 - 187.0') 4" Borehole	(177.0 - 187.0') 2 bags (71%) Note: Indicator sand, used <20% of the calculated volume due to potential formation collapse.
184		Topock - Competent Bedrock - conglomerate					
185							
186							
187							
188							
189							
190							
191							
192							
193							
194							
195							
196							
197							
198							
199							
200							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, BMP = Best Management Practices for stormwater, U = not detected above the laboratory reporting limit; Notes: blue water table symbol represents depth to water measured during the first VAS interval; granular backfill material was removed during overdrilling of the pilot borehole

Final - Revised
12/6/20