

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylors	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
1		Topock - Fluvial Deposits	SP-SM		(0.0 - 50.1') 10" Suregrip 17 Casing		
2					(0.0 - 4.0') Cemex #0/30 MESH	(0.0 - 4.0') 9 bags	(0.0 - 4.0') 17 bags (89%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling
3							
4							
5		Topock - Fluvial Deposits	SP-SM		(0.0 - 21.2') 18.0" Borehole	(4.0 - 31.1') 211.4 gallons	(4.0 - 31.1') 413 gallons (95%) Note: Type I, II, and V 3% Benseal, grout not tagged will be tagged in morning, used > 20% of the calculated volume due to potential grout migration and voids forming during drilling
6							
7							
8							
9		Topock - Fluvial Deposits	SW-SM		(4.0 - 31.1') Grout		
10							
11							
12							
13		Topock - Fluvial Deposits	SM				
14							
15							
16							
17							
18							
19							
20							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylors	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
21			SM		(0.0 - 50.1') 10" Suregrip 17 Casing		
22							
23							
24							
25							
26		Topock - Fluvial Deposits	ML		(4.0 - 31.1') Grout	(21.2 - 30.0') 18.0" Borehole	(4.0 - 31.1') 211.4 gallons
27							
28							
29							
30							
31						(30.0 - 31.0') 18.0" Borehole	
32							
33					(32.5 - 33.5') Centralizer	(31.1 - 35.1') 6.3 bags	(31.1 - 35.1') 17 bags (170%) Note: Puregold Medium Chips, bentonite installed because of concerns with grout migration due to potential large void from 29 to 32 ft. bgs, used >20% of the calculated volume due to potential voids forming during drilling
34					(31.1 - 35.1') Bentonite seal chips		
35							
36		Topock - Fluvial Deposits	SM			(31.0 - 41.0') 18.0" Borehole	
37							
38					(35.1 - 45.0') Cemex Bunker #6 60 Mesh Lapis Lustre Sand	(35.1 - 45.0') 16.6 bags	(35.1 - 45.0') 51 bags (207%) Note: Lapis Lustre Sand, used >20% of the claulated volume due to potential voids forming during drilling
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylor	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
41		Topock - Fluvial Deposits	GM		(0.0 - 50.1') 10" Suregrip 17 Casing		
42							
43					(35.1 - 45.0') Cemex Bunker #6 60 Mesh Lapis Lustre Sand	(35.1 - 45.0') 16.6 bags	(35.1 - 45.0') 51 bags (207%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling
44							
45		Topock - Fluvial Deposits	GW-GM				
46							
47							
48							
49							
50		Topock - Alluvium Deposits	SM		(50.1 - 67.1') 10" 10-slot 316 SS Wire Wrap Screen		
51							
52							
53					(45.0 - 69.0') Cemex Bunker #11 (30x70) Lapis Lustre Sand	(45.0 - 69.0') 36.5 bags	(45.0 - 69.0') 200 bags (448%) Note: Lapis Lustre Sand, used >20% of calculated volume due to potential voids forming during drilling, swabbed filter pack for approximately 1.5 hours prior to the installation of the bentonite seal
54	IRZ-25-VAS-52-57 (3500 ppb) 12/5/2018 10:40	Topock - Alluvium Deposits	GM				
55							
56							
57							
58		Topock - Alluvium Deposits	ML				
59							
60			GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylor	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
61	IRZ-25-VAS-62-67 (620 ppb) 12/5/2018 14:17	Topock - Alluvium Deposits	GM		(50.1 - 67.1') 10" 10-slot 316 SS Wire Wrap Screen		
62							
63							
64					(45.0 - 69.0') Cemex Bunker #11 (30x70) Lapis Lustre Sand	(45.0 - 69.0') 36.5 bags	(45.0 - 69.0') 200 bags (448%) Note: Lapis Lustre Sand, used >20% of calculated volume due to potential voids forming during drilling, swabbed filter pack for approximately 1.5 hours prior to the installation of the bentonite seal
65							
66		Topock - Alluvium Deposits	SM		(67.1 - 77.1') 10" Suregrip 17 Casing		
67							
68					(68.0 - 69.0') Centralizer		
69							
70					(70.5 - 71.5') Centralizer (69.0 - 74.0') Bentonite seal chips	(61.5 - 81.5') 16.0" Borehole	(69.0 - 74.0') 5.3 bags
71		Topock - Alluvium Deposits	SM				(69.0 - 74.0') 28 bags (428%) Note: Puregold Medium Chips, used >20% of the calculated volume due to potential voids forming during drilling
72							
73							
74							
75							
76		Topock - Alluvium Deposits	GM		(74.0 - 103.8') Cemex #3 Mesh (8x20)	(74.0 - 103.8') 45.3 bags	(74.0 - 103.8') 172 bags (280%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling, filter pack was swabbed for approximately 30 minutes prior to installation of the bentonite seal
77							
78							
79							
80							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylors	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction		Calculated Material Volumes	Material Volumes Installed
81		Topock - Alluvium Deposits	SM			(77.1 - 100.0') 10" 30-slot 316 SS Wire Wrap Screen		
82								
83								
84								
85								
86		Topock - Alluvium Deposits	SM			(74.0 - 103.8') Cemex #3 Mesh (8x20)	(74.0 - 103.8') 45.3 bags	(74.0 - 103.8') 172 bags (280%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling, filter pack was swabbed for approximately 30 minutes prior to installation of the bentonite seal
87								
88								
89								
90								
91	IRZ-25-VAS-92-97 (130 ppb) 12/6/2018 09:07	Topock - Alluvium Deposits	ML			(81.5 - 101.5') 16.0" Borehole		
92								
93								
94								
95								
96		Topock - Alluvium Deposits	SM					
97								
98								
99								
100								

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started: 05/12/2019	Surface Elevation: 500.4 ft amsl	Well ID: IRZ-25
Date Completed: 05/29/2019	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Dual Rotary	Northing (NAD83): 2102414.6	Project: Final GW Remedy Phase 1
Driller Name: Jon Martinez	Easting (NAD83): 7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst: E. Martinez / W. Saylor	Borehole Diameter: 15.5-18 inches	
Logger: D Cornell / K. Keon	Water Level Start: 44.95 ft bgs	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 10/1/2019	
Total Depth: 174 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
101		Topock - Alluvium Deposits	SW-SM		(100.0 - 135.0') 10" Suregrip 17 Casing		
102					(74.0 - 103.8') Cemex #3 Mesh (8x20)		
103		Topock - Alluvium Deposits	ML		(81.5 - 101.5') 16.0" Borehole	(74.0 - 103.8') 45.3 bags	(74.0 - 103.8') 172 bags (280%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling, filter pack was swabbed for approximately 30 minutes prior to installation of the bentonite seal
104							
105							
106		Topock - Alluvium Deposits	GM				
107							
108							
109							
110							
111					(101.5 - 121.5') 16.0" Borehole		
112					(103.8 - 126.0') Bentonite seal chips		
113						(103.8 - 126.0') 23.4 bags	(103.8 - 126.0') 34 bags (45%) Note: Puregold Medium Chips, used >20% of the calculated volume due to potential voids forming during drilling
114	IRZ-25-VAS-112-117 (< 0.17 U ppb) 12/11/2018 10:34	Topock - Alluvium Deposits	SM				
115					(114.5 - 115.5') Centralizer		
116							
117							
118		Topock - Alluvium Deposits	SM				
119							
120			ML				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylors	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
121		Topock - Alluvium Deposits	ML		(100.0 - 135.0') 10" Suregrip 17 Casing		
122					(101.5 - 121.5') 16.0" Borehole		
123					(103.8 - 126.0') Bentonite seal chips	(103.8 - 126.0') 23.4 bags	(103.8 - 126.0') 34 bags (45%) Note: Puregold Medium Chips, used >20% of the calculated volume due to potential voids forming during drilling
124							
125		Topock - Alluvium Deposits	SM				
126							
127		Topock - Alluvium Deposits	GM				
128							
129							
130							
131					(121.5 - 141.5') 16.0" Borehole		
132							
133		Topock - Alluvium Deposits	ML		(126.0 - 174.0') Cemex Bunker #8 0/30 Mesh	(126.0 - 174.0') 67.8 bags	(126.0 - 174.0') 136.7 bags (102%) Note: Lapis Lustre Sand, used >20% of calculated volume due to potential voids forming during redrill of borehole, filter pack entered well through upper screens and removed, swabbed filter pack for approximately 30 minutes prior to installing bentonite seal
134							
135							
136					(135.0 - 166.0') 10" 10-slot 316 SS Wire Wrap Screen		
137							
138		Topock - Alluvium Deposits	ML				
139							
140			ML				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylor	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
141							
142							
143							
144		Topock - Alluvium Deposits	ML				
145							
146							
147							
148							
149	IRZ-25-VAS-147-152 (3600 ppb) 12/11/2018 13:54						
150							
151							
152		Topock - Alluvium Deposits	SM				
153							
154							
155							
156							
157							
158		Topock - Weathered Bedrock - conglomerate	ML				
159							
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Well Construction Log

Date Started:	05/12/2019	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25
Date Completed:	05/29/2019	Shallow Well Elevation:	N/A	
Drilling Co.:	Cascade	Deep Well Elevation:	N/A	Client: PG&E
Drilling Method:	Dual Rotary	Northing (NAD83):	2102414.6	Project: Final GW Remedy Phase 1
Driller Name:	Jon Martinez	Easting (NAD83):	7615824.5	Location: PG&E Topock, Needles, California
Drilling Asst:	E. Martinez / W. Saylor	Borehole Diameter:	15.5-18 inches	
Logger:	D Cornell / K. Keon	Water Level Start:	44.95 ft bgs	Project Number: RC000753.0051
Editor:	Sean McGrane	Development End Date:	10/1/2019	
Total Depth:	174 ft bgs	Well Completion:	<input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
161		Topock - Weathered Bedrock - conglomerate	ML		(135.0 - 166.0') 10" 10-slot 316 SS Wire Wrap Screen		
162							
163							
164	IRZ-25-VAS-162-167 (3000 ppb) 12/13/2018 10:37	Topock - Weathered Bedrock - conglomerate	ML				
165							
166							
167					(126.0 - 174.0') Cemex Bunker #8 0/30 Mesh		
168					(161.5 - 173.0') 15.5" Borehole	(126.0 - 174.0') 67.8 bags	(126.0 - 174.0') 136.7 bags (102%) Note: Lapis Lustre Sand, used >20% of calculated volume due to potential voids forming during redrill of borehole, filter pack entered well through upper screens and removed, swabbed filter pack for approximately 30 minutes prior to installing bentonite seal
169					(168.0 - 169.0') Centralizer		
170		Topock - Competent Bedrock - conglomerate					
171					(166.0 - 171.6') Sump and End Cap		
172							
173							
174					(173.0 - 174.0') 15.5" Borehole		
175					End of Boring at 174.0' bgs.		
176							
177							
178							
179							
180							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, groundwater data was collected during drilling of the pilot borehole

Drilling Log

Sheet: 1 of 9

Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25	
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs		
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
1					(0.0 - 4.5') Topock - Fluvial Deposits; Poorly graded sand with silt and gravel (SP-SM)	(0.0 - 17.0') Drilled with water.	(0.0 - 21.2') 845.46 gallons of water used; 615.18 gallons of water recovered; 230.28 gallons of water lost
2							
3		SP-SM					
4							
5					(4.5 - 12.0') Topock - Fluvial Deposits; Poorly graded sand with silt (SP-SM); pale brown (10YR 6/3)		
6							
7							
8		SP-SM					
9							
10	(0.0 - 21.2) 8.02 mins/ft			(0.0 - 21.2') 18.0" Steel Casing			
11							
12							
13					(12.0 - 17.0') Topock - Fluvial Deposits; Well graded sand with silt and gravel (SW-SM); pale brown (10YR 6/3)		
14		SW-SM					
15							
16							
17							
18					(17.0 - 20.5') Topock - Fluvial Deposits; Silty sand with gravel (SM); brown (10YR 5/3)	(17.0 - 21.2') Rough drilling.	
19		SM					
20							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole






Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25	
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches		
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number:	RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs		
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
21	(0.0 - 21.2) 8.02 mins/ft	SM		(0.0 - 21.2') 18.0" Steel Casing	(20.5 - 32.0') Topock - Fluvial Deposits; Sandy silt with gravel (ML); light yellowish brown (10YR 6/4)		
22						(21.2 - 30.0') Advanced 9 ft during 1st 2 hrs, no advancement during 3rd hour. Volume of waste water declined from beginning to end of drilling run. Possible loss could be from backflow to cuttings and shaker tanks.	(21.2 - 31.0') 1065.06 gallons of water used; -121.6 gallons of water recovered; 1186.66 gallons of water lost
23							
24							
25							
26	(21.2 - 30.0) 23.89 mins/ft	ML		(21.2 - 30.0') 18.0" Steel Casing			
27							
28							
29							
30							
31	(30.0 - 31.0) 197.18 mins/ft			(30.0 - 31.0') 18.0" Steel Casing		(30.0 - 31.0') Borehole only advanced 1 foot in 4 hrs, likely drilling on a boulder.	
32						(31.0 - 41.0') Drilled with water.	(31.0 - 41.0') 1087.02 gallons of water used; 2478 gallons of water recovered; 1390.98 gallons of water gained
33					(32.0 - 40.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); pale brown (10YR 6/3)		
34							
35							
36	(31.0 - 41.0) 12.09 mins/ft	SM		(31.0 - 41.0') 18.0" Steel Casing			
37							
38							
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location: PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number: RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs	
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
41	(31.0 - 41.0) 12.09 mins/ft	GM		(31.0 - 41.0') 18.0" Steel Casing	(40.0 - 41.5') Topock - Fluvial Deposits; Silty gravel with sand (GM); pale brown (10YR 6/3)		
42	(41.0 - 43.0) 8.50 mins/ft			(41.0 - 43.0') 16.0" Steel Casing	(41.5 - 49.5') Topock - Fluvial Deposits; Well graded gravel with silt and sand (GW-GM); light brown (7.5YR 6/4)	(41.0 - 43.0') Drilled with water.	(41.0 - 43.0') 230.58 gallons of water used; 0 gallons of water recovered; 230.58 gallons of water lost
43	(43.0 - 61.5) 7.04 mins/ft	GW-GM		(43.0 - 61.5') 16.0" Steel Casing	(49.5 - 52.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (10YR 5/3)	(43.0 - 61.5') Drilled with water.	(43.0 - 61.5') 684.42 gallons of water used; 526.16 gallons of water recovered; 158.26 gallons of water lost
44							
45							
46							
47							
48							
49							
50							
51							
52							
53							
54							
55							
56							
57					(57.0 - 59.5') Topock - Alluvium Deposits; Sandy silt (ML); reddish brown (5YR 5/4)		
58		ML					
59							
60		GM			(59.5 - 68.0') Topock - Alluvium		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Drilling Log

Sheet: 4 of 9

Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location: PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number: RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs	
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
61	(43.0 - 61.5) 7.04 mins/ft			(43.0 - 61.5') 16.0" Steel Casing	Deposits; Silty gravel with sand (GM); reddish brown (5YR 5/4)		
62						(61.5 - 81.5') Drilled with water.	(61.5 - 81.5') 527.04 gallons of water used; 848.24 gallons of water recovered; 321.2 gallons of water gained
63							
64		GM					
65							
66							
67							
68							
69					(68.0 - 72.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (5YR 5/4)		
70		SM					
71	(61.5 - 81.5) 3.67 mins/ft			(61.5 - 81.5') 16.0" Steel Casing			
72							
73					(72.0 - 77.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); yellowish brown / moderate yellowish brown (10YR 5/4)		
74		SM					
75							
76							
77							
78		GM			(77.0 - 79.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown (5YR 5/4)		
79							
80		SM			(79.5 - 87.0') Topock - Alluvium		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location: PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number: RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs	
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
81	(61.5 - 81.5) 3.67 mins/ft			(61.5 - 81.5') 16.0" Steel Casing	Deposits; Silty sand with gravel (SM); reddish brown (5YR 5/4)		
82						(81.5 - 101.5') Drilled with water.	(81.5 - 101.5') 475.8 gallons of water used; 1816.12 gallons of water recovered; 1340.32 gallons of water gained
83							
84		SM					
85							
86							
87							
88					(87.0 - 94.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (5YR 5/4)		
89							
90							
91	(81.5 - 101.5) 4.60 mins/ft	SM		(81.5 - 101.5') 16.0" Steel Casing			
92							
93							
94							
95		ML			(94.5 - 95.5') Topock - Alluvium Deposits; Gravelly silt (ML); reddish brown (5YR 5/4)		
96		SM			(95.5 - 97.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown (5YR 4/4)		
97							
98		SW-SM			(97.0 - 102.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); light reddish brown / light brown (5YR 6/4)		
99							
100							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location: PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number: RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs	
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
101	(81.5 - 101.5) 4.60 mins/ft	SW-SM		(81.5 - 101.5') 16.0" Steel Casing			
102					(102.0 - 103.5') Topock - Alluvium Deposits; Sandy silt with gravel (ML); light reddish brown / light brown (5YR 6/4)	(101.5 - 121.5') Drilled with water.	(101.5 - 121.5') 325.74 gallons of water used; 4086.84 gallons of water recovered; 3761.1 gallons of water gained
103		ML					
104					(103.5 - 109.5') Topock - Alluvium Deposits; Silty gravel (GM); reddish brown (5YR 5/4)		
105							
106		GM					
107							
108							
109							
110					(109.5 - 117.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); (5YR 4/)		
111	(101.5 - 121.5) 6.21 mins/ft			(101.5 - 121.5') 16.0" Steel Casing			
112							
113		SM					
114							
115							
116							
117							
118		SM			(117.0 - 119.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown (5YR 4/4)		
119							
120		ML			(119.5 - 124.5') Topock - Alluvium		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location: PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	
Drilling Asst:	E. Martinez / W. Saylor	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number: RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs	
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
121	(101.5 - 121.5) 6.21 mins/ft			(101.5 - 121.5') 16.0" Steel Casing	Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown (5YR 4/4)		
122		ML				(121.5 - 141.5') Drilled with water.	(121.5 - 141.5') 118.34 gallons of water used; 1244.4 gallons of water recovered; 1126.06 gallons of water gained
123							
124							
125		SM			(124.5 - 127.0') Topock - Alluvium Deposits; Silty sand (SM); reddish brown / moderate brown (5YR 4/4)		
126							
127							
128		GM			(127.0 - 132.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown (5YR 5/4)	(127.0') During the first attempt of installing the well the lower screen twisted during removal of the drill casing. The well was removed from the borehole and the borehole was redrilled. Cascade recommended not advancing 16 inch casing and install the well in an open hole after redrilling.	(127.0 - 174.0') 280 gallons of water used; 12440 gallons of water recovered; 12160 gallons of water gained
129							
130							
131	(121.5 - 141.5) 1.75 mins/ft			(121.5 - 141.5') 16.0" Steel Casing			
132							
133		ML			(132.0 - 137.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown (5YR 4/4)		
134							
135							
136							
137							
138		ML			(137.0 - 139.5') Topock - Alluvium Deposits; Sandy silt (ML); reddish brown / moderate brown (5YR 4/4)		
139							
140		ML			(139.5 - 147.0') Topock - Alluvium		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater
Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole





Date Started:	04/26/2019	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25
Date Completed:	05/12/2019	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Dual Rotary	Total Depth:	174 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type:	Foremost DR-24 HD	Conductor Casing Diameter:	18 inches	Location: PG&E Topock, Needles, California
Driller Name:	Jon Martinez	Drill Casing Diameter:	16 inches	
Drilling Asst:	E. Martinez / W. Saylors	Drill Bit:	15.5 & 17.5 inch Tri-cone	Project Number: RC000753.0051
Tool-Pusher:	Arnold Lamon	Depth to First Water:	48.4 ft bgs	
Rig Geologist:	A. Mack / D Cornell	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Drilling Run and Average Penetration Rate	USCS Code	USCS Class	Casing Diameter	Description (See Pilot boring log for full geologic descriptions)	Drilling Notes	Drilling Fluid
161	(141.5 - 161.5) 2.10 mins/ft	ML		(141.5 - 161.5') 16" Steel Casing			
162					(162.0 - 166.0') Topock - Weathered Bedrock - conglomerate; Gravelly silt (ML); reddish brown / moderate brown (5YR 4/4)	(161.5 - 173.0') Drilled with water, casing became stuck in bedrock attempted to dislodge while advancing borehole. Circulated water to clean out borehole.	
163		ML					
164							
165							
166							
167	(161.5 - 173.0) 6.22 mins/ft			(161.5 - 173.0') 15.5" Open Hole	(166.0 - 174.0') Topock - Competent Bedrock - conglomerate; reddish brown (5YR 5/4)		
168							
169							
170							
171							
172							
173	(173.0 - 174.0) mins/ft			(173.0 - 174.0') 15.5" Open Hole			
174							
End of Boring at 174.0 'bgs.							
175							
176							
177							
178							
179							
180							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater

Remarks: blue water table symbol represents depth to water measured during the first VAS interval of the pilot borehole

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25-Pilot	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number: RC000753.0051	
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
1	84			Topock - Fluvial Deposits	SP-SM		(0.0 - 4.5') Topock - Fluvial Deposits; Poorly graded sand with silt and gravel (SP-SM); very fine grained to fine grained, subangular to subround; little granules to very large pebbles, angular to subangular; little silt; dry	(7.0') Rough drilling	(0.0 - 172.0') No water used
2							(4.0 - 4.5'); lens of granules to medium pebbles		
3				Topock - Fluvial Deposits	SP-SM		(4.5 - 12.0') Topock - Fluvial Deposits; Poorly graded sand with silt (SP-SM); pale brown (10YR 6/3); very fine grained to fine grained, angular to subround; little silt; trace granules to very large pebbles, angular to round; trace cobbles, subround to round; dry		
4									
5	120			Topock - Fluvial Deposits	SW-SM		(12.0 - 17.0') Topock - Fluvial Deposits; Well graded sand with silt and gravel (SW-SM); pale brown (10YR 6/3); very fine grained to coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; trace cobbles, angular to subangular; trace boulders, angular to subangular; dry	(7.0') Rough drilling	(0.0 - 172.0') No water used
6							(14') very dark grayish brown (10YR 3/2); solid rock cores from boulders of basalt with frothy texture		
7				Topock - Fluvial Deposits	SM		(17.0 - 20.5') Topock - Fluvial Deposits; Silty sand with gravel (SM); brown (10YR 5/3); very fine grained to coarse grained, angular to subangular; some silt; little granules to very large pebbles, angular to subround; trace cobbles, angular to subangular; trace boulders, angular to subangular; dry		
8							(19.0 - 20.5') gray (7.5YR 6/1) and white (10YR 8/1); rock core from boulder composed of metadiorite, very hard		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: <u>IRZ-25-Pilot</u>	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
21	120				SM		(20.5 - 32.0') Topock - Fluvial Deposits; Sandy silt with gravel (ML); light yellowish brown (10YR 6/4); no plasticity; little granules to large pebbles, angular to subround; little very fine to fine grained sand, angular to subround; trace cobbles, angular to subround; trace boulders, angular to subangular; dry		(0.0 - 172.0') No water used
22									
23									
24									
25									
26									
27				Topock - Fluvial Deposits	ML				
28									
29									
30							(29.5'); to 32' powerdized rock and solid cores from boulders composed of metadiorite.		
31									
32	120								
33									
34									
35									
36				Topock - Fluvial Deposits	SM		(32.0 - 40.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); pale brown (10YR 6/3); very fine grained to medium grained, angular to subround; and granules to very large pebbles, subangular to subround; little silt; trace cobbles, angular to subround; dry		
37									
38	108								
39									
40									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: <u>IRZ-25-Pilot</u>	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
41	108			Topock - Fluvial Deposits	GM		(40.0 - 41.5') Topock - Fluvial Deposits; Silty gravel with sand (GM); pale brown (10YR 6/3); granules to very large pebbles, angular to subround; some very fine to medium grained sand, angular to subangular; little silt; trace cobbles, angular to subround; dry		(0.0 - 172.0') No water used
42				Topock - Fluvial Deposits	GW-GM		(41.5 - 49.5') Topock - Fluvial Deposits; Well graded gravel with silt and sand (GW-GM); light brown (7.5YR 6/4); granules to very large pebbles, subangular to subround; some cobbles, angular to subround; little very fine to medium grained sand, angular to round; little silt; dry		
43									
44									
45	114	IRZ-25-SS-47-52 12/14/2018 10:35		Topock - Fluvial Deposits	GW-GM		(47'); moist; to 49.5 ft bgs	(49.5') Approximate depth to water table	
46									
47									
48									
49	120	IRZ-25-SS-52-57 12/14/2018 10:40	IRZ-25-VAS-52-57 (3500 ppb) 12/5/2018 10:40	Topock - Alluvium Deposits	SM		(49.5 - 52.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (10YR 5/3); very fine grained to very coarse grained, subangular to subround; some granules to medium pebbles, angular to subangular; some silt; wet		
50									
51									
52									
53	120	IRZ-25-SS-57-62 12/14/2018 10:45		Topock - Alluvium Deposits	GM		(52.0 - 57.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown (5YR 5/4); angular to subangular; some very fine to coarse grained sand, angular to subangular; some silt; little clay; dry to moist		
54									
55									
56									
57	120	IRZ-25-SS-57-62 12/14/2018 10:45		Topock - Alluvium Deposits	ML		(57.0 - 59.5') Topock - Alluvium Deposits; Sandy silt (ML); reddish brown (5YR 5/4); no plasticity; and very fine to very coarse grained sand, angular to subangular; little granules to small pebble, angular to subangular; wet to dry; stiff; strong cementation		
58									
59									
60									
60					GM		(59.5 - 68.0') Topock - Alluvium Deposits; Silty gravel with sand		





Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location: 1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number: RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous	
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
61	120	IRZ-25-SS-57-62 12/14/2018 10:45		Topock - Alluvium Deposits	GM		(GM); reddish brown (5YR 5/4); granules to very large pebbles, angular to subangular; some very fine to coarse grained sand, angular to subangular; some silt; little clay; dry to moist		(0.0 - 172.0') No water used
62									
63									
64		IRZ-25-SS-62-67 12/14/2018 10:55	IRZ-25-VAS-62-67 (620 ppb) 12/5/2018 14:17						
65	120			Topock - Alluvium Deposits	SM		(68.0 - 72.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (5YR 5/4); very fine grained to very coarse grained, subangular to subround; some silt; little granules to medium pebble, angular to subangular; wet		
66									
67									
68		IRZ-25-SS-67-72 12/14/2018 10:55							
69									
70									
71									
72									
73	60	IRZ-25-SS-72-77 12/14/2018 11:05		Topock - Alluvium Deposits	SM		(72.0 - 77.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); yellowish brown / moderate yellowish brown(10YR 5/4); fine grained to very coarse grained, subangular to subround; some silt; little granules to medium pebble, angular to subround; wet		
74									
75									
76									
77									
78		IRZ-25-SS-77-82 12/14/2018 11:05					(77.0 - 79.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown (5YR 5/4); granules to large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; little silt; wet		
79	60			Topock - Alluvium Deposits	GM				
80							(79.5 - 87.0') Topock - Alluvium Deposits; Silty sand with gravel		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: <u>IRZ-25-Pilot</u>	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
81	60	IRZ-25-SS-77-82 12/14/2018 11:05		Topock - Alluvium Deposits	SM		(SM); reddish brown (5YR 5/4); very fine grained to very coarse grained, subangular to round; little granules to medium pebbles, angular to subangular; little silt; trace cobbles, angular to subangular; wet; cobbles composed of metadiorite		(0.0 - 172.0') No water used
82									
83									
84		IRZ-25-SS-82-87 12/14/2018 11:10							
85									
86									
87				Topock - Alluvium Deposits	SM		(87.0 - 94.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (5YR 5/4); fine grained to very coarse grained, subangular to round; some silt; little granules to medium pebble, angular to subangular; wet; trace large pebbles		
88									
89		IRZ-25-SS-87-92 12/14/2018 11:15							
90									
91									
92	108								
93				IRZ-25-VAS-92-97 (130 ppb) 12/6/2018 09:07			(94.5 - 95.5') Topock - Alluvium Deposits; Gravelly silt (ML); reddish brown (5YR 5/4); no plasticity; little granules to medium pebble, angular to subangular; little very fine to very coarse grained sand, angular to subangular; dry to moist; hard; pebbles composed of metadiorite		
94		IRZ-25-SS-92-97 12/14/2018 11:20							
95			Topock - Alluvium Deposits				ML		
96			Topock - Alluvium Deposits				SM		
97				Topock - Alluvium Deposits	SW-SM		(95.5 - 97.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown(5YR 4/4); very fine grained to very coarse grained, angular to subround; some granules to large pebble, angular to subangular; some silt; trace cobbles; wet; cobbles composed of metadiorite		
98	114	IRZ-25-SS-97-102 12/14/2018 11:25							
99									
100									







Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: <u>IRZ-25-Pilot</u>	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
101	114	IRZ-25-SS-97-102 12/14/2018 11:25		Topock - Alluvium Deposits	SW-SM				(0.0 - 172.0') No water used
102									
103				Topock - Alluvium Deposits	ML		(102.0 - 103.5') Topock - Alluvium Deposits; Sandy silt with gravel (ML); light reddish brown / light brown(5YR 6/4); little granules to large pebbles, angular to subangular; little very fine to very coarse grained sand, subangular to subround; little clay; trace cobbles; wet; 100 mm cobble composed of metadiorite		
104		IRZ-25-SS-102-107 12/14/2018 11:30					(103.5 - 109.5') Topock - Alluvium Deposits; Silty gravel (GM); reddish brown (5YR 5/4); granules to large pebbles, angular to subround; some silt; little very fine to very coarse grained sand, angular to subround; trace; wet; trace very large pebble		
105	120								
106									
107				Topock - Alluvium Deposits	GM				
108									
109	120	IRZ-25-SS-107-112 12/14/2018 11:35							
110									
111									
112									
113	120								
114		IRZ-25-SS-112-117 12/14/2018 11:40	IRZ-25-VAS-112-117 (< 0.17 U ppb) 12/11/2018 10:34	Topock - Alluvium Deposits	SM		(109.5 - 117.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); (5YR 4/); fine grained to very coarse grained, subangular to subround; some granules to very large pebbles, angular to subround; some silt; trace cobbles; wet; very large pebbles to cobbles composed of trace amounts of metadiorite		
115									
116									
117	120								
118		IRZ-25-SS-117-122 12/14/2018 11:45		Topock - Alluvium Deposits	SM		(117.0 - 119.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown(5YR 4/4); very fine grained to very coarse grained, subangular to subround; little granules to medium pebbles, angular to subround; little silt; little clay; wet		
119									
120					ML		(119.5 - 124.5') Topock - Alluvium Deposits; Sandy silt with gravel		




Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: IRZ-25-Pilot	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number: RC000753.0051	
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
121	120	IRZ-25-SS-117-122 12/14/2018 11:45		Topock - Alluvium Deposits	ML		(ML); reddish brown / moderate brown(5YR 4/4); some very fine to very coarse grained sand, angular to subround; little granules to medium pebbles, angular to subangular; wet		(0.0 - 172.0') No water used
122		IRZ-25-SS-122-127 12/14/2018 10:50							
123				Topock - Alluvium Deposits	SM		(124.5 - 127.0') Topock - Alluvium Deposits; Silty sand (SM); reddish brown / moderate brown(5YR 4/4); very fine grained to coarse grained, subangular to subround; some silt; little granules to medium pebbles, angular to subangular; wet		
124									
125	120	IRZ-25-SS-127-132 12/14/2018 11:55		Topock - Alluvium Deposits	GM		(127.0 - 132.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown (5YR 5/4); granules to large pebbles, angular to subangular; and silt; little very fine to coarse grained sand, angular to subangular; dry to moist; moderate cementation		
126									
127		IRZ-25-SS-132-137 12/14/2018 12:00		Topock - Alluvium Deposits	ML		(132.0 - 137.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown / moderate brown(5YR 4/4); no plasticity; little granules to medium pebbles, angular to subangular; little very fine to very coarse grained sand, angular to subround; dry to moist		
128									
129									
130	120	IRZ-25-SS-137-142 12/14/2018 12:05		Topock - Alluvium Deposits	ML		(137.0 - 139.5') Topock - Alluvium Deposits; Sandy silt (ML); reddish brown / moderate brown(5YR 4/4); no plasticity; some very fine to coarse grained sand, angular to subround; little granules to medium pebbles, angular to subangular; little clay; wet; dessicated		
131									
132					ML		(139.5 - 147.0') Topock - Alluvium Deposits; Sandy silt with gravel		
133									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Boring No.: <u>IRZ-25-Pilot</u>	
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6		
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project:	Final Groundwater Remedy Phase
Drill Rig Type:	Prosonic Truck Mount	Borehole Diameter:	6-12 inches	Location:	1
Driller Name:	Steve Vasquez	Depth to First Water:	48.4 ft bgs	PG&E Topock, Needles, California	
Drilling Asst:	N. Dominguez/C. Alvarez	Sampling Method:	4 inch x 10 ft Core Barrel	Project Number:	RC000753.0051
Logger:	Connor Mills	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
141	120	IRZ-25-SS-137-142 12/14/2018 12:05		Topock - Alluvium Deposits	ML		(ML); reddish brown / moderate brown (5YR 4/4); no plasticity; little granules to medium pebbles, angular to subangular; little very fine to coarse grained sand, angular to subangular; little clay; hard		(0.0 - 172.0') No water used
142									
143									
144									
145		IRZ-25-SS-142-147 12/14/2018 00:10							
146	108			Topock - Alluvium Deposits	SM		(147.0 - 157.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (5YR 4/3); fine grained to very coarse grained, subangular to round; some granules to large pebbles, angular to subround; little silt; trace cobbles, angular to subangular; wet; cobbles composed of metadiorite	(147.0 - 157.0') Very saturated material with potential to produce water	
147									
148									
149		IRZ-25-SS-147-152 12/14/2018 12:15	IRZ-25-VAS-147-152 (3600 ppb) 12/11/2018 13:54						
150									
151									
152									
153									
154		IRZ-25-SS-152-157 12/14/2018 00:20							
155									
156	108			Topock - Weathered Bedrock - conglomerate	ML		(157.0 - 162.0') Topock - Weathered Bedrock - conglomerate; Gravelly silt (ML); reddish brown (5YR 5/4); no plasticity; little granules to large pebbles, angular to subangular; little very fine to medium grained sand, angular to subangular; dry		
157									
158									
159									
160									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

Date Started:	<u>12/04/2018</u>	Surface Elevation:	<u>500.4 ft amsl</u>	Boring No.: <u>IRZ-25-Pilot</u>	
Date Completed:	<u>12/12/2018</u>	Northing (NAD83):	<u>2102414.6</u>		
Drilling Co.:	<u>Cascade</u>	Easting (NAD83):	<u>7615824.5</u>	Client:	<u>PG&E</u>
Drilling Method:	<u>Sonic Drilling</u>	Total Depth:	<u>172 ft bgs</u>	Project:	<u>Final Groundwater Remedy Phase</u>
Drill Rig Type:	<u>Prosonic Truck Mount</u>	Borehole Diameter:	<u>6-12 inches</u>	Location:	<u>1</u>
Driller Name:	<u>Steve Vasquez</u>	Depth to First Water:	<u>48.4 ft bgs</u>	<u>PG&E Topock, Needles, California</u>	
Drilling Asst:	<u>N. Dominguez/C. Alvarez</u>	Sampling Method:	<u>4 inch x 10 ft Core Barrel</u>	Project Number: <u>RC000753.0051</u>	
Logger:	<u>Connor Mills</u>	Sampling Interval:	<u>Continuous</u>		
Editor:	<u>Sean McGrane</u>	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
161				Topock - Weathered Bedrock - conglomerate	ML				(0.0 - 172.0') No water used
162									
163	108	IRZ-25-SS-162-166 12/14/2018 12:25	IRZ-25-VAS-162-167 (3000 ppb) 12/13/2018 10:37	Topock - Weathered Bedrock - conglomerate	ML		(162.0 - 166.0') Topock - Weathered Bedrock - conglomerate; Gravelly silt (ML); reddish brown / moderate brown (5YR 4/4); low plasticity; some granules to medium pebbles, angular to subround; little very fine to coarse grained sand, angular to subround; wet; stiff	(162.0 - 172.0') Drill rods chattering, rough drilling	
164									
165									
166									
167							(166.0 - 172.0') Topock - Competent Bedrock - conglomerate; reddish brown (5YR 5/4); dry; moderate cementation; friable		
168									
169	60			Topock - Competent Bedrock - conglomerate					
170									
171									
172									
End of Boring at 172.0' bgs.									
173									
174									
175									
176									
177									
178									
179									
180									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval

SOIL BORING LOG PG&E TOPOCK C:\USERS\SMCGRANE\DOCUMENTS\PG&E TOPOCK\DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GPJ 06/02/19 14:35

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed		
1		Topock - Fluvial Deposits	SP-SM		(0.0 - 0.5') Temporary Steel Plate with BMP	(0.0 - 0.5') 1	(0.0 - 0.5') 1 (0%)		
2							(0.0 - 4.0') 12" Borehole		
3							(0.5 - 5.0') Plastered Sand	(0.5 - 5.0') 7.9 bags	(0.5 - 5.0') 4 bags (-49%) Note: Wildcat Washed
4									
5		Topock - Fluvial Deposits	SP-SM						
6									
7									
8									
9									
10									
11									
12		Topock - Fluvial Deposits	SW-SM						
13					(5.0 - 157.0') Pea Gravel	(4.0 - 172.0') 6" Borehole	(5.0 - 157.0') 65.8 bags	(5.0 - 157.0') 60 bags (-9%) Note: Cal-Silica 3/8"x1/4"	
14									
15									
16									
17		Topock - Fluvial Deposits	SM						
18									
19									
20									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
21			SM				
22							
23							
24							
25							
26		Topock - Fluvial Deposits	ML				
27							
28							
29							
30					(5.0 - 157.0') Pea Gravel	(4.0 - 172.0') 6" Borehole	(5.0 - 157.0') 65.8 bags
31							(5.0 - 157.0') 60 bags (-9%) Note: Cal-Silica 3/8"x1/4"
32							
33							
34							
35							
36		Topock - Fluvial Deposits	SM				
37							
38							
39							
40							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
41		Topock - Fluvial Deposits	GM				
42							
43							
44							
45		Topock - Fluvial Deposits	GW-GM				
46							
47							
48							
49							
50		Topock - Alluvium Deposits	SM		(5.0 - 157.0') Pea Gravel	(5.0 - 157.0') 65.8 bags	(5.0 - 157.0') 60 bags (-9%) Note: Cal-Silica 3/8"x1/4"
51							
52							
53							
54	IRZ-25-VAS-52-57 (3500 ppb) 12/5/2018 10:40	Topock - Alluvium Deposits	GM				
55							
56							
57							
58		Topock - Alluvium Deposits	ML				
59							
60			GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction		Calculated Material Volumes	Material Volumes Installed			
61	IRZ-25-VAS-62-67 (620 ppb) 12/5/2018 14:17	Topock - Alluvium Deposits	GM								
62											
63											
64											
65											
66											
67											
68		Topock - Alluvium Deposits	SM								
69											
70											
71		Topock - Alluvium Deposits	SM								
72											
73											
74											
75		Topock - Alluvium Deposits	SM								
76											
77											
78		Topock - Alluvium Deposits	GM								
79											
80			SM								

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
81							
82							
83		Topock - Alluvium Deposits	SM				
84							
85							
86							
87							
88							
89							
90		Topock - Alluvium Deposits	SM		(5.0 - 157.0') Pea Gravel		
91					(4.0 - 172.0') 6" Borehole		
92						(5.0 - 157.0') 65.8 bags	(5.0 - 157.0') 60 bags (-9%) Note: Cal-Silica 3/8"x1/4"
93							
94	IRZ-25-VAS-92-97 (130 ppb) 12/6/2018 09:07						
95		Topock - Alluvium Deposits	ML				
96		Topock - Alluvium Deposits	SM				
97							
98		Topock - Alluvium Deposits	SW-SM				
99							
100							


Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
101		Topock - Alluvium Deposits	SW-SM				
102		Topock - Alluvium Deposits	ML				
103							
104		Topock - Alluvium Deposits	GM				
105							
106							
107							
108							
109							
110					(5.0 - 157.0') Pea Gravel	(4.0 - 172.0') 6" Borehole	(5.0 - 157.0') 65.8 bags
111							
112							
113		Topock - Alluvium Deposits	SM				
114	IRZ-25-VAS-112-117 (< 0.17 U ppb) 12/11/2018 10:34						
115							
116							
117							
118		Topock - Alluvium Deposits	SM				
119							
120			ML				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction		Calculated Material Volumes	Material Volumes Installed	
121		Topock - Alluvium Deposits	ML				(5.0 - 157.0') 65.8 bags	(5.0 - 157.0') 60 bags (-9%) Note: Cal-Silica 3/8"x1/4"	
122									
123									
124									
125		Topock - Alluvium Deposits	SM						(4.0 - 172.0') 6" Borehole
126									
127		Topock - Alluvium Deposits	GM						
128									
129									
130									
131				(5.0 - 157.0') Pea Gravel					
132		Topock - Alluvium Deposits	ML						
133									
134									
135									
136									
137		Topock - Alluvium Deposits	ML						
138									
139									
140			ML						

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
141							
142							
143							
144		Topock - Alluvium Deposits	ML				
145							
146							
147							
148							
149	IRZ-25-VAS-147-152 (3600 ppb) 12/11/2018 13:54				(5.0 - 157.0') Pea Gravel	(5.0 - 157.0') 65.8 bags	(5.0 - 157.0') 60 bags (-9%) Note: Cal-Silica 3/8"x1/4"
150							
151							
152		Topock - Alluvium Deposits	SM		(4.0 - 172.0') 6" Borehole		
153							
154							
155							
156							
157							
158		Topock - Weathered Bedrock - conglomerate	ML		(157.0 - 172.0') Cemex # 2/12 Mesh (16x30)	(157.0 - 172.0') 2.8 bags	(157.0 - 172.0') 4 bags (43%) Note: Lapis Lustre Sand
159							
160							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.

Date Started:	12/04/2018	Surface Elevation:	500.4 ft amsl	Well ID: IRZ-25-Pilot
Date Completed:	12/12/2018	Northing (NAD83):	2102414.6	
Drilling Co.:	Cascade	Easting (NAD83):	7615824.5	Client: PG&E
Drilling Method:	Sonic Drilling	Total Depth:	172 ft bgs	Project: Final GW Remedy Phase 1
Driller Name:	Steve Vasquez	Borehole Diameter:	6-12 inches	Location: PG&E Topock, Needles, California
Drilling Asst:	N. Dominguez/C. Alvarez	Depth to First Water:	48.4 ft bgs	
Logger:	Connor Mills	Editor:	Sean McGrane	Project Number: RC000753.0051

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed
161		Topock - Weathered Bedrock - conglomerate	ML				
162							
163							
164	IRZ-25-VAS-162-167 (3000 ppb) 12/13/2018 10:37	Topock - Weathered Bedrock - conglomerate	ML				
165							
166					(157.0 - 172.0') Cemex # 2/12 Mesh (16x30)	(4.0 - 172.0') 6" Borehole	(157.0 - 172.0') 2.8 bags
167							(157.0 - 172.0') 4 bags (43%) Note: Lapis Lustre Sand
168							
169		Topock - Competent Bedrock - conglomerate					
170							
171							
172							
173							
174							
175							
176							
177							
178							
179							
180							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, blue water table symbol represents depth to water measured during the first VAS interval Note: Granule backfill material will be excavated from the pilot borehole during drilling for the construction of the well.