



SEE SITE PLAN

ALISTO PROJECT NO: 10-320-08 DATE DRILLED: 03/24-25/98
 CLIENT: Pacific Gas and Electric Co.
 LOCATION: Topock Compressor Station
 DRILLING METHOD: AP-1000 Dual Tube Percussion
 DRILLING COMPANY: THF Drilling CASING ELEVATION:
 LOGGED BY: Dan Salaiques APPROVED BY: Dan Salaiques

BORING DIAGRAM	DEPTH feet	GRAPHIC LOG	SOIL CLASS	GEOLOGIC DESCRIPTION
<p>4" Sch. 80 PVC Casing</p> <p>Cement/Bent Grout</p> <p>Bentonite</p> <p>Colorado 10x20 Sand</p> <p>4" PVC Screen 0.020-inch slot</p>	10	GP	GP	sandy GRAVEL: moderate yellowish-brown; ~80-70% gravel, subrounded, to 80 mm; ~30-40% sand.
	20	SP	SP	SAND: pale yellowish-brown; very fine- to fine-grained; ~5% gravel.
	30	GP	GP	sandy GRAVEL: light brownish-gray; cobble at 21-24 feet. Changes at 24 feet of color to moderate yellowish-brown; ~80-70% gravel, subrounded, to 80 mm.
	40	SP	SP	gravelly SAND: light gray; ~80% sand, very fine- to fine-grained; ~10% gravel, subrounded, to 50 mm. gravelly SAND continued.
	50	GP	GP	SAND: reddish brown; fine- to very fine-grained; ~5% fines; damp.
	60	GP	GP	sandy GRAVEL: reddish-brown; ~55% gravel, subrounded, to 80 mm; ~45% sand. Appears wet at 80 feet.