

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
1	45.6			Topock - Fluvial Deposits	SW		(0.0 - 3.8') Topock - Fluvial Deposits; Well graded sand with gravel (SW); light brown (7.5YR 6/4); very fine grained to very coarse grained, angular to round; little granules to very large pebbles, angular to subangular; trace small to large cobbles, angular to subangular; trace silt; coarser clasts composed of metadiorite; dry to moist	(0.0 - 3.8') Hand augured for utility clearance, had refusal at 3.8 ft bgs, logged from hand augur cuttings.	(0.0 - 32.0') No water used
2									
3	62.4			Topock - Fluvial Deposits	SM		(3.8 - 5.0') Topock - Fluvial Deposits; Silty sand (SM); light brown (7.5YR 6/4); very fine grained to very coarse grained, angular to round; some silt; little granules to very large pebbles, angular to subangular; trace small to large cobbles, angular to subround; trace boulders, subangular; coarser clasts composed of metadiorite; moist	(3.8 - 9.0') Advanced 12-inch conductor material logged from clean out sample disturbed.	
4									
5									
6	96			Topock - Alluvium Deposits	SM		(5.0 - 9.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/4); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist		
7									
8									
9									
10	60			Topock - Alluvium Deposits	GW		(9.0 - 9.8') Topock - Alluvium Deposits; Well graded gravel (GW); grayish green (GLE1 5/2); boulders, subangular; dry; iron oxide staining; pulverized into rock flour	(9.0 - 16.0') Normal Drilling.	
11									
12	60			Topock - Alluvium Deposits	SW-SM		(9.8 - 11.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; dry; iron oxide staining	(9.5 - 57.0') Formation tight when advancing 10-inch casing.	
13									
14									
15	60			Topock - Alluvium Deposits	SW		(11.0 - 14.3') Topock - Alluvium Deposits; Well graded sand with gravel (SW); gray (2.5Y 5/1); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, subangular to subround; trace silt; trace clay; coarser clasts composed of metadiorite; dry to moist; iron oxide staining		
16									
17	60			Topock - Alluvium Deposits	SW-SM		(14.3 - 16.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/2) and brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist; iron oxide staining	(16.0 - 17.0') Hard drilling.	
18									
19									
20	60			Topock - Alluvium Deposits	SM		(16.0 - 18.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/2) and brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; little granules to very large pebbles, angular to subround; little silt; coarser clasts composed of metadiorite; dry to moist	(17.0 - 22.0') Core came out hot and melted bag 20 to 22 ft. bgs disturbed, potential boulder at 22 ft. bgs.	
21									
22	60			Topock - Alluvium Deposits	SW-SM		(17.5') trace clay; decrease in sand, increase in granules and pebbles		
23									
24	60			Topock - Alluvium Deposits	SM		(18.0 - 19.3') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; dry to moist		
25									
26	60			Topock - Alluvium Deposits	SM		(19.3 - 21.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained,		
27									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG_PG&E-TOPOCK_C:\USERS\MCGRANE\DOCUMENTS\PG&E-TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
21	60			Deposits Topock - Alluvium Deposits	SM		angular to subround; some granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist		
22				Topock - Alluvium Deposits	GW		(21.0 - 22.0') Topock - Alluvium Deposits; Well graded gravel (GW); greenish gray (GLE1 5/1); small cobbles to boulders; dry; cobbles and boulders pulverized into pieces and rock flour		
23				Topock - Alluvium Deposits	SM		(22.0 - 23.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/4) with brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist; organic odor	(22.0 - 27.0') Hard drilling, top 0.5 feet of core slough.	
24				Topock - Alluvium Deposits	SW		(23.5 - 25.0') Topock - Alluvium Deposits; Well graded sand with gravel (SW); brown (7.5YR 5/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; trace small cobbles, subangular to subround; trace silt; trace clay; coarser clasts composed of metadiorite; dry to moist		
25	66			Topock - Alluvium Deposits	SW		(25.0 - 26.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist	(25.0') Slow drilling with 10-inch casing due to potential boulder.	
26				Topock - Alluvium Deposits	SM		(26.0 - 27.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; little silt; trace small cobbles, subround; trace clay; coarser clasts composed of metadiorite; dry to moist		
27				Topock - Alluvium Deposits	GW		(27.0 - 27.5') Topock - Alluvium Deposits; Well graded gravel with sand (GW); dark greenish gray (GLE1 4/1); small cobbles, subangular to round; and small to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; trace silt; coarser clasts composed of metadiorite; moist; iron oxide staining; cobbles pulverized into rock flour difficult to determine silt content	(27.0 - 32.0') Hard drilling.	
28				Topock - Alluvium Deposits	SW-SM		(27.5 - 28.3') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/2); very fine grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist to dry		
29				Topock - Alluvium Deposits	GW-GM		(28.3 - 30.5') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); gray (2.5Y 5/1); small cobbles, angular to subangular; and granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to round; little silt; dry; iron oxide staining; cobbles pulverized to rock flour difficult to determine silt content	(32.0 - 37.0') Drilling got softer.	(32.0 - 67.0') No water used
30				Topock - Alluvium Deposits	SM		(30.5 - 34.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3) and brown (7.5YR 5/4); very fine grained to very coarse grained, angular to round; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist		
31				Topock - Alluvium Deposits	SM		(34.5 - 37.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to round; some granules to very large pebbles, angular to subangular; some silt; dry to moist		
32	120			Topock - Alluvium Deposits	SM		(35'); little silt; trace small cobbles, subround; trace clay; increase in sand, increase in granules and pebbles		
33				Topock - Alluvium Deposits	SM		(37.0 - 38.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); yellowish brown / moderate yellowish brown (10YR 5/4); very fine grained to medium grained, angular to subround; some granules to very large pebbles, angular to subangular; some silt; little coarse to very coarse grained sand, angular to subround; trace small cobbles, subangular; trace clay; coarser clasts composed of metadiorite; trace; dry; weak cementation; iron oxide staining	(37.0 - 39.0') Formation tight 2 foot drill run.	
34				Topock - Alluvium Deposits	SM		(38.0 - 39.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (10YR 5/2); very fine grained to very coarse	(39.0 - 47.0') Soft drilling, top one foot of core	
35				Topock - Alluvium Deposits	SM				
36				Topock - Alluvium Deposits	SM				
37				Topock - Alluvium Deposits	SM				
38	24			Topock - Alluvium Deposits	SM				
39				Topock - Alluvium Deposits	SM				
40	108			Topock - Alluvium Deposits	GW-GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG - PG&E - TOPOCK - C:\USERS\SMCGRANE\DOCUMENTS\PG&E\TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel		
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid	
41	108			Topock - Alluvium Deposits	SW		grained, angular to round; some granules to large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry; weak cementation; iron oxide staining	slough.		
42				Topock - Alluvium Deposits	ML		(39.0 - 40.0') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); brown (7.5YR 5/3); granules to very large pebbles, angular to subround; some very fine to very coarse grained sand, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist to dry			
43							(40.0 - 41.5') Topock - Alluvium Deposits; Well graded sand with gravel (SW); brown (7.5YR 4/3); very fine grained to very coarse grained, angular to round; some granules to large pebbles, angular to subround; trace silt; trace clay; coarser clasts composed of metadiorite; moist to dry			
44							(41.5 - 44.5') Topock - Alluvium Deposits; Silt with sand (ML); brown (10YR 5/3); no plasticity; some granules to large pebbles, angular to subround; some very fine to very coarse grained sand, angular to subround; trace clay; coarser clasts composed of metadiorite; dry; weak cementation			
45							(44.5 - 48.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist to dry; iron oxide staining			
46							(46.5') boulders; dry; trace boulder subround pulverized into rock flour			
47					Topock - Alluvium Deposits	SW-SM				(47.0 - 56.0') Got tight at 56 ft. tripped out core barrel, top 0.5 ft slough.
48							(48.0 - 49.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (10YR 5/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry; boulder pulverized into rock flour			
49					Topock - Alluvium Deposits	SM				(50.0') Hard drilling.
50							(49.0 - 51.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to large pebbles, angular to subround; some silt; trace clay; coarser clasts composed of metadiorite; moist; weak cementation; iron oxide staining			
51	114			Topock - Alluvium Deposits	SW		(51.0 - 52.0') Topock - Alluvium Deposits; Well graded sand with gravel (SW); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; trace silt; trace clay; coarser clasts composed of metadiorite; dry	(54.0') Hard Drilling.		
52							(52.0 - 54.3') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to large pebbles, angular to subround; some silt; trace clay; coarser clasts composed of metadiorite; moist; weak cementation			
53							(53') some granules to very large pebbles, angular to subround; little silt; increase in sand, no clay			
54							(54.3 - 55.3') Topock - Alluvium Deposits; Well graded sand with gravel (SW); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; trace silt; coarser clasts composed of metadiorite; strong cementation			
55							(55.3 - 56.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (10YR 5/3); very fine grained to very coarse grained, angular to subround; some silt; little granules to large pebbles, angular to subround; trace clay; coarser clasts composed of metadiorite; dry; weak cementation; iron oxide staining			
56							(56.0 - 67.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subround; little silt; coarser clasts composed of metadiorite; dry to moist			
57	132			Topock - Alluvium Deposits	SW-SM		(59') brown (7.5YR 5/2); weak cementation; iron oxide staining	(56.0 - 67.0') Normal drilling, interbedded moist and dry layers.		
58										
59										
60										

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG - PG&E - TOPOCK - C:\USERS\SMCGRANE\DOCUMENTS\PG&E\TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid		
61	132			Topock - Alluvium Deposits	SW-SM		(61.5'); and granules to large pebbles, angular to subround				
62							(64'); and granules to very large pebbles, angular to subround; trace small cobbles, subround				
63											
64											
65	120			Topock - Alluvium Deposits	SM		(67.0 - 69.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist	(67.0 - 77.0') Normal Drilling.	(67.0 - 107.0') No water used		
66				Topock - Alluvium Deposits	SM		(69.0 - 70.5') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist				
67				Topock - Alluvium Deposits	SM		(69.5') Silty sand with gravel (SM); gray / light brownish gray (5YR 6/1); dry; weak cementation; 0.4 foot lens				
68				Topock - Alluvium Deposits	SM		(70.5 - 71.3') Topock - Alluvium Deposits; Silty sand with gravel (SM); pinkish gray (7.5YR 6/2); very fine grained to very coarse grained, angular to subround; little granules to large pebbles, angular to subround; little silt; trace clay; dry to moist; weak cementation				
69				Topock - Alluvium Deposits	SM		(71.3 - 78.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; dry to moist				
70				Topock - Alluvium Deposits	SM		(73.5'); some granules to large pebbles, angular to subangular				
71				Topock - Alluvium Deposits	SM		(75'); some granules to very large pebbles, angular to subangular				
72				Topock - Alluvium Deposits	SM		(75.5'); some granules to large pebbles, angular to subangular; weak cementation				
73				Topock - Alluvium Deposits	SM		(77'); some granules to very large pebbles, angular to subround; moist; weak cementation	(77.0 - 82.0') Normal Drilling, stopped at 82 ft core barrel full with slough.			
74				Topock - Alluvium Deposits	SM		(78.0 - 80.0') Topock - Alluvium Deposits; Well graded gravel with sand (GW); grayish brown (2.5Y 5/2); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; little small cobbles, subangular; coarser clasts composed of metadiorite; dry; iron oxide staining; pebbles and cobbles pulverized into rock flour cannot determine silt content				
75	60			Topock - Alluvium Deposits	GW						
76											
77											
78											
79											
80											

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG_PG&E-TOPOCK_C:\USERS\SMCGRANE\DOCUMENTS\PG&E-TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
81	60			Topock - Alluvium Deposits	SM		(80.0 - 82.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace small cobbles, subangular; moist to dry		
82				Topock - Alluvium Deposits	SW-SM		(82.0 - 86.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist	(82.0 - 92.0') Normal Drilling.	
83									
84							(85.5'); trace small cobbles, angular to subangular		
85				Topock - Alluvium Deposits	SW		(86.0 - 92.0') Topock - Alluvium Deposits; Well graded sand with gravel (SW); reddish brown (5YR 5/3); very fine grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subround; trace silt; trace clay; coarser clasts composed of metadiorite; moist to dry (87'); and granules to large pebbles, angular to subround (88'); and granules to very large pebbles, angular to subangular (88.25') grayish brown (2.5Y 5/2); 0.2 foot lens (88.45') reddish brown (5YR 5/3)		
86									
87	120								
88									
89									
90									
91									
92									
93				Topock - Alluvium Deposits	SM		(92.0 - 94.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist		
94							(93.5'); little granules to large pebbles, angular to subround; increase in sand		
95	60			Topock - Alluvium Deposits	SW-SM		(94.0 - 94.8') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist		
96				Topock - Alluvium Deposits	GW		(94.8 - 95.0') Topock - Alluvium Deposits; Well graded gravel (GW); (GLE1 5/3); boulders, subangular; dry; boulders have been pulverized into some rock flour		
97				Topock - Alluvium Deposits	SM		(95.0 - 100.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some silt; little granules to large pebbles, angular to subangular; trace clay; coarser clasts composed of metadiorite; moist; weak cementation; iron oxide staining (97'); little clay; moist to wet; increase in silt, decrease in sand (98'); trace small to large cobbles, subangular (98.25'); increase in sand, decrease in silt, no clay		
98									
99	54	MW-95-VAS-97-102.0 (0.79 ppb) 3/10/2020 10:17							
100									
							(96.8') Approximate depth to groundwater.		
							(97.0 - 102.0') Tight drilling, core barrel came out hot, bag melted lost 0.5 ft in hopper.		
							(97.1 - 107.0')		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG_PG&E_TOPOCK_C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
101	54		MW-95-VAS-97-102.0 (0.79 ppb) 3/10/2020 10:17	Topock - Alluvium Deposits	SM		(99.9') some granules to large pebbles, angular to subangular; trace clay; decrease in sand, increase in silt	Drilling easy with 8-inch core barrel.	
102				Topock - Alluvium Deposits	NR		(100.5 - 101.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown (5YR 4/4); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; well sorted; moist to wet (101.5 - 102.0') No recovery (NR); fell out of core barrel into hopper	(102.0 - 107.0') Hard drilling.	
103				Topock - Alluvium Deposits	SM		(102.0 - 104.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/4); very fine grained to very coarse grained, angular to subround; some silt; little granules to large pebbles, angular to subangular; trace clay; coarser clasts composed of metadiorite; wet		
104				Topock - Alluvium Deposits	SM		(103.5') some granules to very large pebbles, angular to subangular; increase in sand, decrease in silt		
105	60			Topock - Alluvium Deposits	SM		(104.0 - 107.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (10YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace clay; coarser clasts composed of metadiorite; moist to wet; weak cementation		
106				Topock - Alluvium Deposits	ML		(107.0 - 108.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 4/4); no plasticity; some very fine to very coarse grained sand, angular to subangular; little granules to very large pebbles, angular to subangular; trace clay; moist to wet; very stiff	(107.0') Hard Drilling	(107.0 - 147.0') No water used
107				Topock - Alluvium Deposits	ML		(108.0 - 110.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 5/3); no plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; trace clay; coarser clasts composed of metadiorite; dry to moist; hard		
108				Topock - Alluvium Deposits	SM		(109.5') trace small cobbles, subangular; cobbles pulverized into rock flour	(110.0') Hard Drilling.	
109				Topock - Alluvium Deposits	SM		(110.0 - 112.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; some silt; trace small cobbles, subangular; moist to wet		
110	120			Topock - Alluvium Deposits	ML		(112.5 - 114.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (10YR 5/3); low plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; coarser clasts composed of metadiorite; moist to wet; very stiff		
111				Topock - Alluvium Deposits	SM		(114.0 - 115.8') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace clay; coarser clasts composed of metadiorite; moist to wet (114.75'); moist to dry	(114.0') Hard Drilling.	
112				Topock - Alluvium Deposits	SM		(115.8 - 117.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark yellowish brown (10YR 4/4); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; coarser clasts composed of metadiorite; moist to dry		
113				Topock - Alluvium Deposits	GM		(117.0 - 118.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); grayish brown (10YR 5/2); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; little silt; coarser clasts composed of metadiorite; moist to wet; pebbles pulverized, some silt maybe rock flour	(117.0 - 127.0') Normal drilling, 9.5 ft of recovery due to compaction.	
114				Topock - Alluvium Deposits	GM		(118.0 - 121.5') Topock - Alluvium Deposits; (GM); brown (10YR 5/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; coarser clasts composed of metadiorite; moist to wet; weak		
115				Topock - Alluvium Deposits	GM				
116				Topock - Alluvium Deposits	GM				
117				Topock - Alluvium Deposits	GM				
118	114			Topock - Alluvium Deposits	GM				
119				Topock - Alluvium Deposits	GM				
120				Topock - Alluvium Deposits	GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG: PG&E-TOPOCK_C:\USERS\MCGRANE\DOCUMENTS\PG&E-TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
121	114			Topock - Alluvium Deposits	GM		cementation		
122				Topock - Alluvium Deposits	SM		(121.5 - 124.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (10YR 5/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace small cobbles, subangular to subround; trace clay; coarser clasts composed of metadiorite; dry		
123				Topock - Alluvium Deposits	SM		(123') and granules to very large pebbles, angular to subangular; little silt; trace boulders, subangular; increase in sand		
124	120		MW-95-VAS-122-127 (0.87 ppb) 3/10/2020 15:24	Topock - Alluvium Deposits	SM		(124.0 - 127.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/4); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; wet		
125				Topock - Alluvium Deposits	SM		(125') and granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; wet		
126				Topock - Alluvium Deposits	SM		(126') and granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; wet		
127				Topock - Alluvium Deposits	SM		(127') and granules to very large pebbles, angular to subangular; little silt; trace clay; coarser clasts composed of metadiorite; wet		
128	114			Topock - Alluvium Deposits	GW-GM		(127.0 - 129.5') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); brown (7.5YR 5/3); granules to very large pebbles, angular to subround; and very fine to very coarse grained sand, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; wet	(127.0 - 137.0') Normal drilling.	
129				Topock - Alluvium Deposits	GM		(129.5 - 132.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 5/3); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; some silt; coarser clasts composed of metadiorite; wet	(130.0 - 140.0') Borehole caving in during drilling with 8-inch, potential voids forming. Advancing 10-inch casing hard.	
130				Topock - Alluvium Deposits	GM		(130.5') increase in granules and pebbles, increase in sand, decrease in silt		
131				Topock - Alluvium Deposits	ML		(132.5 - 133.5') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 5/3); low plasticity; some granules to very large pebbles, angular to subround; some very fine to very coarse grained sand, angular to subround; trace clay; moist; very stiff		
132				Topock - Alluvium Deposits	SM		(133.5 - 137.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 5/3); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular to subangular; some silt; trace clay; coarser clasts composed of metadiorite; moist to moist		
133	114			Topock - Alluvium Deposits	ML		(137.0 - 140.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); dark yellowish brown (10YR 4/4) with reddish brown (5YR 5/4); medium plasticity; and very fine to very coarse grained sand, angular to round; little granules to very large pebbles, angular to subround; coarser clasts composed of metadiorite; moist to wet; soft; mottled	(137.0 - 147.0') Normal Drilling, 9.5 ft of recovery due to compaction.	
134				Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-		
135				Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-		
136				Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-		
137				Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-		
138				Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-		
139				Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-		
140			Topock - Alluvium Deposits	ML		(138.0') Encountered potential boulder advancing 10-			

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG_PG&E_TOPOCK_C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started: 03/08/2020	Surface Elevation: N/A	Boring No.: MW-95
Date Completed: 03/26/2020	Northing (NAD83): N/A	
Drilling Co.: Cascade	Easting (NAD83): N/A	Client: PG&E
Drilling Method: Sonic Drilling	Total Depth: 197 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type: Boart Longyear Track	Borehole Diameter: 6-12 inches	Location: PG&E Topock, Needles, California
Driller Name: Jose Hernandez	Depth to First Water: 96.7 ft bgs	
Drilling Asst: J. Colon / F. Sandoval	Sampling Method: 4 inch x 10 ft. Core Barrel	Project Number: RC000753.0051
Logger: Sean McGrane	Sampling Interval: Continuous	
Editor: Sean McGrane	Converted to Well: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
141	114			Topock - Alluvium Deposits	SW-SM	(140.0 - 141.0')	Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 5/2); very fine grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subround; little silt; trace clay; coarser clasts composed of metadiorite; moist to wet	inch casing. (140.0 - 150.0') Normal drilling advancing 10-inch casing.	
142				Topock - Alluvium Deposits	ML	(141.0 - 144.0')	Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 4/4); low plasticity; and very fine to very coarse grained sand, angular to subround; little granules to very large pebbles, angular to subround; trace clay; coarser clasts composed of metadiorite; moist to wet; soft		
143							(143.8'); trace small cobbles, subangular		
144	62.4			Topock - Alluvium Deposits	SW-SM	(144.0 - 147.0')	Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 4/3); very fine grained to very coarse grained, angular to round; some granules to very large pebbles, angular to subround; little silt; some coarser clasts composed of metadiorite; moist to wet	(147.0 - 153.0') Hard Drilling, 5.2 ft of recovery due to compaction in sample bag.	(147.0 - 157.0') No water used
145						(146.5'); trace small cobbles, subangular			
146							(147.0 - 149.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 4/4); low plasticity; some very fine to very coarse grained sand, angular to subround; little granules to very large pebbles, angular to subangular; trace clay; coarser clasts composed of metadiorite; moist; very stiff		
147	42			Topock - Alluvium Deposits	ML	(149.0 - 153.0')	Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; some silt; trace clay; coarser clasts composed of metadiorite; moist	(153.0 - 157.0') Normal drilling, 3.5 ft recovery due to compaction of sediments in bag.	(157.0 - 175.0') Normal drilling. No water used
148						(151.5'); increase in sand, no clay			
149							(153.0 - 157.0') Topock - Alluvium Deposits; Well graded sand with silt and gravel (SW-SM); brown (7.5YR 4/4); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; coarser clasts composed of metadiorite; wet		
150	216		MW-95-VAS152-157 (<0.033 U ppb) 3/12/2020 09:57	Topock - Alluvium Deposits	SW-SM	(154.5')	trace small cobbles, subangular		
151						(155'); trace clay; decrease in sand			
152							(157.0 - 163.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (10YR 4/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; little silt; coarser clasts composed of metadiorite; wet		
153						(159'); some silt; decrease in sand			

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG_PG&E_TOPOCK_C:\USERS\SMC\GRAND\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
161				Topock - Alluvium Deposits	SM		(161.5'); little silt; increase in sand		
162									
163									
164				Topock - Alluvium Deposits	ML		(163.0 - 166.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (10YR 4/3); medium plasticity; and very fine to very coarse grained sand, angular to subround; little granules to very large pebbles, angular to subangular; coarser clasts composed of metadiorite; soft		
165								(165.0') Hard drilling.	
166									
167				Topock - Alluvium Deposits	SM		(166.0 - 170.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark yellowish brown (10YR 4/4); very fine grained to very coarse grained, angular to subround; little granules to very large pebbles, angular to subangular; little silt; coarser clasts composed of metadiorite; wet		
168	216						(167.5'); increase in silt, decrease in sand		
169							(169') brown (10YR 4/3); some silt; trace clay; moist; decrease in sand		
170				Topock - Alluvium Deposits	ML		(170.0 - 171.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); very dark grayish brown (10YR 3/2); medium plasticity; some very fine to very coarse grained sand, angular to round; little granules to very large pebbles, angular to subround; trace small cobbles, subangular; trace silt; wet; soft		
171									
172				Topock - Alluvium Deposits	SM		(171.0 - 175.8') Topock - Alluvium Deposits; Silty sand with gravel (SM); very dark grayish brown (10YR 3/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subangular; some silt; coarser clasts composed of metadiorite; wet		
173							(172'); and silt; trace clay; decrease in sand		
174							(173'); no clay, increase in sand		
175									
176				Topock - Alluvium Deposits	SM		(175.5'); trace clay; decrease in sand		
177							(175.8 - 176.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark grayish brown / dark yellowish brown (10YR 4/2); very fine grained to very coarse grained, angular to round; some granules to very large pebbles, angular to subround; some silt; trace clay; coarser clasts composed of metadiorite; wet		
178	74.4			Topock - Alluvium Deposits	ML		(176.5 - 179.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); dark grayish brown / dark yellowish brown (10YR 4/2); medium plasticity; some very fine to very coarse grained sand, angular to subround; little granules to very large pebbles, angular to subangular; trace clay; coarser clasts composed of metadiorite; moist; very stiff; some metadiorite is weathered		
179									
180				Topock - Alluvium Deposits	SM		(179.0 - 182.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); very dark grayish brown (10YR 3/2); very fine grained to very coarse grained, angular to round; some silt; little granules to very		
								(175.0 - 182.0') Normal drilling, driller said lost 1 foot of core out of bottom of core barrel.	(175.0 - 187.0') No water used

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG: PG&E-TOPOCK_C:\USERS\SMCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29


Date Started:	03/08/2020	Surface Elevation:	N/A	Boring No.: MW-95	
Date Completed:	03/26/2020	Northing (NAD83):	N/A		
Drilling Co.:	Cascade	Easting (NAD83):	N/A	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	197 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	6-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Jose Hernandez	Depth to First Water:	96.7 ft bgs		
Drilling Asst:	J. Colon / F. Sandoval	Sampling Method:	4 inch x 10 ft. Core Barrel	Project Number:	RC000753.0051
Logger:	Sean McGrane	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
181	74.4			Topock - Alluvium Deposits	SM		large pebbles, angular to subround; trace clay; coarser clasts composed of metadiorite; moist to wet (179.5'); dry (180'); weak cementation		
182							(181.5') brown (7.5YR 4/3) with dark gray (10YR 4/1); mottled		
183				Topock - Alluvium Deposits	SM		(182.0 - 183.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/2); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace clay; coarser clasts composed of metadiorite; wet	(182.0 - 186.0') Normal drilling, extra recovery material lost downhole 181 to 182.	
184	78		MW-95-VAS-182-187 (<0.17 U ppb) 3/20/2020 16:18				(183.5 - 188.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); dark gray (10YR 4/1); medium plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand; coarser clasts composed of metadiorite; moist; very stiff		
185				Topock - Alluvium Deposits	ML		(185.5'); wet	(186.0 - 187.0') Started getting hard during drilling.	
186							(187'); trace small to large cobbles, subangular	(187.0 - 193.0') Cobble may have jammed up core barrel, preventing advancing to 197, lost 3 ft. of core down hole going back in to retrieve.	(187.0 - 188.0') No water used
188				Topock - Alluvium Deposits	ML		(188.0 - 190.2') Topock - Alluvium Deposits; Sandy silt with gravel (ML); reddish brown (5YR 4/3) and grayish brown (10YR 5/2); no plasticity; some granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; trace small to large cobbles, subangular; trace clay; coarser clast composed of conglomerate; coarser clasts composed of metadiorite; moist; hard; mottled; conglomerate clasts weathered		(188.0 - 193.0') 1744 gallons of water used; 800 gallons of water recovered; 944 gallons of water lost; Used to flush casing prior to installation of the well.
189				Topock - Weathered Bedrock - conglomerate	SM		(188.5'); dry (189.5'); moist (190'); dry (190.2 - 191.7') Topock - Weathered Bedrock - conglomerate; Sandy silt with gravel (SM); reddish brown (5YR 4/3) with red (2.5YR 4/6); low plasticity; some very fine to very coarse grained sand, angular to subangular; little granules to very large pebbles, angular to subangular; trace clay; coarser clasts composed of metadiorite; moist; mottled; iron oxide staining	(188.0') Very hard drilling with 8-inch multiple clean outs, driller did not want to advance 10 inch further.	
190	38.4						(191.7 - 197.0') Topock - Competent Bedrock - conglomerate; red (2.5YR 4/6); dry; friable, pulverized by drilling	(192.0') Drilling got hard.	
191				Topock - Competent Bedrock - conglomerate				(193.0 - 197.0') Hard drilling, extra recovery retrieved core from 187 to 193 ft run.	(193.0 - 197.0') 484 gallons of water used; 123 gallons of water recovered; 361 gallons of water lost; Used to flush casing prior to installation of bentonite in Rathole.
192								(196.0') Very hard drilling, 6-inch casing refusal.	
193									
194									
195	80.4								
196									
197									
End of Boring at 197.0' bgs.									
198									
199									
200									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

SOIL BORING LOG_PG&E_TOPOCK_C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04_16_20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:29

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	



Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK_DRAFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
18		Topock - Alluvium Deposits	SM		(+2.3 - 93.0') 2" PVC Sch 80 Casing		
19		Topock - Alluvium Deposits	SW-SM				
20		Topock - Alluvium Deposits	SM				
21		Topock - Alluvium Deposits	GW				
22		Topock - Alluvium Deposits	SM				
23		Topock - Alluvium Deposits	SW				
24		Topock - Alluvium Deposits	SW				
25		Topock - Alluvium Deposits	SW-SM				
26		Topock - Alluvium Deposits	SM		(5.0 - 34.5') Portland Cement 6% Bentonite	(5.0 - 34.5') 117.9 gallons	(5.0 - 34.5') 150 gallons (127%) Note: Type I, II and V and Hydrogel, used >20% of the calculated volume due to potential voids forming. Installed on 3/30/2020.
27		Topock - Alluvium Deposits	SM				
28		Topock - Alluvium Deposits	GW				
29		Topock - Alluvium Deposits	SW-SM				
30		Topock - Alluvium Deposits	GW-GM				
31		Topock - Alluvium Deposits	SM				
32		Topock - Alluvium Deposits	SM				
33		Topock - Alluvium Deposits	SM				
34		Topock - Alluvium Deposits	SM				
35		Topock - Alluvium Deposits	SM		(34.5 - 35.5') Centralizer (34.5 - 85.0') Portland Cement 6% Bentonite	(34.5 - 85.0') 189.4 gallons	(34.5 - 85.0') 400 gallons (211%) Note: Type I, II and V and Hydrogel, used >20% of the calculated volume due to potential voids forming. Installed on 3/29/30.
36		Topock - Alluvium Deposits	SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK DRAFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_04/16/20 16:42


Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
38		Topock - Alluvium Deposits	SM		(+2.3 - 93.0') 2" PVC Sch 80 Casing		
39		Topock - Alluvium Deposits	SM				
40		Topock - Alluvium Deposits	GW-GM				
41		Topock - Alluvium Deposits	SW				
42		Topock - Alluvium Deposits	ML				
43		Topock - Alluvium Deposits	ML				
44		Topock - Alluvium Deposits	ML				
45		Topock - Alluvium Deposits	SW-SM				
46		Topock - Alluvium Deposits	SW-SM				
47		Topock - Alluvium Deposits	SW-SM		(34.5 - 85.0') Portland Cement 6% Bentonite	(34.5 - 85.0') 189.4 gallons	(34.5 - 85.0') 400 gallons (211%) Note: Type I, II and V and Hydrogel, used >20% of the calculated volume due to potential voids forming. Installed on 3/29/30.
48		Topock - Alluvium Deposits	SM				
49		Topock - Alluvium Deposits	SM				
50		Topock - Alluvium Deposits	SM				
51		Topock - Alluvium Deposits	SM				
52		Topock - Alluvium Deposits	SW				
53		Topock - Alluvium Deposits	SM				
54		Topock - Alluvium Deposits	SM				
55		Topock - Alluvium Deposits	SW				
56		Topock - Alluvium Deposits	SM				
56		Topock - Alluvium Deposits	SW-SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	



Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK_DRAFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
78		Topock - Alluvium Deposits	SW-SM		(+2.3 - 93.0') 2" PVC Sch 80 Casing		
79		Topock - Alluvium Deposits	GW				
80		Topock - Alluvium Deposits	SM		(34.5 - 85.0') Portland Cement 6% Bentonite	(34.5 - 85.0') 189.4 gallons	(34.5 - 85.0') 400 gallons (211%) Note: Type I, II and V and Hydrogel, used >20% of the calculated volume due to potential voids forming. Installed on 3/29/30.
81		Topock - Alluvium Deposits	SM				
82		Topock - Alluvium Deposits	SW-SM				
83		Topock - Alluvium Deposits	SW-SM				
84		Topock - Alluvium Deposits	SW-SM				
85		Topock - Alluvium Deposits	SW-SM				
86		Topock - Alluvium Deposits	SW		(85.0 - 90.0') Cemex #0/30 MESH (30x50)	(85.0 - 90.0') 5 bags	(85.0 - 90.0') 7 bags (140%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling.
87		Topock - Alluvium Deposits	SW		(9.0 - 188.0') 10.0" Borehole		
88		Topock - Alluvium Deposits	SW				
89		Topock - Alluvium Deposits	SW				
90		Topock - Alluvium Deposits	SW				
91		Topock - Alluvium Deposits	SM		(90.0 - 116.0') Cemex #3 MESH (8x10)	(90.0 - 116.0') 26.4 bags	(90.0 - 116.0') 43 bags (163%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling.
92		Topock - Alluvium Deposits	SM				
93		Topock - Alluvium Deposits	SM				
94		Topock - Alluvium Deposits	SW-SM		(93.0 - 113.0') 2" 20-Slot Sch 80 PVC Screen		
95		Topock - Alluvium Deposits	GW				
96		Topock - Alluvium Deposits	SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GPJ_04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
98	MW-95-VAS-97-102.0 (0.79 ppb) 3/10/2020 10:17	Topock - Alluvium Deposits	SM		(93.0 - 113.0') 2" 20-Slot Sch 80 PVC Screen		
99		Topock - Alluvium Deposits	SM				
100			NR	X			
101		Topock - Alluvium Deposits	SM				
102							
103		Topock - Alluvium Deposits	SM				
104							
105		Topock - Alluvium Deposits	SM				
106					(90.0 - 116.0') Cemex #3 MESH (8x10)	(90.0 - 116.0') 26.4 bags	(90.0 - 116.0') 43 bags (163%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling.
107		Topock - Alluvium Deposits	ML				
108							
109		Topock - Alluvium Deposits	ML				
110							
111		Topock - Alluvium Deposits	SM				
112							
113		Topock - Alluvium Deposits	ML				
114					(113.5 - 114.2') Centralizer		
115		Topock - Alluvium Deposits	SM				
116					(113.0 - 115.3') Sump and End Cap		
		Topock - Alluvium Deposits	SM		(116.0 - 130.0') Bentonite seal pellets	(116.0 - 130.0') 11.7	

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
118	MW-95-VAS-122-127 (0.87 ppb) 3/10/2020 15:24	Topock - Alluvium Deposits	GM		(+2.2 - 137.0') 2" PVC Sch 80 Casing		
119		Topock - Alluvium Deposits	GM				
120		Topock - Alluvium Deposits	GM				
121		Topock - Alluvium Deposits	GM				
122		Topock - Alluvium Deposits	SM				
123		Topock - Alluvium Deposits	SM		(116.0 - 130.0') Bentonite seal pellets	(116.0 - 130.0') 11.7	(116.0 - 130.0') 24 (205%) Note: Pel-Plug (TR30) 3/8", used >20% of the calculated volume due to potential voids forming during drilling.
124		Topock - Alluvium Deposits	SM		(124.5 - 125.2') Centralizer		
125		Topock - Alluvium Deposits	SM				
126		Topock - Alluvium Deposits	SM				
127		Topock - Alluvium Deposits	SM		(9.0 - 188.0') 10.0" Borehole		
128		Topock - Alluvium Deposits	GW-GM				
129		Topock - Alluvium Deposits	GW-GM				
130		Topock - Alluvium Deposits	GM				
131		Topock - Alluvium Deposits	GM				
132		Topock - Alluvium Deposits	GM				
133		Topock - Alluvium Deposits	ML		(130.0 - 135.0') Cemex #0/30 MESH (30x50)	(130.0 - 135.0') 5.2 bags	(130.0 - 135.0') 7 bags (135%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling
134		Topock - Alluvium Deposits	ML				
135		Topock - Alluvium Deposits	SM				
136		Topock - Alluvium Deposits	SM		(135.0 - 161.5') Cemex #3 MESH (8x10)	(135.0 - 161.5') 27.3 bags	(135.0 - 161.5') 35 bags (128%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK_DRAFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	Project Number: RC000753.0051
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
138		Topock - Alluvium Deposits	ML		(137.0 - 157.0') 2" 20-Slot Sch 80 PVC Screen		
139		Topock - Alluvium Deposits	SW-SM				
140		Topock - Alluvium Deposits	ML				
141		Topock - Alluvium Deposits	SW-SM				
142		Topock - Alluvium Deposits	ML				
143		Topock - Alluvium Deposits	ML				
144		Topock - Alluvium Deposits	SW-SM				
145		Topock - Alluvium Deposits	SW-SM				
146		Topock - Alluvium Deposits	SW-SM				
147		Topock - Alluvium Deposits	ML		(135.0 - 161.5') Cemex #3 MESH (8x10)	(135.0 - 161.5') 27.3 bags	(135.0 - 161.5') 35 bags (128%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling
148		Topock - Alluvium Deposits	ML		(9.0 - 188.0') 10.0" Borehole		
149		Topock - Alluvium Deposits	ML				
150		Topock - Alluvium Deposits	SM				
151		Topock - Alluvium Deposits	SM				
152		Topock - Alluvium Deposits	SM				
153		Topock - Alluvium Deposits	SW-SM				
154	MW-95-VAS152-157 (<0.033 U ppb) 3/12/2020 09:57	Topock - Alluvium Deposits	SW-SM				
155		Topock - Alluvium Deposits	SW-SM				
156		Topock - Alluvium Deposits	SW-SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\SMCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
158		Topock - Alluvium Deposits	SM		(157.5 - 158.5') Centralizer	(135.0 - 161.5') 27.3 bags	(135.0 - 161.5') 35 bags (128%) Note: Lapis Lustre Sand, used >20% of the calculated volume due to potential voids forming during drilling
159					(135.0 - 161.5') Cemex #3 MESH (8x10)		
160							
161							
162		Topock - Alluvium Deposits	ML				
163							
164							
165							
166		Topock - Alluvium Deposits	SM				
167							
168							
169							
170		Topock - Alluvium Deposits	ML				(161.5 - 193.0') 32 buckets (124%) Note: Pel-Plug (TR30) 3/8", used >20% of the calculated volume due to potential voids forming during drilling
171							
172							
173		Topock - Alluvium Deposits	SM				
174							
175							
176		Topock - Alluvium Deposits	SM				
177							
178							
179							
180							
181							
182							
183							
184							
185							
186							
187							
188							
189							
190							
191							
192							
193							
194							
195							
196							
197							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
178		Topock - Alluvium Deposits	ML				
179							
180		Topock - Alluvium Deposits	SM				
181							
182							
183		Topock - Alluvium Deposits	SM				
184	MW-95-VAS-182-187 (<0.17 U ppb) 3/20/2020 16:18					(161.5 - 193.0') Bentonite seal pellets	(161.5 - 193.0') 25.9 buckets
185		Topock - Alluvium Deposits	ML				
186							
187							
188							
189		Topock - Alluvium Deposits	ML				
190							
191		Topock - Weathered Bedrock - conglomerate	SM		(188.0 - 193.0') 8.0" Borehole		
192							
193							
194		Topock - Competent Bedrock - conglomerate			(193.0 - 196.0') 6.0" Borehole		
195					(193.0 - 197.0') Bentonite seal pellets	(193.0 - 197.0') 1.08 buckets	(193.0 - 197.0') 1 buckets (93%) Note: Pel-Plug (TR30) 3/8", overshot draft design by 1 foot
196					(196.0 - 197.0') 4.0" Borehole		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_04/16/20 16:42

Date Started: 03/27/2020	Surface Elevation: N/A	Well ID: MW-95-113, MW-95-157
Date Completed: 04/01/2020	Shallow Well Elevation: N/A	
Drilling Co.: Cascade	Deep Well Elevation: N/A	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): N/A	Project: Final GW Remedy Phase 1
Driller Name: Jose Hernandez	Easting (NAD83): N/A	Location: PG&E Topock, Needles, California
Drilling Asst: J. Colon / F. Sandoval	Borehole Diameter: 6-12 inches	
Logger: Sean McGrane	Water Level Start: 96.7 ft bgs	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: N/A	
Total Depth: 197 ft bgs	Well Completion: <input type="checkbox"/> Flush <input checked="" type="checkbox"/> Stick-up	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
197.0					End of Boring at 197.0 'bgs.		
198							
199							
200							
201							
202							
203							
204							
205							
206							
207							
208							
209							
210							
211							
212							
213							
214							
215							
216							

Draft Final -
Pending Final
Survey 4/16/20

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery, blue water table symbol represents depth to water measurement during the first VAS interval

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\SMCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\04.16.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 04/16/20 16:42