

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
0					(+0.3 - 1.5') Surface completion		(+0.3 - 1.5') 5 bags Note: 2.5 x 2.5 ft concrete pad with 18 diameter lockable vault, King Kon-Crete 4000 PSI
1					(0.1 - 173.2') 2" PVC Sch 80 Casing		
2					(1.5 - 4.0') Portland Cement 5% Bentonite Type I, II and V with Enviroplug	(1.5 - 4.0') 13.9 gallons	(1.5 - 4.0') 8 gallons (58%) Note: Grout seal, used <20% of the calculated volume due to formation collapse.
3			NR		(4.0 - 8.0') Bentonite seal chips Puregold medium chips	(4.0 - 8.0') 4.12 bags	(4.0 - 8.0') 15 bags (364%) Note: Installed due to some formation collapse, which shifted the well casing to side of the borehole, well checked no obstruction was observed. Used >20% of the calculated volume to fill void.
4					(0.0 - 8.0') 12" Borehole		
5		Topock - Fluvial Deposits	SW-SM		(9.5 - 10.5') Centralizer		
6					(8.0 - 13.0') Portland Cement 5% Bentonite Type I, II and V with Enviroplug	(8.0 - 13.0') 19.8 gallons	(8.0 - 13.0') 70 gallons (354%) Note: Grout seal, used >20% of the calculated volume due to potential voids forming during drilling and potential grout migration.
7					(8.0 - 197.6') 10" Borehole		
8			NR		(13.0 - 37.1') Portland Cement 5% Bentonite Type I, II and V with Enviroplug	(13.0 - 37.1') 95.4 gallons	(13.0 - 37.1') 200 gallons (210%) Note: Grout seal, used >20% of the calculated volume due to potential voids forming during drilling and potential grout migration.
9		Topock - Fluvial Deposits	SW-SM				
10							
11							
12							
13							
14							
15							
16							
17							
18		Topock - Fluvial Deposits	SW-SM				
19							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E TOPOCK DRAFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume		
20		Topock - Fluvial Deposits	GW-GM		(+0.0 - 112.0') 2" PVC Sch 80 Casing				
21			GW-GM		(0.1 - 173.2') 2" PVC Sch 80 Casing				
22									
23									
24									
25									
26									
27									
28		Topock - Fluvial Deposits	SW-SM		(13.0 - 37.1') Portland Cement 5% Bentonite Type I, II and V with Enviroplug	(13.0 - 37.1') 95.4 gallons	(13.0 - 37.1') 200 gallons (210%) Note: Grout seal, used >20% of the calculated volume due to potential voids forming during drilling and potential grout migration.		
29							(8.0 - 197.6') 10" Borehole		
30									
31									
32									
33									
34									
35					(34.5 - 35.5') Centralizer				
36									
37									
38		Topock - Fluvial Deposits	SM		(37.1 - 46.0') Bentonite seal chips Puregold/Halliburton medium chips	(37.1 - 46.0') 6.54 bags	(37.1 - 46.0') 24 bags (367%) Note: Seal above high solids grout, used >20% due to chips potentially settling into high solids grout.		
39									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK_TOPOCK DRAFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT_11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
40		Topock - Fluvial Deposits	SM		(+0.0 - 112.0') 2" PVC Sch 80 Casing		
41					(0.1 - 173.2') 2" PVC Sch 80 Casing		
42		Topock - Alluvium Deposits	GM		(37.1 - 46.0') Bentonite seal chips Puregold/Halliburton medium chips	(37.1 - 46.0') 6.54 bags	(37.1 - 46.0') 24 bags (367%) Note: Seal above high solids grout, used >20% due to chips potentially settling into high solids grout.
43							
44							
45							
46							
47		Topock - Alluvium Deposits	GM		(8.0 - 197.6') 10" Borehole		
48							
49							
50							
51							
52							
53		Topock - Alluvium Deposits	GW		(46.0 - 94.3') Aqua Guard High Solids Bentonite Grout	(46.0 - 94.3') 191.2 gallons	(46.0 - 94.3') 228 gallons (119%) Note: Annular seal across the screen intervals of the wells in the MW-84s borehole.
54	MW-M-VAS-52-57 (28 ppb) 3/28/2019 11:10						
55							
56							
57							
58							
59			SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\SMC\GRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume	
60		Topock - Alluvium Deposits	SM		(+0.0 - 112.0') 2" PVC Sch 80 Casing			
61		Topock - Alluvium Deposits	GM					
62		Topock - Alluvium Deposits	GM					
63		Topock - Alluvium Deposits	SM					
64		Topock - Alluvium Deposits	SM		(64.5 - 65.5') Centralizer			
65		Topock - Alluvium Deposits	SM					
66		Topock - Alluvium Deposits	GM					
67		Topock - Alluvium Deposits	GM					
68		Topock - Alluvium Deposits	GM					
69		Topock - Alluvium Deposits	GM					
70		Topock - Alluvium Deposits	GM		(46.0 - 94.3') Aqua Guard High Solids Bentonite Grout	(8.0 - 197.6') 10" Borehole	(46.0 - 94.3') 191.2 gallons	(46.0 - 94.3') 228 gallons (119%) Note: Annular seal across the screen intervals of the wells in the MW-84s borehole.
71		Topock - Alluvium Deposits	GM					
72		Topock - Alluvium Deposits	GM					
73		Topock - Alluvium Deposits	SW-SM					
74	MW-M-VAS-72-77 (<0.033 U ppb) 3/29/2019 14:01	Topock - Alluvium Deposits	SW-SM					
75		Topock - Alluvium Deposits	SW-SM					
76		Topock - Alluvium Deposits	SW-SM					
77		Topock - Alluvium Deposits	SW-SM					
78		Topock - Alluvium Deposits	GM					
79		Topock - Alluvium Deposits	GM					
		Topock - Alluvium Deposits	SW-SM					

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK TOPOCK DRAFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
80		Alluvium Deposits	SW-SM		(+0.0 - 112.0') 2" PVC Sch 80 Casing		
81		Topock - Alluvium Deposits	ML				
82		Topock - Alluvium Deposits	GW-GM				
83		Topock - Alluvium Deposits	GW-GM				
84		Topock - Alluvium Deposits	GW-GM				
85		Topock - Alluvium Deposits	SM				
86		Topock - Alluvium Deposits	SM				
87		Topock - Alluvium Deposits	SM		(46.0 - 94.3') Aqua Guard High Solids Bentonite Grout	(46.0 - 94.3') 191.2 gallons	(46.0 - 94.3') 228 gallons (119%) Note: Annular seal across the screen intervals of the wells in the MW-84s borehole.
88		Topock - Alluvium Deposits	SM				
89		Topock - Alluvium Deposits	SM				
90		Topock - Alluvium Deposits	SM				
91		Topock - Alluvium Deposits	SM				
92		Topock - Alluvium Deposits	SM				
93		Topock - Alluvium Deposits	SM				
94		Topock - Alluvium Deposits	SM				
95		Topock - Alluvium Deposits	ML		(94.3 - 96.3') Cemex #3 MESH (8x20) Lapis Lustré Sand	(94.3 - 96.3') 2.1 bags	(94.3 - 96.3') 6 bags (286%) Note: Installed because driller were concerned about bentonite swelling in casing overnight placed sand in casing and open borehole. Used >20% of the calculated volume due to a potential void.
96		Topock - Alluvium Deposits	ML				
97		Topock - Alluvium Deposits	SM				
98		Topock - Alluvium Deposits	SM		(96.3 - 106.9') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(96.3 - 106.9') 9 buckets	(96.3 - 106.9') 9.5 buckets (106%) Note: Intermediate seal
99		Topock - Alluvium Deposits	SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume		
100			SM		(99.5 - 100.5') Centralizer				
101		Topock - Alluvium Deposits	ML		(+0.0 - 112.0') 2" PVC Sch 80 Casing				
102									
103					(96.3 - 106.9') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(96.3 - 106.9') 9 buckets	(96.3 - 106.9') 9.5 buckets (106%) Note: Intermediate seal		
104		Topock - Alluvium Deposits	SM						
105									
106									
107									
108	MW-M-VAS-107-112 (<0.033 U ppb) 3/30/2019 13:59	Topock - Alluvium Deposits	SM						
109									
110									
111									
112					(112.0 - 132.0') 2" Sch 80 PVC (20-slot) Screen				
113					(106.9 - 136.0') Cemex #3 MESH (8x20) Lapis Lustre Sand	(106.9 - 136.0') 30.2 bags	(106.9 - 136.0') 35 bags (116%) Note: Filter pack		
114									
115									
116		Topock - Alluvium Deposits	GM						
117									
118									
119									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DATA\DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GPJ 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
120		Topock - Alluvium Deposits	GM		(112.0 - 132.0') 2" Sch 80 PVC (20-slot) Screen		
121					(0.1 - 173.2') 2" PVC Sch 80 Casing		
122		Topock - Alluvium Deposits	SM				
123							
124		Topock - Alluvium Deposits	GW-GM				
125							
126							
127		Topock - Alluvium Deposits	GM		(106.9 - 136.0') Cemex #3 MESH (8x20) Lapis Lustre Sand	(106.9 - 136.0') 30.2 bags	(106.9 - 136.0') 35 bags (116%) Note: Filter pack
128							
129							
130					(8.0 - 197.6') 10" Borehole		
131							
132							
133		Topock - Alluvium Deposits	GM		(132.5 - 133.5') Centralizer		
134					(132.0 - 134.4') Sump and PVC End Cap		
135							
136							
137							
138					(136.0 - 163.0') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(136.0 - 163.0') 23.8 buckets	(136.0 - 163.0') 25 buckets (105%) Note: Intermediate seal
139							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume	
140		Topock - Alluvium Deposits	GM					
141								
142								
143								
144		Topock - Alluvium Deposits	ML					
145								
146								
147								
148		Topock - Alluvium Deposits	SM		(136.0 - 163.0') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(8.0 - 197.6') 10" Borehole	(136.0 - 163.0') 23.8 buckets	(136.0 - 163.0') 25 buckets (105%) Note: Intermediate seal
149	MW-M-VAS-147-152 (<0.17 U ppb) 3/31/2019 15:21							
150								
151								
152								
153								
154								
155		Topock - Alluvium Deposits	GM					
156								
157								
158								
159								

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
160		Topock - Alluvium Deposits	GM		(0.1 - 173.2') 2" PVC Sch 80 Casing		
161					(136.0 - 163.0') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(136.0 - 163.0') 23.8 buckets	(136.0 - 163.0') 25 buckets (105%) Note: Intermediate seal
162							
163							
164		Topock - Alluvium Deposits	SM				
165							
166							
167							
168							
169							
170		Topock - Alluvium Deposits	GM		(8.0 - 197.6') 10" Borehole		
171					(163.0 - 197.6') Cemex #3 MESH (8x20) Lapis Lustre Sand	(163.0 - 197.6') 38.2 bags	(163.0 - 197.6') 42 bags (110%) Note: Filter pack
172							
173		Topock - Alluvium Deposits	GM				
174	MW-M-VAS-172-177 (<0.033 U ppb) 4/2/2019 14:57				(173.2 - 193.2') 2" Sch 80 PVC (20-slot) Screen		
175							
176							
177		Topock - Alluvium Deposits	GM				
178							
179							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
180		Topock - Alluvium Deposits	GM		(173.2 - 193.2') 2" Sch 80 PVC (20-slot) Screen		
181							
182							
183							
184							
185							
186							
187							
188							
189					(163.0 - 197.6') Cemex #3 MESH (8x20) Lapis Lustre Sand	(8.0 - 197.6') 10" Borehole	(163.0 - 197.6') 38.2 bags (163.0 - 197.6') 42 bags (110%) Note: Filter pack
190							
191							
192	MW-M-VAS-190-195 (<0.17 U ppb) 4/10/2019 16:35	Topock - Alluvium Deposits	GM				
193							
194							
195		Topock - Alluvium Deposits	SM		(193.7 - 194.7') Centralizer		
196		Topock - Alluvium Deposits	GM		(193.2 - 195.5') Sump and PVC End Cap		
197							
198							
199					(197.6 - 209.5') Bentonite seal chips Halliburton Holeplug 3/8" chips	(197.6 - 211.0') 6" Borehole	(197.6 - 209.5') 3.4 bags (197.6 - 209.5') 3 bags (88%) Note: Decommissioned rathole, during reaming drilled out 0.6 ft of seal.

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started: 04/30/2019	Surface Elevation: 501.27 ft amsl	Well ID: MW-84-132, MW-84-193
Date Completed: 07/30/2019	Shallow Well Elevation: 501.26 ft amsl	
Drilling Co.: Cascade	Deep Well Elevation: 501.18 ft amsl	Client: PG&E
Drilling Method: Sonic Drilling	Northing (NAD83): 2102363.81	Project: Final GW Remedy Phase 1
Driller Name: Tyler Alymer	Easting (NAD83): 7614866.21	Location: PG&E Topock, Needles, California
Drilling Asst: C. Winland/J. Candelaria	Borehole Diameter: 4-12 inches	
Logger: C. Bonessi/R. Moniz	Static Water Level: See Log for Depths	Project Number: RC000753.0051
Editor: Sean McGrane	Development End Date: 6/15/2019	
Total Depth: 216 ft bgs	Well Completion: <input checked="" type="checkbox"/> Flush <input type="checkbox"/> Stick-up <input type="checkbox"/> To Be Completed in Well Vault	

Depth (ft)	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Well Construction	Calculated Material Volumes	Material Volumes Installed Note: percentages are the actual volume vs the calculated volume
200		Topock - Alluvium Deposits	GM		(197.6 - 209.5') Bentonite seal chips Halliburton Holeplug 3/8" chips	(197.6 - 209.5') 3.4 bags	(197.6 - 209.5') 3 bags (88%) Note: Decommissioned rathole, during reaming drilled out 0.6 ft of seal.
201							
202	--no sample-- (Interval did not produce.) 4/10/2019 12:28						
203		Topock - Bedrock - metadiorite			(197.6 - 211.0') 6" Borehole		
204							
205							
206							
207							
208							
209		Topock - Bedrock - metadiorite			(209.5 - 216.0') Bentonite seal pellets Pel-Plug (TR30) 3/8"	(209.5 - 216.0') 1.2 buckets	(209.5 - 216.0') 1 buckets (83%) Note: Decommissioned rathole
210							
211							
212							
213							
214							
215							
216							
217					End of Boring at 216.0 ft bgs.		
218							
219							

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: solid blue and hollow blue water table marks represent depth to water (ft. bgs.) measured post development for the shallow well and deep well respectively; installed in MW-84d

WELL CONSTRUCTION DETAILS_PG&E_TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E_TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ_TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:31

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
1							(0.0 - 8.0') No recovery (NR); and cleared for utility clearance to 1 foot bgs, ~2 foot boulder encountered had to used rig to break boulder loose, drilled to 8 ft. bgs with no core collected.	(0.0 - 8.0') Added 10 gallons of water to hydrate bentonite mud tub seal.	(0.0 - 37.0') No water used
2									
3	0								
4					NR				
5									
6	0								
7									
8									
9				Topock - Fluvial Deposits	SW-SM		(8.0 - 10.5') Topock - Fluvial Deposits; Well graded sand with silt and gravel (SW-SM); light olive brown (2.5Y 5/4); very fine grained to very coarse grained, subangular to subround; some granules to very large pebbles, subangular to subround; trace subangular to subround; trace silt; trace clay; dry; some moisture present due to hydration of bentonite	(8.0 - 32.0') Soft drilling, formation collapsing after every run.	
10		No Sieve Samples Collected							
11							(10.5 - 17.0') No recovery (NR)		
12									
13	24				NR				
14									
15									
16									
17									
18				Topock - Fluvial Deposits	SW-SM		(17.0 - 19.5') Topock - Fluvial Deposits; Well graded sand with silt and gravel (SW-SM); light olive brown (2.5Y 5/4); very fine grained to very coarse grained, subangular to subround; some granules to very large pebbles, subangular to subround; trace subangular to subround; trace silt; trace clay; dry; some moisture present due to hydration of bentonite		
19	120								
20					GW-GM		(19.5 - 27.0') Topock - Fluvial Deposits; Well graded gravel with		

Final 11/20/20

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started: 03/20/2019	Surface Elevation: 501.27 ft amsl	Boring No.: MW-84d
Date Completed: 04/30/2019	Northing (NAD83): 2102363.81	
Drilling Co.: Cascade	Easting (NAD83): 7614866.21	Client: PG&E
Drilling Method: Sonic Drilling	Total Depth: 216 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type: Boart Longyear Track	Borehole Diameter: 4-12 inches	Location: PG&E Topock, Needles, California
Driller Name: Tyler Alymer	Depth to First Water: 46.4 ft bgs	Project Number: RC000753.0051
Drilling Asst: C. Winland/J. Candelaria	Sampling Method: 4-8 inch x 10 ft. Core Barrel	
Logger: C. Bonessi/R. Moniz	Sampling Interval: Continuous	
Editor: Sean McGrane	Converted to Well: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
21	120			Topock - Fluvial Deposits	GW-GM		silt and sand (GW-GM); light olive brown (2.5Y 5/4); granules to very large pebbles, subangular to subround; some very fine to very coarse grained sand, subangular to subround; trace subangular to subround; trace silt; trace clay; dry		
22									
23									
24									
25	60	No Sieve Samples Collected		Topock - Fluvial Deposits	SW-SM		(27.0 - 38.0') Topock - Fluvial Deposits; Well graded sand with silt and gravel (SW-SM); light olive brown (2.5Y 5/4); very fine grained to very coarse grained, subangular to subround; some granules to very large pebbles, subangular to subround; little silt; trace subangular to subround; dry		
26									
27									
28									
29									
30									
31	60			Topock - Fluvial Deposits	SM		(38.0 - 42.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); strong brown (7.5YR 5/6); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular to subangular; some silt; little subangular; dry to moist; weak cementation; iron oxide staining; cobbles composed of sandstone/breccia	(32.0 - 37.0') Hard drilling due to boulder. Borehole collapsing after each clean out run. Rod broke while doing clean out at 35 ft bgs.	(37.0 - 42.0') Drill rods chattering, change geologist from CB to RM. (37.1') Change in geologist from CB to RM.
32									
33									
34									
35	60			Topock - Fluvial Deposits	SM		(38.0 - 42.0') Topock - Fluvial Deposits; Silty sand with gravel (SM); strong brown (7.5YR 5/6); very fine grained to very coarse grained, angular to subangular; some granules to very large pebbles, angular to subangular; some silt; little subangular; dry to moist; weak cementation; iron oxide staining; cobbles composed of sandstone/breccia	(37.0 - 205.0') No used	5 gallons of water used; 5 gallons of water recovered; 0 gallons of water lost
36									
37									
38									
39									
40									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid		
41	60			Topock - Fluvial Deposits	SM						
42				Topock - Alluvium Deposits	GM		(42.0 - 47.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); strong brown (7.5YR 5/6); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subround; little; little silt; moist; weak cementation; iron oxide staining; Interbedded silty units, cobbles composed of sandstone/breccia	(44.0 - 47.0') Drill rods chattering			
43							(47.0 - 52.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); dark yellowish brown (10YR 4/4); granules to very large pebbles, angular to subround; some silt; little; little very fine to medium grained sand, angular to subround; little clay; moist to wet	(48.0') Approximate depth to water table.			
44				Topock - Alluvium Deposits	GM		(51') brown (7.5YR 5/4); little silt; trace clay; moist; weak cementation; iron oxide staining; increase in granules and pebbles, decrease in sand				
45											
46											
47		No Sieve Samples Collected		Topock - Alluvium Deposits	GW		(52.0 - 59.0') Topock - Alluvium Deposits; Well graded gravel with sand (GW); strong brown (7.5YR 5/6); granules to very large pebbles, angular to subround; some very fine to very coarse grained sand, angular to subround; little; trace silt; wet; weak cementation; iron oxide staining	(52.0 - 57.0') Drill rods chattering, driller suggest water table has been encountered.			
48											
49											
50											
51	120						(58') moist	(57.0 - 67.0') Hard drilling and became harder at 61 ft.			
52			MW-M-VAS-52-57 (28 ppb) 3/28/2019 11:10								
53											
54											
55											
56											
57											
58	114										
59											
60				Topock - Alluvium Deposits	SM		(59.0 - 61.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (10YR 5/2); very fine grained to medium grained; some silt; little granules to very large pebbles, angular to				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
61	114			Topock - Alluvium Deposits	SM		subround; little clay; trace angular to subround; moist		
62				Topock - Alluvium Deposits	GM		(61.0 - 63.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); light brownish gray / pale yellowish brown (10YR 6/2); granules to very large pebbles, subangular to subround; little very fine to medium grained sand, subangular to subround; little silt; trace clay; dry		
63				Topock - Alluvium Deposits	SM		(63.0 - 67.0') Topock - Alluvium Deposits; Silty sand (SM); brown (7.5YR 4/3); very fine grained to medium grained, angular to subround; little granules to very large pebbles, angular to subround; little silt; trace angular to subround; trace clay; dry; weak cementation; iron oxide staining		
64	120	No Sieve Samples Collected		Topock - Alluvium Deposits	SM		(65'); potential caliche deposits in sediments		
65				Topock - Alluvium Deposits	GM		(67.0 - 75.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 4/3); granules to very large pebbles, angular to subround; some angular to subround; some very fine to very coarse grained sand, angular to subround; little silt; moist	(67.0 - 77.0') Softer drilling	
66				Topock - Alluvium Deposits	GM		(69.5') brown (10YR 5/3); some silt; little angular to subround; little clay; moist; weak cementation		
67				Topock - Alluvium Deposits	GM		(70.5'); dry; potential caliche deposits in sediments		
68				Topock - Alluvium Deposits	GM		(71'); moist		
69	120			Topock - Alluvium Deposits	GM		(72'); wet; lens of green staining		
70				Topock - Alluvium Deposits	SW-SM		(75.0 - 78.0') Topock - Alluvium Deposits; Well graded sand with gravel (SW-SM); weak red (2.5YR 5/2); very fine grained to coarse grained, angular to subround; little granules to very large pebbles, angular to subround; little silt; trace angular to subangular; wet		
71				Topock - Alluvium Deposits	GM		(78.0 - 79.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); weak red (2.5YR 4/2); granules to very large pebbles, angular to subround; little angular to subround; little very fine to very coarse grained sand, angular to subround; little silt; little clay; wet		
72	120			Topock - Alluvium Deposits	SW-SM		(79.0 - 80.0') Topock - Alluvium Deposits; Poorly graded sand with	(77.0 - 87.0') Soft drilling, lost core 82 to 87 ft downhole.	
73				Topock - Alluvium Deposits	GM				
74				Topock - Alluvium Deposits	SW-SM				
75	120			Topock - Alluvium Deposits	GM				
76				Topock - Alluvium Deposits	SW-SM				
77				Topock - Alluvium Deposits	SW-SM				
78	120			Topock - Alluvium Deposits	GM				
79				Topock - Alluvium Deposits	SW-SM				
80				Topock - Alluvium Deposits	SW-SM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E: TOPOCK - C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
81	120			Topock - Alluvium Deposits	ML		silt and gravel (SW-SM); weak red (2.5YR 5/2); medium grained to very coarse grained, angular to subround; and granules to very large pebbles, angular to subround; little silt; trace angular to subangular; wet		
82				Topock - Alluvium Deposits	GW-GM		(80.0 - 82.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 4/3); low plasticity; some very fine to medium grained sand, angular to subround; little granules to very large pebbles, angular to subangular; little clay; moist to wet; medium stiff		
83				Topock - Alluvium Deposits			(82.0 - 84.0') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); weak red (2.5YR 5/2); granules to very large pebbles, angular to subround; some medium to very coarse grained sand, angular to subround; little angular to subangular; little silt; wet		
84	120	No Sieve Samples Collected		Topock - Alluvium Deposits	SM		(84.0 - 95.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/3); medium grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; little angular to subround; trace clay; moist; interbedded with layers of silty gravel, with sand and gravelly silt with sand	(87.0 - 97.0') Soft drilling, recovered 82 to 87 ft core.	
85									
86									
87									
88	120			Topock - Alluvium Deposits	ML		(91.7'); dry, with lenses of potential caliche in sediments and weak cementation		
89									
90									
91	120			Topock - Alluvium Deposits	ML		(95.0 - 97.0') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 4/3); low plasticity; some medium to very large pebbles, angular to subround; little granules to very large pebbles, angular to subround; little angular to subround; trace clay; moist		
92									
93	120			Topock - Alluvium Deposits	SM		(97.0 - 100.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/3); medium grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace angular to subround; trace clay; moist; interbedded with layers of silty gravel with sand and gravelly silt with sand	(97.0 - 127.0') Formation collapse during clean out drilling with 10 inch casing, soft drilling (97' to 107'), slightly rough drilling	
94									
95									
96	120			Topock - Alluvium Deposits	ML				
97									
98	120			Topock - Alluvium Deposits	SM				
99									
100									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
101	120			Topock - Alluvium Deposits	ML		(100.0 - 103.5') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (7.5YR 4/3); low plasticity; some very fine to medium grained sand, angular to subround; little granules to very large pebbles, angular to subround; trace angular to subround; trace clay; moist; weak cementation; iron oxide staining (101'); dry; with lens of potential caliche in sediments and weak cementation	(107' to 109'), soft drilling (109' to 117'), soft drilling lost 5 feet of sample downhole (117' to 127') with 6 inch casing.	
102				Topock - Alluvium Deposits	SM		(103.5 - 105.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); grayish brown (2.5Y 5/2) and brown (7.5YR 4/3); medium grained to very coarse grained; little granules to very large pebbles, angular to subround; little silt; trace angular to subround; trace clay; moist; interbedded color changes (104'); to 104.5', wet silty gravel lens		
103				Topock - Alluvium Deposits	SM		(105.0 - 114.5') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/3); medium grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace angular to subround; trace clay; moist; interbedded layers with poor to moderate gradation (106'); to 107', dry with green staining (107'); to 109.5', wet		
104	108	No Sieve Samples Collected	MW-M-VAS-107-112 (<0.033 U ppb) 3/30/2019 13:59	Topock - Alluvium Deposits	SM			(107.0') During reaming with 10-inch casing flapper bit broke, getting poor recovery. Driller thinks material is getting pushed into formation or falling down 6-inch Rathole.	
105				Topock - Alluvium Deposits	GM		(114.5 - 122.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 4/3); granules to very large pebbles, angular to subround; some very fine to medium grained sand, angular to subangular; some silt; little angular to subround; trace clay; moist; green staining		
106				Topock - Alluvium Deposits	GM				
107				Topock - Alluvium Deposits	GM		(118.2'); sand lens at 118.2 ft		
108	120			Topock - Alluvium Deposits	GM				
109				Topock - Alluvium Deposits	GM				
110				Topock - Alluvium Deposits	GM				
111				Topock - Alluvium Deposits	GM				

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\SMC\GRAND\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
121	120			Topock - Alluvium Deposits	GM	(120.5'); weathered metamorphic cobble, black and green staining around cobble			
122				Topock - Alluvium Deposits	SM	(122.0 - 124.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); dark grayish brown / dark yellowish brown (10YR 4/2); very fine grained to very coarse grained, angular to subangular; little granules to very large pebbles, angular to subangular; little silt; trace clay; wet			
123				Topock - Alluvium Deposits	GW-GM	(124.0 - 128.0') Topock - Alluvium Deposits; Well graded gravel with silt and sand (GW-GM); light olive brown (2.5Y 5/6); granules to very large pebbles, angular to subangular; some very fine to very coarse grained sand, angular to subangular; little silt; trace; wet; iron oxide staining; occasional sandier and siltier lenses			
124	60	No Sieve Samples Collected		Topock - Alluvium Deposits	GM	(126') brown (7.5YR 4/3); orange staining		(127.0 - 132.0') Soft drilling, recovered lost 5 feet of sample from drilling run (117' to 127').	
125						(127'); moist			
126				Topock - Alluvium Deposits	GM	(128.0 - 144.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); light olive brown (2.5Y 5/6); granules to very large pebbles, angular to subangular; little very fine to very coarse grained sand, angular to subangular; little silt; little clay; trace; gravel lens; moist			
127	90			Topock - Alluvium Deposits	GM	(131'); to 131.5' cobbles		(132.0 - 142.0') Rough drilling	
128						(132') brown (7.5YR 4/2)			
129							(133.5'); dry; with potential caliche in sediments and weak cementation		

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E-TOPOCK C:\USERS\SMC\GRAND\DOCUMENTS\PG&E-TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
141	90			Topock - Alluvium Deposits	GM				
142									
143									
144				Topock - Alluvium Deposits	ML		(144.0 - 144.5') Topock - Alluvium Deposits; Sandy silt with gravel (ML); brown (10YR 5/3); low plasticity; some very fine to medium grained sand, angular to subangular; trace granules to very large pebbles, angular to subround; wet; liquefied		
145									
146									
147	120			Topock - Alluvium Deposits	SM		(144.5 - 154.4') Topock - Alluvium Deposits; Silty sand with gravel (SM); brown (7.5YR 4/2) and brown (7.5YR 4/3); very fine grained to very coarse grained, angular to subround; some granules to very large pebbles, angular to subround; some silt; trace angular to subangular; trace clay; moist to wet; occasional gravelly and silty lenses 2in to 6in thick		
148									
149			MW-M-VAS-147-152 (<0.17 U ppb) 3/31/2019 15:21						
150		No Sieve Samples Collected							
151									
152									
153								(152.0 - 167.0') Soft drilling	
154									
155				Topock - Alluvium Deposits	GM		(154.4 - 166.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 4/2) and brown (7.5YR 4/3); granules to very large pebbles, angular to subround; some very fine to medium grained sand, angular to subround; some silt; little angular to subangular; moist to wet; iron oxide staining; occasional sand lens 2in to 6in thick		
156	180								
157							(157'); dry, with red and green staining		
158							(158'); moist		
159									
160									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\SMC\GRAND\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started: 03/20/2019	Surface Elevation: 501.27 ft amsl	Boring No.: MW-84d
Date Completed: 04/30/2019	Northing (NAD83): 2102363.81	
Drilling Co.: Cascade	Easting (NAD83): 7614866.21	Client: PG&E
Drilling Method: Sonic Drilling	Total Depth: 216 ft bgs	Project: Final GW Remedy Phase 1
Drill Rig Type: Boart Longyear Track	Borehole Diameter: 4-12 inches	Location: PG&E Topock, Needles, California
Driller Name: Tyler Alymer	Depth to First Water: 46.4 ft bgs	Project Number: RC000753.0051
Drilling Asst: C. Winland/J. Candelaria	Sampling Method: 4-8 inch x 10 ft. Core Barrel	
Logger: C. Bonessi/R. Moniz	Sampling Interval: Continuous	
Editor: Sean McGrane	Converted to Well: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
161	180			Topock - Alluvium Deposits	GM		(164'); moist to dry		
162									
163									
164									
165	No Sieve Samples Collected			Topock - Alluvium Deposits	SM		(166.5 - 170.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown (5YR 4/3); very fine grained to medium grained, angular to subround; some silt; little granules to very large pebbles, angular to subround; trace angular to subangular; trace clay; wet	(167.0 - 177.0') Soft drilling	
166									
167									
168									
169	120			Topock - Alluvium Deposits	GM		(170.0 - 176.5') Topock - Alluvium Deposits; Silty gravel with sand (GM); brown (7.5YR 4/3) with brown (7.5YR 5/2); granules to very large pebbles, angular to subround; some angular to subangular; little very fine to medium grained sand, angular to subangular; little silt; moist		
170									
171									
172									
173	180			Topock - Alluvium Deposits	GM		(172'); dry; to 176.5', with red and green staining, potential caliche in sediments and weak cementation		
174									
175									
176									
177	180			Topock - Alluvium Deposits	GM		(176.5 - 192.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4); granules to small pebbles, angular to subangular; some very fine to very coarse grained sand; little medium to very large pebbles, angular to subangular; little silt; trace clay; wet to moist; interbedded GW and GM with occasional well graded sand with gravel lenses 2in to 6 in thick	(177.0 - 192.0') Soft drilling	
178									
179									
180									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\MCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
181	180	No Sieve Samples Collected		Topock - Alluvium Deposits	GM				
182									
183									
184									
185									
186									
187	120	MW-M-VAS-190-195 (<0.17 U ppb) 4/10/2019 16:35		Topock - Alluvium Deposits	GM		(192.0 - 195.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4) trace reddish brown (2.5YR 4/4); granules to large pebbles, angular to subround; some very fine to very coarse grained sand, angular to subround; little silt; little clay; trace; wet; weak cementation	(192.0') Change in geologist to CB.	
188									
189									
190									
191	120	MW-M-VAS-190-195 (<0.17 U ppb) 4/10/2019 16:35		Topock - Alluvium Deposits	SM		(195.0 - 196.0') Topock - Alluvium Deposits; Silty sand with gravel (SM); reddish brown / moderate brown (5YR 4/4); very fine grained to coarse grained, angular to subround; some silt; little granules to large pebbles, angular to subround; trace clay; wet	(196.0 - 203.0') Rough drilling	
192									
193									
194									
195	120	MW-M-VAS-190-195 (<0.17 U ppb) 4/10/2019 16:35		Topock - Alluvium Deposits	GM		(196.0 - 205.0') Topock - Alluvium Deposits; Silty gravel with sand (GM); reddish brown / moderate brown (5YR 4/4) trace reddish brown (2.5YR 4/4); granules to large pebbles, angular to subround; some very fine to very coarse grained sand, angular to subround; little silt; little clay; trace; wet; weak cementation		
196									
197									
198									
199									
200									

Final 11/20/20

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E-TOPOCK-C:\USERS\MCGRANE\DOCUMENTS\PG&E-TOPOCK\DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GPJ 11/20/20 00:52

Date Started:	03/20/2019	Surface Elevation:	501.27 ft amsl	Boring No.: MW-84d	
Date Completed:	04/30/2019	Northing (NAD83):	2102363.81		
Drilling Co.:	Cascade	Easting (NAD83):	7614866.21	Client:	PG&E
Drilling Method:	Sonic Drilling	Total Depth:	216 ft bgs	Project:	Final GW Remedy Phase 1
Drill Rig Type:	Boart Longyear Track	Borehole Diameter:	4-12 inches	Location:	PG&E Topock, Needles, California
Driller Name:	Tyler Alymer	Depth to First Water:	46.4 ft bgs	Project Number:	RC000753.0051
Drilling Asst:	C. Winland/J. Candelaria	Sampling Method:	4-8 inch x 10 ft. Core Barrel		
Logger:	C. Bonessi/R. Moniz	Sampling Interval:	Continuous		
Editor:	Sean McGrane	Converted to Well:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		

Depth (ft)	Recovery (in)	Sieve Sample ID	Groundwater Sample ID	Geologic Formation	USCS Code	USCS Class	Soil Description	Drilling Notes	Drilling Fluid
201	120		--no sample-- (Interval did not produce.) 4/10/2019 12:28	Topock - Alluvium Deposits	GM				
202									
203									
204									
205	72	No Sieve Samples Collected		Topock - Bedrock - metadiorite			(205.0 - 208.0') Topock - Bedrock - metadiorite; grayish brown (2.5Y 5/2) with greenish gray (10Y 6/1); moist; moderate cementation; weathered metadiorite	(205.0 - 211.0') Very tight drilling, locked up core barrel at 208 ft. bgs.	(205.0 - 211.0') 600 gallons of water used; 600 gallons of water recovered; 0 gallons of water lost
206									
207				Topock - Bedrock - metadiorite			(208.0 - 216.0') Topock - Bedrock - metadiorite; grayish brown (2.5Y 5/2) with greenish gray (10Y 6/1); dry; moderate cementation; bedrock pulverized during drilling	(211.0 - 216.0') Rough drilling, hard, rods and head chattering.	(211.0 - 216.0') No used
208									
209									
210									
211	48			Topock - Bedrock - metadiorite			(211'); to 213 ft. moist, potential slough based on QC geologist review of time between runs, notes, and photos		
212									
213				Topock - Bedrock - metadiorite			(214'); to 214.2 silt lens potentially pulverized metadiorite		
214									
215									
216									
End of Boring at 216.0 ft bgs.									
217									
218									
219									
220									

Abbreviations: USCS = Unified Soil Classification System, ft = feet, bgs = below ground surface, amsl = above mean sea level, GW = groundwater, ppb = parts per billion, U = not detected above the laboratory reporting limit, NR = no recovery; Notes: depth to water measured during the first VAS interval; apparent partial recoveries can be the result of potential compaction of sediments in the core bag; wells MW-84-132, MW-84-193 installed in borehole

SOIL BORING LOG: PG&E TOPOCK C:\USERS\SMCGRANE\DOCUMENTS\PG&E TOPOCK\DRIFT BORING LOGS\GINT FILES\11.19.20\TOPOCK DATABASE FOR PLOG.GPJ TOPOCK DATA TEMPLATE FOR PLOG.GDT 11/20/20 00:52